



## About Samsung

Samsung inspires the world and shapes the future with transformative ideas and technologies. The company is redefining the worlds of TVs, smartphones, wearable devices, tablets, digital appliances, network systems, and memory, system LSI, foundry and LED solutions. For the latest news, please visit the Samsung Newsroom at <http://news.samsung.com>.

## For more information

For more information about Samsung Interactive Display, SMART LED Signage, SMART Signage, and Business Monitor, visit [www.samsung.com/business](http://www.samsung.com/business) or [www.samsung.com/displaysolutions](http://www.samsung.com/displaysolutions)

Copyright © 2018 Samsung Electronics Co. Ltd. All rights reserved. Samsung is a registered trademark of Samsung Electronics Co. Ltd. Specifications and designs are subject to change without notice. Non-metric weights and measurements are approximate. All data were deemed correct at time of creation. Samsung is not liable for errors or omissions. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognized and acknowledged.

Samsung Electronics Co., Ltd.  
416, Maetan 3-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do 443-772, Korea  
2018-11  
[www.samsung.com](http://www.samsung.com)

# Samsung DooH Display Solutions

Discovering new opportunities for advertisement through state-of-the-art-technology

LED Signage | Outdoor Signage | SMART Signage | Interactive Display | MagicINFO Solution

**SAMSUNG**

**SAMSUNG**




## The Samsung DooH Display Solution delivers real-time dynamic messaging experiences that enable


**Merchandising:** At retail stores, banks and even restaurants, Samsung DooH Display Solution highlight goods and services to increase sales and build brand awareness. Many popular clothing stores feature immersive branded videos with music, text and interviews in their retail locations.

**Advertising:** Across transportation venues, theaters and high-traffic public spaces, Samsung DooH Display Solutions deliver interactive advertising content for multiple brands, increasing advertising revenue. Travelers waiting at airports view diverse advertising content, supplied by a network operator, delivering visually engaging ad content to captive audiences.


**Informational:** For hospitality venues, healthcare facilities and educational campuses, Samsung DooH Display Solutions deliver rich digital informational and entertainment content that enhance customer experiences. An example of these immersive viewing experiences is the digital signage and content in hospital waiting rooms that feature health news and diet tips.



Merchandising



Advertising



Informational

# What Samsung offers


Samsung, the #1 global digital signage solution provider, offers a comprehensive portfolio of display solutions for a wide array of indoor and outdoor applications including billboards, street furniture, entrance & moving walk displays and ad-case solutions.

## Way-finding

High-impact displays assist and guide guests and enhance the customer experience. Standalone signage and interactive displays can be placed in high-traffic areas with easy-to-find information to make shopping experiences more enjoyable and airports easier to navigate.

## Entrance & Moving walk

Indoor LEDs video walls encourage consumers to enter and browse. Retailers can display sale items, new product lines and provide incentives for pedestrians to come in and shop. The displays also help travelers quickly learn about top destinations or get a flavor for the region's culture. Service providers can direct passengers to transportation options, and theme parks can inform families of must-visit locations.



### Billboard

Vivid outdoor LEDs engage viewers and deliver compelling content. DooH displays reinvent the billboard experience for consumers with state-of-the-art technology, while brands gain a more absorbing connection with their customers.

### Street furniture / Bus shelter

Vibrant outdoor signage entertains and informs with dynamic ads. Waiting passengers are delivered visually engaging content from multiple brands, compelling brand interactions and purchases.

### Ad-case

Standalone signage entice visitors to watch, learn and interact anywhere – whether in a mall, airport or other venue. Compelling ad content can drive customers to a specific store or restaurant, or encourage visitor to scan a QR code and buy online.

# Billboard

## Delivering highly engaging advertising content

Vivid outdoor LEDs engage viewers and deliver compelling content. DooH displays reinvent the billboard experience for consumers with state-of-the-art technology, while brands gain a more absorbing connection with their customers.



# Street furniture / Bus shelter

## Capturing viewers and increasing advertising revenue

Vibrant outdoor signage entertains and informs with dynamic ads. Waiting passengers are delivered visually engaging content from multiple brands, compelling brand interactions and purchases.



## Outdoor LED signage: XPE series



### Superior image quality regardless of conditions

Samsung's XPE series LED signage delivers excellent image quality that captures audience eyes even in challenging environments. Through two-step in-depth calibration, enhanced image processing and an industry-best contrast ratio, the displays deliver accurate and consistent color quality content with a high refresh rate. The XPE series also is equipped to deter light interference, and produce bright images regardless of conditions.




### High reliability with proactive expert support

Each XPE series signage undergoes rigorous environmental testing to ensure uninterrupted performance. C3 Contamination and Ionograph testing deters circuit contamination and extends shelf-life. Complementary Climate and Humidity and Salt Fog Chamber exposure additionally ensures performance in variable weather conditions and wet and corrosive elements. In addition to enhanced durability, from inception to installation, Samsung makes the easy outdoor signage experience easy, providing round-the-clock service.




## Outdoor signage: OHF / OHN / OHN-D series



### Unsurpassable visibility

Samsung's outdoor signage allows for exceptional, consistent content delivery with maximum 3,300 nit brightness\* and 24/7 performance for outdoor display at airport. With a built-in dimming sensor, the display automatically adjusts the brightness based on the external lighting environment, saving operating expenses and power consumption.

\* Brightness varies by model.




### Resistant to outdoor elements

Samsung outdoor signage is verified to perform in outdoor settings. IP56-rated protection\*\* ensures the signage will withstand physical impact as well as dust\*\*\*, humidity or other outdoor elements that could affect the display.

\*\* Additional glass needed for kit type.


\*\*\* Ingress of dust is not entirely prevented, but will not accumulate in sufficient quantities to interfere with the satisfactory operation of the equipment.



# Entrance & Moving walk

## Enhancing customer experiences with rich digital content

Indoor LEDs video walls encourage consumers to enter and browse. Retailers can display sale items, new product lines and provide incentives for pedestrians to come in and shop. The displays also help travelers quickly learn about top destinations or get a flavor for the region's culture. Service providers can direct passengers to transportation options, and theme parks can inform families of must-visit locations.





## Indoor LED signage: IF series



### Showcase brilliant true-to-life imagery

Through in-depth color management, Samsung's IF series has the ability to preserve constant gradation of images, ensuring pictures are true-to-life. The display uses technology that is nearly twice as high as the standard LED, showcasing information and advertisement brilliantly. The IF series contains dynamic peaking technology that elevates images while removing interference from natural lighting.

-   
LED HDR
-   
Dynamic Peaking
-   
Color Management
-   
Fine-tune Uniformity



### A clean, hassle-free installation

A hook-based design allows IF Series to be mount screens in a single, smooth motion. This seamless installation eliminates gaps while keeping all front and rear components visible and accessible for quick-turn maintenance. The IF Series' compact, durable design also can withstand damage from natural events as strong as a Level 4 earthquake, while also meeting Americans with Disabilities Act (ADA) protrusion regulations.

-   
Direct Mount Kit
-   
Catwalk Space free
-   
Advanced Design
-   
Earthquake Durability

## Video wall display signage: UHF-E, VMR-U, UHF5 series



### Deeper visual impact with thin bezel

Samsung created the extreme narrow bezel video wall to be a robust display that is impactful to pedestrians moving through a mall, airport or other venue. The video wall's ultra slim bezel that yields a seamless picture across multiple screens. Samsung's video wall is a non-glare display that distributes light through the screen, while preserving the vivid pictures and original information.

-   
Narrow Bezel
-   
Non Glare
-   
Enhanced Uniformity
-   
High Contrast Ratio



### Securely stabilized in any configuration

Building a visually appealing video wall that is customizable to any malls, terminals, airports and stores and gives the freedom to design a distinctive display that is exclusive to them. The video wall attaches to a surface with wall mounts sized to dimensions of the video and hidden with no distractions. An easy to understand installation guide elevates steps during installation.

-   
Fine adjustment
-   
Slim depth
-   
Easy Installation
-   
24/7

# Ad-case

## Driving customer engagement and purchases

Standalone signage entice visitors to watch, learn and interact anywhere – whether in a mall, airport or other venue. Compelling ad content can drive customers to a specific store or restaurant, or encourage visitor to scan a QR code and buy online.



# Way-finding

## Informing and entertaining customers with interactive content

High-impact displays assist and guide guests and enhance the customer experience. Standalone signage and interactive displays can be placed in high-traffic areas with easy-to-find information to make shopping experiences more enjoyable and airports easier to navigate.



## QLED 8K signage: QPR-8K series



### Spectacular 33-million-pixel resolution

Samsung QLED 8K offers ground-breaking, super-high resolution, 4 times higher than 4K UHD content and 16 times higher than FHD. With more than 33 million pixels, QLED 8K provides exceptional depth and detail, resulting in a spectacularly immersive viewing experience in any business environment.



8K resolution



100% Color volume




Peak Brightness



Quantum HDR

## UHD signage: QMR/QBR series



### Intelligent UHD upscaling

Samsung's cutting-edge intelligent UHD upscaling technology performs edge restoration and noise reduction to deliver perfect UHD picture quality for advertisement, even with lower resolution content. This "future-proof" solution ensures best-in-class picture quality regardless of the original content resolution.

\*"Conventional" refers to the models that do not adopt UHD upscaling function.



Intelligent UHD engine



Noise Reduction



Edge Restoration



HDR+

## Interactive display: PMF-BC series



### Comfortable, multi-point capacitive touch communication

Through capacitive touch technology and a user-friendly design, Samsung's PMF-BC displays foster a comfortable, easy-to-navigate digital writing experience. The interactive displays can accommodate 10 Unique touch points\* while maintaining the smooth, familiar feel of analog board or pen-and-paper writing.

\*The number of available touch points varies depending on configuration. Connected external PCs provide the PMF-BC display with 10 touch points, while the integrated operating system supports two additional touch points.



Seamless Touch



Multi Touch



Fast Response time



Intuitive UI



### High reliability & convenient management

Samsung's PMF-BC displays are resilient and require little maintenance, yet are dependable and deliver content effortlessly. This display withstood extensive testing to validate its durability against dust, dirt, vandalism and other factors as these displays are typically used at transportation stations. Users are able to control the display, no matter their location, using infrared receivers, for continuous content.



Dust Resistant



Sunlight Resistant



High Reliability



Central IR

# Samsung's solutions and services

## Manage your display devices and contents comprehensively

Along with partners, Samsung provides intuitive management solutions that allow the users to have a great ability to manage and control all of the devices, creating and updating information easily and as needed.


- Ongoing content design
- Content management system
- Data integration
- Programming
- Network design & Integration
- Network monitoring



## Management solution: MagicINFO, SSSP solution

### MagicINFO solution

Samsung's comprehensive MagicINFO platform can remotely manage both hardware and software through one single-point management system. With this solution, users can conveniently create, schedule and deploy content across its entire digital signage network. MagicINFO enables content teams to update informational or advertising contents from any location at any time that creates greater user control from one central location. The platform also is compatible with a host of display types, ensuring the delivery of compelling content regardless of the operational framework.




### SSSP solution

For a Samsung Smart Signage Platform(SSSP) partner that has its own CMS solution, Samsung MagicINFO Remote Management Solution is a perfect fit for advanced needs. Samsung Remote Management Solution allows in-depth remote monitoring of the digital devices and eliminates the need for site visits or service calls. The Remote Management Solution platform synchronizes with users' CRM and provides a complete review of hardware and display content. Though its install package is the same with MagicINFO Server, there is a separate license key for Samsung's Remote Management Solution.



### Remote management solution

Thanks to Samsung MagicINFO Remote Management Solution, a SSSP Partner that has its own CMS solution can perform in-depth remote monitoring of the digital devices and eliminate the need for site visits or service calls.



# Specification

## LED signage

|         | Project | Pixel Pitch    | Diode Type                                       | Brightness <sup>(1)</sup><br>(*) Dynamic Peaking applied | Contrast Ratio                    | Certification               | Cabinet Size  | Weight   | Service <sup>(2)</sup>            | IP Rating  |
|---------|---------|----------------|--|--|-----------------------------------|-----------------------------|---|--|-----------------------------------|--|
| Indoor  | IFJ     | P1.2           | Surface Mount Device                             | 1,200 nit  | 4,000:1                           | EMC Class B, Safety 60950-1 | 806.4x453.6x76.7mm (LxHxD, per cabinet)   | 11.8kg/cabinet   | Front and Parts Rear              | IP20   |
|         | IFJ-E   | P1.2           | Surface Mount Device                             | 1,200 nit  | 4,000:1                           | EMC Class B, Safety 60950-1 | 806.4x453.6x76.7mm (LxHxD, per cabinet)   | 11.8kg/cabinet   | Front and Parts Rear              | IP20   |
|         | IFH     | P1.5, 2.0, 2.5 | Surface Mount Device                             | 1,600 nit (P1.5)<br>2,400 nit (P2.0, 2.5)                | 5,000:1                           | EMC Class A, Safety 60950-1 | 480x540x65mm (LxHxD, per cabinet)   | 5.8kg/cabinet  | Front and Rear                    | IP20   |
|         | IFH-E   | P1.5, 2.5      | Surface Mount Device                             | 1,200 nit (P1.5)<br>2,000 nit (P2.5)                     | 5,000:1                           | EMC Class A, Safety 60950-1 | 480x540x65mm (LxHxD, per cabinet)   | 5.8kg/cabinet  | Front and Rear                    | IP20   |
|         | IFH-D   | P2.5, 4.0, 6.0 | Surface Mount Device                             | 1,700 nit (P4.0)<br>1,800 nit (P6.0)                     | 5,000:1                           | EMC Class A, Safety 60950-1 | 480x720x65mm (LxHxD, per cabinet)   | 7.4kg/cabinet  | Front and Parts Rear              | IP20   |
| Outdoor | XPE     | P6, 8, 10      | Surface Mount Device                             | 7,500 nit  | 8,500:1 (P6)<br>10,000:1 (P8, 10) | EMC Class A, Safety 60950-1 | 203x203mm (LxH, per module) (P6)<br>264x297mm (LxH, per module) (P8)<br>330x165mm (LxH, per module) (P10)                     | 0.54kg/module (P6)<br>1kg/module (P8)<br>0.69kg/module (P10)     | Front Service and/or Rear Service | Silicone sealed (Module IP67, Cabinet IP65) (P6, P8)<br>Silicone sealed (IP65) (P10) |
|         | XAF     | P6, 8, 10, 16  | SMD2727 (P6)<br>SMD3535 (P8, 10)<br>DIP346 (P16) | 6,300 nit (P6, 8)<br>6,750 nit (P10)<br>7,700 nit (P16)  | 3,000:1                           | EMC Class A, Safety 60950-1 | 1152x864x142mm (LxH, per cabinet) (P6, 8)<br>960x960x142mm (LxH, per cabinet) (P10)<br>960x960x154mm (LxH, per cabinet) (P16) | 56kg/cabinet (P6, 8)<br>52kg/cabinet (P10)<br>55kg/cabinet (P16) | Rear                              | Front IP65<br>Rear IP45  |

<sup>(1)</sup> Peak Value according to IDMS (Information Display Measurement Standard)

<sup>(2)</sup> Front Service : Front Service to Power Supply and Main Board on a cabinet level / Parts Rear Service : Power Supply and Main Board can be accessed from the rear

## Outdoor signage

|              | Project              | Screen Size   | Resolution  | Brightness                            | Contrast Ratio               | Operation Hour | IP Rating      | Connectivity   | SoC    | S/W                 |
|--------------|----------------------|---------------|-------------|---------------------------------------|------------------------------|----------------|----------------|--|--------|---------------------|
| Outdoor      | OHN                  | 85"           | 3840 x 2160 | 3,300 nit                             | 3,000:1                      | 24/7           | IP56           | In: DP1.2, HDMI 2.0(2), HDCP 2.2, USB2.0<br>Out: Stereo Mini Jack<br>Ext: RS232C(In), RJ45(In)   | SSSP 6 | MagicINFO Player S6 |
|              | OHN-D (Dual display) | 85"           | 3840 x 2160 | 3,300 nit                             | 3,000:1                      | 24/7           | IP56           | In: DP1.2(2), HDMI 2.0(4), HDCP 2.2, USB2.0(2)<br>Out: Stereo Mini Jack<br>Ext: RS232C(In), RJ45(In)   | SSSP 6 | MagicINFO Player S6 |
|              | OHF                  | 46", 55", 75" | 1920 x 1080 | 3,000 nit(46")<br>2,500 nit(55", 75") | 5,000:1                      | 24/7           | IP56           | In: HDMI 1.4(2), HDBaseT(LAN Common), HDCP 2.2, USB2.0<br>Out: Stereo Mini Jack<br>Ext: RS232C(In/Out), RJ45(In/Out), HDBaseT  | SSSP 4 | MagicINFO Player S4 |
| Semi-Outdoor | OMN                  | 46", 55"      | 1920 x 1080 | 4,000 nit                             | 5,000:1(46")<br>4,000:1(55") | 24/7           | IP5X Validated | In: DP1.2, HDMI 2.0(2), HDCP 2.2, USB2.0<br>Out: HDMI 2.0, Stereo Mini Jack<br>Ext: RS232C(In/Out), RJ45(In/Out)   | SSSP 6 | MagicINFO Player S6 |
|              | OMN-D (Dual Display) | 46", 55"      | 1920 x 1080 | 3,000 nit(front)<br>1,000 nit(back)   | 5,000:1(46")<br>4,000:1(55") | 24/7           | IP5X Validated | In: HDMI 2.0(2), HDCP 2.2, USB2.0(2)<br>Ext: RS232C(In), RJ45(In)  | SSSP 6 | MagicINFO Player S6 |
|              | OMD-W                | 75"           | 1920 x 1080 | 2,500 nit                             | 5,000:1                      | 24/7           | -              | In: Analog D-SUB, DVI-D, DP1.2, HDMI(2), Component(CVBS Common), HDCP1.4, Stereo Mini Jack, USB 2.0<br>Out: DP1.2(Loop-out), Stereo Mini Jack<br>Ext: RS232C(In/Out), RJ45 | SSSP 2 | MagicINFO Player S2 |
|              | OMH                  | 32"           | 1920 x 1080 | 1,000 nit                             | 3,000:1                      | 16/7           | -              | In: DP, HDMI(2), HDCP 2.2, USB(1)<br>Out: DP1.2(Daisy Chain), Stereo Mini Jack<br>Ext: RS232C(In/Out), RJ45(In/Out), HDBaseT(In)   | SSSP 4 | MagicINFO Player S4 |

## Video wall display

| Project     | Screen Size              | Resolution  | Brightness | Contrast Ratio | Operation Hour | B-to-B (mm) | Bezel Width                 | Connectivity  |
|-------------|--------------------------|-------------|------------|----------------|----------------|-------------|-----------------------------|---|
| UHF-E/UHN-E | 46"(UHN-E)<br>55"(UHF-E) | 1920 x 1080 | 700 nit    | 4,000:1        | 24/7           | 1.7mm       | 1.15mm(U/L),<br>0.55mm(R/B) | In: Analog D-SUB, DVI-D, DP1.2, HDMI 2.0(2), HDCP 2.2, Stereo Mini Jack<br>Out: DP1.2(Loop-out), Stereo Mini Jack / Ext: RS232C(In/Out), RJ45 |
| UMH-E/UMN-E | 46"(UMN-E)<br>55"(UMH-E) | 1920 x 1080 | 500 nit    | 4,000:1        | 24/7           | 1.7mm       | 1.15mm(U/L),<br>0.55mm(R/B) | In: Analog D-SUB, DVI-D, DP1.2, HDMI 2.0(2), HDCP 2.2, Stereo Mini Jack<br>Out: DP1.2(Loop-out), Stereo Mini Jack / Ext: RS232C(In/Out), RJ45 |
| VMR-U       | 46"                      | 1920 x 1080 | 500 nit    | 3,500:1        | 24/7           | 3.5mm       | 2.3mm(U/L)<br>1.2mm(R/B)    | In: DP1.2, HDMI 2.0(2), HDCP 2.2, Stereo Mini Jack<br>Out: HDMI, Stereo Mini Jack / Ext: RS232C(In/Out), RJ45                                 |
| UHF5        | 46"                      | 1920 x 1080 | 700 nit    | 4,000:1        | 24/7           | 5.5mm       | 3.4mm(U/L),<br>2.0mm(R/B)   | In: DVI-D, DP1.2, HDMI 2.0(2), HDCP 2.2, Stereo Mini Jack<br>Out: DP1.2(Loop-out), Stereo Mini Jack / Ext: RS232C(In/Out), RJ45(In)           |

## QLED 8K signage

| Project  | Screen Size | Resolution  | Brightness | Operation Hour | Connectivity   | SoC    | S/W          |
|----------|-------------|-------------|------------|----------------|--|--------|--------------|
| QPR - 8K | 82"         | 7680 x 4320 | 500 nit    | 16/7           | In: HDMI 2.0(4, Including 8K 60p input support 1), USB 2.0(3)<br>Out: Optical(Digital Audio Out) / Ext: RS232C(In), RJ45 | SSSP 7 | MagicInfo S7 |

## UHD signage

| Project | Screen Size             | Resolution  | Brightness | Contrast Ratio   | Operation Hour | Panel Type | IP Rating      | Connectivity   | SoC    | S/W                 |
|---------|-------------------------|-------------|------------|--|----------------|------------|----------------|--|--------|---------------------|
| QHH     | 55", 65"                | 3840 x 2160 | 600 nit    | 6,000:1  | 16/7           | -          | -              | In: DP1.2, HDMI 2.0(2), HDCP 2.2, USB2.0(2)<br>Out: HDMI #1 ARC support<br>Ext: RS232C(In/Out), RJ45   | SSSP 5 | MagicINFO Player S5 |
| QMR     | 43", 49", 55", 65", 75" | 3840 x 2160 | 500 nit    | 6,000:1(75")<br>4,000:1<br>(43", 49", 55", 65")        | 24/7           | Non-Glare  | IP5X Validated | In: DVI-D, DP1.2, HDMI 2.0(2), HDCP 2.2, Stereo Mini Jack, USB2.0(2)<br>Out: HDMI 2.0(Loop-out), Stereo Mini Jack<br>Ext: RS232C(In/Out), RJ45 | SSSP 6 | MagicINFO Player S6 |
| QMN     | 85", 98"                | 3840 x 2160 | 500 nit    | 4,000:1(98")<br>3,000:1(85")                           | 24/7           | Non-Glare  | -              | In: DVI-D, DP1.2, HDMI 2.0(2), HDCP 2.2, Stereo Mini Jack, USB2.0(2)<br>Out: HDMI 2.0(Loop-out), Stereo Mini Jack<br>Ext: RS232C(In/Out), RJ45 | SSSP 6 | MagicINFO Player S6 |
| QBR     | 43", 49", 55", 65", 75" | 3840 x 2160 | 350 nit    | 5,000:1(43")<br>4,700:1(49", 55")<br>4,000:1(65", 75") | 16/7           | -          | IP5X Validated | In: DVI-D, HDMI 2.0(2), HDCP 2.2, Stereo Mini Jack, USB2.0(2)<br>Out: Stereo Mini Jack<br>Ext: RS232C(In/Out), RJ45                            | SSSP 6 | MagicINFO Player S6 |
| QEN     | 82"                     | 3840 x 2160 | 300 nit    | 5,000:1  | 16/7           | -          | -              | In: DVI-D, HDMI 2.0(2), HDCP 2.2, Stereo Mini Jack, USB2.0(2)<br>Out: Stereo Mini Jack<br>Ext: RS232C(In/Out), RJ45                            | SSSP 6 | MagicINFO Player S6 |

## FHD signage

| Project | Screen Size   | Resolution  | Brightness | Contrast Ratio                    | Operation Hour | Panel Type | IP Rating      | Connectivity  | SoC        | S/W                   |
|---------|---------------|-------------|------------|-----------------------------------|----------------|------------|----------------|---|------------|-----------------------|
| PHF-P   | 43", 49", 55" | 1920 x 1080 | 700 nit    | 4,000:1(49", 55")<br>3,000:1(43") | 24/7           | Non-Glare  | IP5X Validated | In: DVI-I, DP1.2, HDMI 2.0(2), HDCP 2.2, Stereo Mini Jack, USB2.0(2)<br>Out: DP1.2(Loop-out), Stereo Mini Jack<br>Ext: RS232C(In/Out), RJ45 | SSSP 4     | MagicINFO Player S4   |
| PMF     | 32"           | 1920 x 1080 | 400 nit    | 5,000:1                           | 16/7           | -          | IP5X Validated | In: DVI-I, DP1.2, HDMI 2.0(2), HDCP 2.2, Stereo Mini Jack, USB2.0(2)<br>Out: DP1.2(Loop-out), Stereo Mini Jack<br>Ext: RS232C(In/Out), RJ45 | SSSP 4     | MagicINFO Player S4   |
| DCE     | 32", 55"      | 1920 x 1080 | 350 nit    | 5,000:1                           | 16/7           | -          | -              | In: D-SUB, DVI-I, HDMI 1.4(2), HDCP 1.4, Stereo Mini Jack, USB2.0<br>Out: Stereo Mini Jack<br>Ext: RS232C(In), RJ45                         | Simple SoC | MagicINFO Player Lite |
| DCJ     | 43", 49"      | 1920 x 1080 | 300 nit    | 3,000:1                           | 16/7           | -          | -              | In: DVI-I, HDMI 1.4(2), HDCP 1.4, Stereo Mini Jack, USB2.0<br>Out: Stereo Mini Jack<br>Ext: RS232C(In), RJ45                                | Simple SoC | MagicINFO Player Lite |

## Interactive display

| Project | Screen Size | Resolution  | Brightness                                      | Contrast Ratio                               | Operation Hour              | Touch Type       | # of Touch    | Connectivity  | SoC    | S/W                   |
|---------|-------------|-------------|---|--|-----------------------------|------------------|---------------|---|--------|-----------------------|
| PMF-BC  | 32" 43" 55" | 1920 x 1080 | 300 nit (32")<br>350 nit (43")<br>400 nit (55") | 5,000:1(32")<br>3,000:1(43")<br>4,000:1(55") | 24/7(43", 55")<br>16/7(32") | Capacitive touch | Max. 10 Touch | In: DVI-I(D-SUB Common), DP1.2, HDMI 2.0(2), HDCP 2.2, Stereo Mini Jack, USB 2.0(2, 1 used for touch)<br>Out: DP1.2(Loop-out), Stereo Mini Jack, USB Type-B(2)<br>Ext: RS232C(In/Out), RJ45 | SSSP 4 | Built-in MagicInfo S4 |

## MagicINFO solution

|                   | Number of displays connecting to MagicINFO Server  |                              |                              |                                  |
|-------------------|--|------------------------------|------------------------------|----------------------------------|
|                   | <200   | <2000                        | <5000                        | >5000                            |
| OS                | Windows Server® 2008 / 2012 / 2016   |                              |                              |                                  |
| CPU               | Intel Xeon E3-1200 or better   | Intel Xeon E5-2400 or better | Intel Xeon E5-2600 or better | Intel Xeon E5-4600 or better     |
| RAM               | 4 GB or more   | 8 GB or more                 | 16 GB or more                | 32 GB or more                    |
| HDD               | At least 100 GB for basic setup (operating system and server application)<br>*Heavily dependent on the amount of content data to be stored on the server |                              |                              |                                  |
| Network Bandwidth | 64 kbps or better  |                              |                              |                                  |
| Number of Servers | 1  | 2                            | 3                            | 3 or more; dependent on scenario |