

# Connection Combination

## AJ050TXJ2KH/EA Cooling

Unit	Indoor Unit		Cooling Capacity (W)		Capacity			Power Consumption			Current			EER
	A	B	A	B	W			W			A			W/W
					MIN	Rated	MAX	MIN	Rated	MAX	MIN	Rated	MAX	Rated
1	020		2,000		1,250	2,000	2,880	300	730	880	1.4	3.3	4.0	2.74
	025		2,500		1,250	2,500	3,120	300	800	960	1.4	3.7	4.4	3.13
	035		3,500		1,250	3,500	4,200	300	1,090	1,310	1.4	5.0	6.0	3.21
	050		5,000		1,250	5,000	5,200	300	1,600	1,740	1.4	7.3	8.0	3.13
2	020	020	2,000	2,000	1,300	4,000	4,800	350	1,245	1,490	1.6	5.7	6.8	3.21
	020	025	2,010	2,590	1,300	4,600	5,200	350	1,430	1,720	1.6	6.5	7.9	3.22
	020	035	1,840	3,160	1,400	5,000	5,400	350	1,490	1,780	1.6	6.8	8.1	3.36
	020	050	1,400	3,600	1,400	5,000	5,400	350	1,450	1,800	1.6	6.6	8.2	3.45
	025	025	2,500	2,500	1,400	5,000	5,400	350	1,500	1,780	1.6	6.9	8.1	3.33
	025	035	2,140	2,860	1,400	5,000	5,400	350	1,500	1,780	1.6	6.9	8.1	3.33
	025	050	1,670	3,330	1,400	5,000	5,400	350	1,450	1,700	1.6	6.6	7.8	3.45
	035	035	2,500	2,500	1,400	5,000	5,400	350	1,500	1,780	1.6	6.9	8.1	3.33
	035	050	2,000	3,000	1,400	5,000	5,400	350	1,320	1,700	1.6	6.0	7.8	3.79

## AJ068TXJ3KH/EA Cooling

Unit	Indoor Unit			Cooling Capacity (W)			Capacity			Power Consumption			Current			ERR
	A	B	B	A	B	B	W			W			A			W/W
							MIN	Rated	MAX	MIN	Rated	MAX	MIN	Rated	MAX	Rated
1	020			2,000			1,280	2,000	2,880	400	630	930	1.8	2.9	4.3	3.17
	025			2,500			1,280	2,500	3,120	400	790	1,010	1.8	3.6	4.6	3.16
	035			3,500			1,280	3,500	4,200	400	1,070	1,370	1.8	4.9	6.3	3.27
	050			5,000			1,300	5,000	5,800	400	1,620	1,900	1.8	7.4	8.7	3.09
2	020	020		2,000	2,000		1,300	4,000	4,800	420	1,240	1,480	1.9	5.7	6.8	3.23
	020	025		1,970	2,530		1,300	4,500	5,520	420	1,410	1,680	1.9	6.5	7.7	3.19
	020	035		2,030	3,470		1,300	5,500	6,550	420	1,830	2,470	1.9	8.4	11.3	3.01
	020	050		1,820	4,680		1,300	6,500	7,740	420	2,000	2,690	1.9	9.2	12.3	3.25
	025	025		2,500	2,500		1,300	5,000	5,950	420	1,660	2,260	1.9	7.6	10.3	3.01
	025	035		2,570	3,430		1,300	6,000	7,140	420	1,980	2,670	1.9	9.1	12.2	3.03
	025	050		2,270	4,530		1,380	6,800	8,090	430	2,090	2,660	2.0	9.6	12.2	3.25
	035	035		3,250	3,250		1,300	6,500	7,740	420	2,010	2,700	1.9	9.2	12.4	3.23
	035	050		2,720	4,080		1,380	6,800	8,090	430	2,100	2,670	2.0	9.6	12.2	3.24
3	020	020	020	2,000	2,000	2,000	1,800	6,000	7,400	440	1,970	2,650	2.0	9.0	12.1	3.05
	020	020	025	1,980	1,980	2,540	1,800	6,500	8,000	440	2,000	2,690	2.0	9.2	12.3	3.25
	020	020	035	1,830	1,830	3,140	1,800	6,800	8,400	440	2,070	2,700	2.0	9.5	12.4	3.29
	020	020	050	1,490	1,490	3,830	1,800	6,800	8,400	440	2,000	2,690	2.0	9.2	12.3	3.40
	020	025	025	1,820	2,340	2,340	1,800	6,500	8,000	440	2,030	2,690	2.0	9.3	12.3	3.20
	020	025	035	1,700	2,190	2,910	1,800	6,800	8,400	440	2,090	2,690	2.0	9.6	12.3	3.25
	020	025	050	1,400	1,800	3,600	1,800	6,800	8,400	440	2,010	2,690	2.0	9.2	12.3	3.38
	020	035	035	1,540	2,630	2,630	1,800	6,800	8,400	440	2,010	2,700	2.0	9.2	12.4	3.38
	020	035	050	1,290	2,210	3,310	1,800	6,800	8,400	440	2,050	2,700	2.0	9.4	12.4	3.32
	025	025	025	2,270	2,270	2,270	1,800	6,800	8,400	440	2,060	2,690	2.0	9.4	12.3	3.30
	025	025	035	2,040	2,040	2,720	1,800	6,800	8,400	440	2,130	2,700	2.0	9.7	12.4	3.19
	025	025	050	1,700	1,700	3,400	1,800	6,800	8,400	440	2,030	2,690	2.0	9.3	12.3	3.35
	025	035	035	1,850	2,470	2,470	1,800	6,800	8,400	440	2,020	2,700	2.0	9.2	12.4	3.37
	025	035	050	1,570	2,090	3,140	1,800	6,800	8,400	440	2,070	2,700	2.0	9.5	12.4	3.29
	035	035	035	2,270	2,270	2,270	1,800	6,800	8,400	440	2,000	2,710	2.0	9.2	12.4	3.40

- Specifications may be subject to change without prior notice.
- Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
- Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
- Combination table capacity based on connecting Wind-Free AR9500 Wall mounted indoor range (AJxxxTNAPKH).
- Minimum two indoor units should be connected to outdoor unit for system operation.
- Power consumption include indoor unit power.

# Connection Combination

## AJ080TXJ4KH/EA Cooling

Unit	Indoor Unit				Cooling Capacity (W)				Capacity			Power Consumption			Current			EER
	A	B	C	D	A	B	C	D	W			W			A			W/W
									MIN	Rated	MAX	MIN	Rated	MAX	MIN	Rated	MAX	Rated
1	020				2,000				1,470	2,000	2,900	380	970	1,050	1.7	4.4	4.8	2.06
	025				2,500				1,520	2,500	3,300	390	1,180	1,280	1.8	5.4	5.9	2.12
	035				3,500				1,600	3,500	3,700	400	1,470	1,590	1.8	6.7	7.3	2.38
	050				5,000				1,750	5,000	6,300	420	2,120	2,300	1.9	9.7	10.5	2.36
	068				6,200				1,900	6,200	7,000	580	2,300	2,820	2.7	10.5	12.9	2.70
2	020	020			2,000	2,000			1,640	4,000	4,800	410	1,240	1,490	1.9	5.7	6.8	3.23
	020	025			2,010	2,590			1,690	4,600	5,520	420	1,430	1,720	1.9	6.5	7.9	3.22
	020	035			2,030	3,470			1,770	5,500	6,600	430	1,710	2,050	2.0	7.8	9.4	3.22
	020	050			2,020	5,180			1,900	7,200	8,640	580	2,240	2,690	2.7	10.3	12.3	3.21
	020	068			1,680	5,770			1,900	7,450	8,640	580	2,350	2,730	2.7	10.8	12.5	3.17
	025	025			2,600	2,600			1,750	5,200	6,240	420	1,660	2,000	1.9	7.6	9.2	3.13
	025	035			2,610	3,490			1,820	6,100	7,320	440	1,900	2,260	2.0	8.7	10.3	3.21
	025	050			2,400	4,800			1,900	7,200	8,640	580	2,240	2,690	2.7	10.3	12.3	3.21
	025	068			2,060	5,490			1,900	7,550	8,760	580	2,380	2,760	2.7	10.9	12.6	3.17
	035	035			3,500	3,500			1,900	7,000	8,000	580	2,490	2,620	2.7	11.4	12.0	2.81
	035	050			2,940	4,410			1,900	7,350	8,820	580	2,290	2,750	2.7	10.5	12.6	3.21
	035	068			2,570	5,130			1,900	7,700	8,930	580	2,400	2,780	2.7	11.0	12.7	3.21
	050	050			3,830	3,830			1,900	7,660	9,180	580	2,380	2,860	2.7	10.9	13.1	3.22
050	068			3,340	4,460			1,900	7,800	8,970	580	2,430	2,820	2.7	11.1	12.9	3.21	
3	020	020	020		2,000	2,000	2,000		1,810	6,000	7,200	440	1,850	2,310	2.0	8.5	10.6	3.24
	020	020	025		2,010	2,010	2,580		1,870	6,600	7,920	440	2,000	2,500	2.0	9.2	11.4	3.30
	020	020	035		1,940	1,940	3,320		1,900	7,200	9,000	580	2,290	2,780	2.7	10.5	12.7	3.14
	020	020	050		1,650	1,650	4,250		1,900	7,550	9,180	580	2,260	2,730	2.7	10.3	12.5	3.34
	020	020	068		1,470	1,470	5,050		1,900	8,000	9,300	580	2,340	2,870	2.7	10.7	13.1	3.42
	020	025	025		1,960	2,520	2,520		1,900	7,000	8,640	580	2,220	2,680	2.7	10.2	12.3	3.15
	020	025	035		1,830	2,350	3,130		1,900	7,310	9,060	580	2,220	2,690	2.7	10.2	12.3	3.29
	020	025	050		1,580	2,030	4,050		1,900	7,650	9,250	580	2,260	2,730	2.7	10.3	12.5	3.38
	020	025	068		1,400	1,800	4,800		1,900	8,000	9,300	580	2,340	2,870	2.7	10.7	13.1	3.42
	020	035	035		1,700	2,920	2,920		1,900	7,540	9,160	580	2,260	2,730	2.7	10.3	12.5	3.34
	020	035	050		1,490	2,560	3,830		1,900	7,880	9,300	580	2,330	2,820	2.7	10.7	12.9	3.38
	020	050	050		1,300	3,350	3,350		1,900	8,000	9,300	580	2,370	2,910	2.7	10.8	13.3	3.38
	025	025	025		2,400	2,400	2,400		1,900	7,200	9,030	580	2,180	2,640	2.7	10.0	12.1	3.30
	025	025	035		2,230	2,230	2,970		1,900	7,420	9,130	580	2,210	2,690	2.7	10.1	12.3	3.36
	025	025	050		1,940	1,940	3,890		1,900	7,770	9,300	580	2,280	2,780	2.7	10.4	12.7	3.41
	025	025	068		1,710	1,710	4,570		1,900	8,000	9,300	580	2,370	2,910	2.7	10.8	13.3	3.38
	025	035	035		2,090	2,780	2,780		1,900	7,650	9,230	580	2,250	2,730	2.7	10.3	12.5	3.40
025	035	050		1,850	2,460	3,690		1,900	8,000	9,300	580	2,330	2,870	2.7	10.7	13.1	3.43	
025	035	035		2,630	2,630	2,630		1,900	7,890	9,300	580	2,330	2,820	2.7	10.7	12.9	3.39	
035	035	050		2,290	2,290	3,430		1,900	8,000	9,300	580	2,370	2,910	2.7	10.8	13.3	3.38	
4	020	020	020	020	1,830	1,830	1,830	1,830	1,900	7,320	9,050	580	2,210	2,690	2.7	10.1	12.3	3.31
	020	020	020	025	1,740	1,740	1,740	2,230	1,900	7,440	9,120	580	2,210	2,690	2.7	10.1	12.3	3.37
	020	020	020	035	1,620	1,620	1,620	2,780	1,900	7,650	9,220	580	2,250	2,730	2.7	10.3	12.5	3.40
	020	020	020	050	1,440	1,440	1,440	3,690	1,900	8,000	9,300	580	2,380	2,870	2.7	10.9	13.1	3.36
	020	020	025	025	1,650	1,650	2,120	2,120	1,900	7,540	9,180	580	2,260	2,730	2.7	10.3	12.5	3.34
	020	020	025	035	1,550	1,550	2,000	2,660	1,900	7,760	9,280	580	2,270	2,780	2.7	10.4	12.7	3.42
	020	020	025	050	1,370	1,370	1,760	3,510	1,900	8,000	9,300	580	2,380	2,870	2.7	10.9	13.1	3.36
	020	020	035	035	1,470	1,470	2,530	2,530	1,900	8,000	9,300	580	2,350	2,870	2.7	10.8	13.1	3.40
	020	025	025	025	1,580	2,030	2,030	2,030	1,900	7,650	9,250	580	2,260	2,730	2.7	10.3	12.5	3.38
	020	025	025	035	1,490	1,920	1,920	2,560	1,900	7,890	9,300	580	2,330	2,820	2.7	10.7	12.9	3.39
	020	025	025	050	1,300	1,670	1,670	3,350	1,900	8,000	9,300	580	2,380	2,910	2.7	10.9	13.3	3.36
	020	025	035	035	1,400	1,800	2,400	2,400	1,900	8,000	9,300	580	2,380	2,870	2.7	10.9	13.1	3.36
	025	025	025	025	1,940	1,940	1,940	1,940	1,900	7,760	9,300	580	2,290	2,780	2.7	10.5	12.7	3.39
	025	025	025	035	1,850	1,850	1,850	2,460	1,900	8,000	9,300	580	2,380	2,870	2.7	10.9	13.1	3.36
	025	025	035	035	1,710	1,710	2,290	2,290	1,900	8,000	9,300	580	2,380	2,910	2.7	10.9	13.3	3.36

- Specifications may be subject to change without prior notice.
- Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
- Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
- Combination table capacity based on connecting Wind-Free AR9500 Wall mounted indoor range (AJxxxTNA PKH).
- Minimum two indoor units should be connected to outdoor unit for system operation.
- Power consumption include indoor unit power.

# Connection Combination

## AJ100TXJ5KH/EA Cooling

Unit	Indoor Unit					Cooling Capacity (W)					Capacity			Power Consumption			Current			EER
	A	B	C	D	E	A	B	C	D	E	W			W			A			W/W
											MIN	Rated	MAX	MIN	Rated	MAX	MIN	Rated	MAX	Rated
1	020					2,000					1,600	2,000	2,600	580	960	1,050	2.7	4.4	4.8	2.08
	025					2,500					1,600	2,500	3,200	580	1,100	1,190	2.7	5.0	5.4	2.27
	035					3,500					1,620	3,500	3,800	590	1,360	1,480	2.7	6.2	6.8	2.57
	050					5,000					1,650	5,000	6,300	600	1,970	2,140	2.7	9.0	9.8	2.54
	068					6,200					1,710	6,200	7,600	620	2,380	2,580	2.8	10.9	11.8	2.61
2	020	020				2,000	2,000				1,680	4,000	4,900	610	1,260	1,650	2.8	5.8	7.6	3.17
	020	025				1,970	2,530				1,680	4,500	5,530	610	1,400	1,860	2.8	6.4	8.5	3.21
	020	035				2,030	3,470				1,710	5,500	6,950	620	1,750	2,330	2.8	8.0	10.7	3.14
	020	050				1,960	5,040				2,210	7,000	8,690	630	2,190	2,910	2.9	10.0	13.3	3.20
	020	068				1,820	6,250				2,280	8,070	10,110	650	2,550	3,390	3.0	11.7	15.5	3.16
	025	025				2,500	2,500				1,680	5,000	6,320	610	1,600	2,120	2.8	7.3	9.7	3.13
	025	035				2,570	3,430				1,710	6,000	7,270	620	1,840	2,430	2.8	8.4	11.1	3.26
	025	050				2,500	5,000				2,210	7,500	9,320	630	2,340	3,120	2.9	10.7	14.3	3.21
	025	068				2,220	5,930				2,280	8,150	10,110	650	2,550	3,390	3.0	11.7	15.5	3.20
	035	035				3,500	3,500				2,170	7,000	8,530	620	2,130	2,850	2.8	9.7	13.0	3.29
	035	050				3,210	4,810				2,240	8,020	9,950	640	2,490	3,330	2.9	11.4	15.2	3.22
	035	068				2,860	5,730				2,480	8,590	10,740	660	2,700	3,600	3.0	12.4	16.5	3.18
	050	050				4,280	4,280				2,440	8,560	10,430	650	2,650	3,500	3.0	12.1	16.0	3.23
	050	068				3,780	5,040				2,510	8,820	10,900	670	2,760	3,670	3.1	12.6	16.8	3.20
068	068				4,550	4,550				3,110	9,100	11,000	690	2,830	3,740	3.2	13.0	17.1	3.22	
3	020	020	020			2,000	2,000	2,000			1,760	6,000	7,270	640	1,870	2,460	2.9	8.6	11.3	3.21
	020	020	025			1,980	1,980	2,540			1,760	6,500	7,900	640	2,010	2,660	2.9	9.2	12.2	3.23
	020	020	035			2,020	2,020	3,460			2,280	7,500	8,850	650	2,260	2,980	3.0	10.3	13.6	3.32
	020	020	050			1,900	1,900	4,890			2,310	8,690	10,270	660	2,610	3,450	3.0	11.9	15.8	3.33
	020	020	068			1,650	1,650	5,670			2,550	8,970	10,430	680	2,680	3,530	3.1	12.3	16.2	3.35
	020	025	025			1,960	2,520	2,520			2,240	7,000	8,370	640	2,110	2,820	2.9	9.7	12.9	3.32
	020	025	035			2,000	2,570	3,430			2,280	8,000	9,320	650	2,350	3,130	3.0	10.8	14.3	3.40
	020	025	050			1,810	2,320	4,650			2,310	8,780	10,270	660	2,610	3,450	3.0	11.9	15.8	3.36
	020	025	068			1,530	1,970	5,260			2,550	8,760	10,430	680	2,680	3,530	3.1	12.3	16.2	3.27
	020	035	035			1,960	3,360	3,360			2,280	8,690	10,270	650	2,600	3,440	3.0	11.9	15.7	3.34
	020	035	050			1,690	2,900	4,340			2,510	8,930	10,430	670	2,660	3,510	3.1	12.2	16.1	3.36
	020	035	068			1,460	2,500	5,000			2,760	8,960	10,740	690	2,730	3,630	3.2	12.5	16.6	3.28
	020	050	050			1,450	3,730	3,730			2,720	8,900	10,740	680	2,720	3,630	3.1	12.4	16.6	3.27
	020	050	068			1,320	3,400	4,540			3,150	9,260	11,000	700	2,840	3,750	3.2	13.0	17.2	3.26
	020	068	068			1,250	4,280	4,280			3,240	9,800	11,000	720	2,860	3,770	3.3	13.1	17.3	3.43
	025	025	025			2,500	2,500	2,500			2,240	7,500	8,850	640	2,250	2,970	2.9	10.3	13.6	3.33
	025	025	035			2,550	2,550	3,400			2,280	8,500	9,950	650	2,500	3,340	3.0	11.4	15.3	3.40
	025	025	050			2,210	2,210	4,430			2,480	8,850	10,270	660	2,610	3,450	3.0	11.9	15.8	3.39
	025	025	068			1,900	1,900	5,070			2,550	8,870	10,740	680	2,720	3,630	3.1	12.4	16.6	3.26
	025	035	035			2,390	3,190	3,190			2,280	8,770	10,270	650	2,600	3,440	3.0	11.9	15.7	3.37
	025	035	050			2,010	2,680	4,020			2,510	8,700	10,430	670	2,660	3,510	3.1	12.2	16.1	3.27
	025	035	068			1,810	2,420	4,830			2,760	9,060	10,900	690	2,780	3,690	3.2	12.7	16.9	3.26
	025	050	050			1,800	3,600	3,600			2,720	9,000	10,900	680	2,770	3,680	3.1	12.7	16.8	3.25
	025	050	068			1,650	3,300	4,400			3,150	9,360	11,000	700	2,740	3,750	3.2	12.5	17.2	3.42
	025	068	068			1,550	4,130	4,130			3,240	9,800	11,000	720	2,860	3,770	3.3	13.1	17.3	3.43
	035	035	035			2,980	2,980	2,980			2,480	8,940	10,430	660	2,650	3,500	3.0	12.1	16.0	3.37
035	035	050			2,550	2,550	3,820			2,680	8,910	10,740	670	2,710	3,620	3.1	12.4	16.6	3.29	
035	035	068			2,320	2,320	4,630			3,110	9,260	11,000	690	2,830	3,740	3.2	13.0	17.1	3.27	
035	050	050			2,300	3,450	3,450			3,110	9,210	11,000	690	2,820	3,740	3.2	12.9	17.1	3.27	
035	050	068			2,180	3,270	4,360			3,200	9,800	11,000	710	2,800	3,760	3.2	12.8	17.2	3.50	
035	068	068			1,960	3,920	3,920			3,290	9,800	11,000	730	2,910	3,780	3.3	13.3	17.3	3.37	
050	050	050			3,270	3,270	3,270			3,150	9,800	11,000	700	2,790	3,750	3.2	12.8	17.2	3.51	
050	050	068			2,940	2,940	3,920			3,240	9,800	11,000	720	2,910	3,770	3.3	13.3	17.3	3.37	

- Specifications may be subject to change without prior notice.
- Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
- Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
- Combination table capacity based on connecting Wind-Free AR9500 Wall mounted indoor range (AJxxxTNAPKH).
- Minimum two indoor units should be connected to outdoor unit for system operation.
- Power consumption include indoor unit power.

# Connection Combination

## AJ100TXJ5KH/EA Cooling

Unit	Indoor Unit					Cooling Capacity (W)					Capacity			Power Consumption			Current			EER
	A	B	C	D	E	A	B	C	D	E	W			W			A			W/W
											MIN	Rated	MAX	MIN	Rated	MAX	MIN	Rated	MAX	Rated
020	020	020	020	020		2,000	2,000	2,000	2,000		2,350	8,000	9,320	670	2,380	3,160	3.1	10.9	14.5	3.36
020	020	020	025			1,980	1,980	1,980	2,550		2,350	8,500	9,950	670	2,520	3,360	3.1	11.5	15.4	3.37
020	020	020	035			1,860	1,860	1,860	3,190		2,380	8,780	10,270	680	2,620	3,470	3.1	12.0	15.9	3.35
020	020	020	050			1,560	1,560	1,560	4,010		2,590	8,690	10,430	690	2,690	3,540	3.2	12.3	16.2	3.23
020	020	020	068			1,410	1,410	1,410	4,840		2,840	9,080	10,900	710	2,800	3,710	3.2	12.8	17.0	3.24
020	020	025	025			1,900	1,900	2,450	2,450		2,350	8,700	10,270	670	2,620	3,460	3.1	12.0	15.8	3.32
020	020	025	035			1,770	1,770	2,280	3,030		2,550	8,850	10,270	680	2,620	3,470	3.1	12.0	15.9	3.38
020	020	025	050			1,500	1,500	1,930	3,860		2,590	8,800	10,740	690	2,730	3,640	3.2	12.5	16.7	3.22
020	020	025	068			1,360	1,360	1,750	4,680		3,200	9,160	10,900	710	2,800	3,710	3.2	12.8	17.0	3.27
020	020	035	035			1,600	1,600	2,750	2,750		2,550	8,700	10,430	680	2,680	3,530	3.1	12.3	16.2	3.25
020	020	035	050			1,430	1,430	2,450	3,680		2,800	9,000	10,900	700	2,790	3,700	3.2	12.8	16.9	3.23
020	020	035	068			1,310	1,310	2,250	4,490		3,240	9,360	11,000	720	2,760	3,770	3.3	12.6	17.3	3.39
020	020	050	050			1,300	1,300	3,350	3,350		3,200	9,300	11,000	710	2,850	3,760	3.2	13.0	17.2	3.26
020	020	050	068			1,230	1,230	3,150	4,200		3,290	9,800	11,000	730	2,870	3,780	3.3	13.1	17.3	3.41
020	025	025	025			1,810	2,320	2,320	2,320		2,550	8,780	10,270	670	2,620	3,460	3.1	12.0	15.8	3.35
020	025	025	035			1,690	2,170	2,170	2,900		2,550	8,940	10,430	680	2,670	3,520	3.1	12.2	16.1	3.35
020	025	025	050			1,450	1,860	1,860	3,720		2,760	8,880	10,740	690	2,730	3,640	3.2	12.5	16.7	3.25
020	025	025	068			1,320	1,700	1,700	4,540		3,200	9,260	11,000	710	2,850	3,760	3.2	13.0	17.2	3.25
020	025	035	035			1,540	1,980	2,640	2,640		2,550	8,800	10,740	680	2,720	3,630	3.1	12.4	16.6	3.24
020	025	035	050			1,380	1,780	2,370	3,560		3,150	9,100	10,900	700	2,790	3,700	3.2	12.8	16.9	3.26
020	025	035	068			1,270	1,640	2,190	4,370		3,240	9,470	11,000	720	2,810	3,770	3.3	12.9	17.3	3.37
020	025	050	050			1,270	1,630	3,250	3,250		3,200	9,400	11,000	710	2,800	3,760	3.2	12.8	17.2	3.36
020	025	050	068			1,180	1,520	3,040	4,060		3,290	9,800	11,000	730	2,870	3,780	3.3	13.1	17.3	3.41
020	035	035	035			1,470	2,510	2,510	2,510		2,760	9,000	10,900	690	2,780	3,690	3.2	12.7	16.9	3.24
020	035	035	050			1,330	2,280	2,280	3,420		3,150	9,320	11,000	700	2,840	3,750	3.2	13.0	17.2	3.28
020	035	035	068			1,250	2,140	2,140	4,280		3,240	9,800	11,000	720	2,860	3,770	3.3	13.1	17.3	3.43
020	035	050	050			1,250	2,140	3,210	3,210		3,240	9,800	11,000	720	2,850	3,770	3.3	13.0	17.3	3.44
020	035	050	068			1,120	1,930	2,890	3,860		3,330	9,800	11,000	740	2,920	3,790	3.4	13.4	17.3	3.36
020	050	050	050			1,120	2,890	2,890	2,890		3,290	9,800	11,000	730	2,920	3,780	3.3	13.4	17.3	3.36
025	025	025	025			2,210	2,210	2,210	2,210		2,510	8,840	10,270	670	2,620	3,460	3.1	12.0	15.8	3.37
025	025	025	035			2,010	2,010	2,010	2,680		2,550	8,710	10,430	680	2,670	3,520	3.1	12.2	16.1	3.26
025	025	025	050			1,800	1,800	1,800	3,600		2,760	9,000	10,900	690	2,780	3,690	3.2	12.7	16.9	3.24
025	025	025	068			1,660	1,660	1,660	4,410		3,200	9,380	11,000	710	2,750	3,760	3.2	12.6	17.2	3.41
025	025	035	035			1,910	1,910	2,540	2,540		2,720	8,900	10,740	680	2,720	3,630	3.1	12.4	16.6	3.27
025	025	035	050			1,730	1,730	2,300	3,450		3,150	9,200	11,000	700	2,830	3,750	3.2	13.0	17.2	3.25
025	025	035	068			1,630	1,630	2,180	4,360		3,240	9,800	11,000	720	2,810	3,770	3.3	12.9	17.3	3.49
025	025	050	050			1,630	1,630	3,270	3,270		3,200	9,800	11,000	710	2,800	3,760	3.2	12.8	17.2	3.50
025	025	050	068			1,470	1,470	2,940	3,920		3,290	9,800	11,000	730	2,920	3,780	3.3	13.4	17.3	3.36
025	035	035	035			1,820	2,430	2,430	2,430		3,110	9,100	10,900	690	2,780	3,690	3.2	12.7	16.9	3.27
025	035	035	050			1,660	2,210	2,210	3,320		3,150	9,400	11,000	700	2,790	3,750	3.2	12.8	17.2	3.37
025	035	035	068			1,550	2,060	2,060	4,130		3,240	9,800	11,000	720	2,860	3,770	3.3	13.1	17.3	3.43
025	035	050	050			1,550	2,060	3,090	3,090		3,240	9,800	11,000	720	2,850	3,770	3.3	13.0	17.3	3.44
035	035	035	035			2,330	2,330	2,330	2,330		3,110	9,320	11,000	690	2,830	3,740	3.2	13.0	17.1	3.29
035	035	035	050			2,180	2,180	2,180	3,270		3,200	9,800	11,000	710	2,840	3,760	3.2	13.0	17.2	3.45
035	035	035	068			1,960	1,960	1,960	3,920		3,290	9,800	11,000	730	2,910	3,780	3.3	13.3	17.3	3.37
035	035	050	050			1,960	1,960	2,940	2,940		3,240	9,800	11,000	720	2,910	3,770	3.3	13.3	17.3	3.37

- Specifications may be subject to change without prior notice.
- Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
- Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
- Combination table capacity based on connecting Wind-Free AR9500 Wall mounted indoor range (AJxxxTNAPKH).
- Minimum two indoor units should be connected to outdoor unit for system operation.
- Power consumption include indoor unit power.

# Connection Combination

## AJ100TXJ5KH/EA Cooling

Unit	Indoor Unit					Cooling Capacity (W)					Capacity			Power Consumption			Current			EER
	A	B	C	D	E	A	B	C	D	E	W			W			A			W/W
											MIN	Rated	MAX	MIN	Rated	MAX	MIN	Rated	MAX	Rated
5	020	020	020	020	020	1,900	1,900	1,900	1,900	1,900	2,630	9,500	10,270	700	2,650	3,490	3.2	12.1	16.0	3.58
	020	020	020	020	025	1,810	1,810	1,810	1,810	2,320	2,630	9,550	10,430	700	2,700	3,550	3.2	12.4	16.2	3.54
	020	020	020	020	035	1,690	1,690	1,690	1,690	2,900	2,660	9,660	10,740	710	2,750	3,650	3.2	12.6	16.7	3.51
	020	020	020	020	050	1,520	1,520	1,520	1,520	3,910	3,240	10,000	10,900	720	2,810	3,720	3.3	12.9	17.0	3.56
	020	020	020	020	068	1,350	1,350	1,350	1,350	4,620	3,330	10,000	11,000	740	2,830	3,790	3.4	13.0	17.3	3.53
	020	020	020	025	025	1,720	1,720	1,720	2,220	2,220	2,630	9,610	10,430	700	2,700	3,550	3.2	12.4	16.2	3.56
	020	020	020	025	035	1,620	1,620	1,620	2,080	2,770	2,840	9,710	10,740	710	2,750	3,650	3.2	12.6	16.7	3.53
	020	020	020	025	050	1,460	1,460	1,460	1,880	3,750	3,240	10,000	11,000	720	2,860	3,770	3.3	13.1	17.3	3.50
	020	020	020	025	068	1,300	1,300	1,300	1,670	4,440	3,330	10,000	11,000	740	2,830	3,790	3.4	13.0	17.3	3.53
	020	020	020	035	035	1,560	1,560	1,560	2,670	2,670	3,200	10,000	10,900	710	2,800	3,710	3.2	12.8	17.0	3.57
	020	020	020	035	050	1,370	1,370	1,370	2,350	3,530	3,290	10,000	11,000	730	2,820	3,780	3.3	12.9	17.3	3.55
	020	020	020	035	068	1,230	1,230	1,230	2,110	4,210	3,380	10,000	11,000	750	2,880	3,800	3.4	13.2	17.4	3.47
	020	020	020	050	050	1,230	1,230	1,230	3,160	3,160	3,330	10,000	11,000	740	2,880	3,790	3.4	13.2	17.3	3.47
	020	020	025	025	025	1,650	1,650	2,120	2,120	2,120	2,630	9,660	10,740	700	2,740	3,650	3.2	12.5	16.7	3.53
	020	020	025	025	035	1,590	1,590	2,050	2,050	2,730	2,840	10,000	10,900	710	2,800	3,710	3.2	12.8	17.0	3.57
	020	020	025	025	050	1,400	1,400	1,800	1,800	3,600	3,240	10,000	11,000	720	2,860	3,770	3.3	13.1	17.3	3.50
	020	020	025	025	068	1,250	1,250	1,610	1,610	4,290	3,330	10,000	11,000	740	2,880	3,790	3.4	13.2	17.3	3.47
	020	020	025	035	035	1,490	1,490	1,910	2,550	2,550	3,200	10,000	11,000	710	2,850	3,760	3.2	13.0	17.2	3.51
	020	020	025	035	050	1,320	1,320	1,700	2,260	3,400	3,290	10,000	11,000	730	2,820	3,780	3.3	12.9	17.3	3.55
	020	020	025	035	068	1,190	1,190	1,530	2,030	4,070	3,380	10,000	11,000	750	2,930	3,800	3.4	13.4	17.4	3.41
	020	020	025	050	050	1,190	1,190	1,530	3,050	3,050	3,330	10,000	11,000	740	2,930	3,790	3.4	13.4	17.3	3.41
	020	020	035	035	035	1,400	1,400	2,400	2,400	2,400	3,240	10,000	11,000	720	2,810	3,770	3.3	12.9	17.3	3.56
	020	020	035	035	050	1,250	1,250	2,140	2,140	3,210	3,290	10,000	11,000	730	2,870	3,780	3.3	13.1	17.3	3.48
	020	025	025	025	025	1,580	2,030	2,030	2,030	2,030	2,800	9,700	10,740	700	2,740	3,650	3.2	12.5	16.7	3.54
	020	025	025	025	035	1,520	1,960	1,960	1,960	2,610	3,200	10,000	10,900	710	2,800	3,710	3.2	12.8	17.0	3.57
	020	025	025	025	050	1,350	1,730	1,730	1,730	3,460	3,240	10,000	11,000	720	2,810	3,770	3.3	12.9	17.3	3.56
	020	025	025	025	068	1,210	1,550	1,550	1,550	4,140	3,330	10,000	11,000	740	2,880	3,790	3.4	13.2	17.3	3.47
	020	025	025	035	035	1,430	1,840	1,840	2,450	2,450	3,200	10,000	11,000	710	2,850	3,760	3.2	13.0	17.2	3.51
	020	025	025	035	050	1,270	1,640	1,640	2,180	3,270	3,290	10,000	11,000	730	2,860	3,780	3.3	13.1	17.3	3.50
	020	025	025	035	068	1,150	1,480	1,480	1,970	3,930	3,380	10,000	11,000	750	2,930	3,800	3.4	13.4	17.4	3.41
	020	025	025	050	050	1,150	1,480	1,480	2,950	2,950	3,330	10,000	11,000	740	2,930	3,790	3.4	13.4	17.3	3.41
	020	025	035	035	035	1,350	1,730	2,310	2,310	2,310	3,240	10,000	11,000	720	2,810	3,770	3.3	12.9	17.3	3.56
020	025	035	035	050	1,210	1,550	2,070	2,070	3,100	3,290	10,000	11,000	730	2,920	3,780	3.3	13.4	17.3	3.42	
020	035	035	035	035	1,270	2,180	2,180	2,180	2,180	3,240	10,000	11,000	720	2,860	3,770	3.3	13.1	17.3	3.50	
025	025	025	025	025	2,000	2,000	2,000	2,000	2,000	3,000	10,000	11,000	700	2,900	3,700	3.2	13.3	16.9	3.45	
025	025	025	025	035	1,880	1,880	1,880	1,880	2,500	3,200	10,000	11,000	710	2,840	3,760	3.2	13.0	17.2	3.52	
025	025	025	025	050	1,670	1,670	1,670	1,670	3,330	3,240	10,000	11,000	720	2,810	3,770	3.3	12.9	17.3	3.56	
025	025	025	025	068	1,500	1,500	1,500	1,500	4,000	3,330	10,000	11,000	740	2,930	3,790	3.4	13.4	17.3	3.41	
025	025	025	035	035	1,760	1,760	1,760	2,350	2,350	3,200	10,000	11,000	710	2,800	3,760	3.2	12.8	17.2	3.57	
025	025	025	035	050	1,580	1,580	1,580	2,110	3,160	3,290	10,000	11,000	730	2,860	3,780	3.3	13.1	17.3	3.50	
025	025	035	035	035	1,670	1,670	2,220	2,220	2,220	3,240	10,000	11,000	720	2,850	3,770	3.3	13.0	17.3	3.51	
025	025	035	035	050	1,500	1,500	2,000	2,000	3,000	3,290	10,000	11,000	730	2,920	3,780	3.3	13.4	17.3	3.42	
025	035	035	035	035	1,580	2,110	2,110	2,110	2,110	3,240	10,000	11,000	720	2,910	3,770	3.3	13.3	17.3	3.44	

- Specifications may be subject to change without prior notice.
- Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
- Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
- Combination table capacity based on connecting Wind-Free AR9500 Wall mounted indoor range (AJxxxTNAPKH).
- Minimum two indoor units should be connected to outdoor unit for system operation.
- Power consumption include indoor unit power.

# Connection Combination

## AJ125TXJ5KH/EA Cooling

Unit	Indoor Unit					Cooling Capacity (W)					Capacity			Power Consumption			Current			EER
	A	B	C	D	E	A	B	C	D	E	W			W			A			W/W
											MIN	Rated	MAX	MIN	Rated	MAX	MIN	Rated	MAX	Rated
1	020					2,000					2,490	2,000	2,600	660	730	790	3.0	3.3	3.6	2.74
	025					2,500					2,490	2,500	3,200	660	890	970	3.0	4.1	4.4	2.81
	035					3,500					2,490	3,500	3,800	660	1,160	1,250	3.0	5.3	5.7	3.02
	050					5,000					2,780	5,000	6,100	680	1,670	1,810	3.1	7.6	8.3	2.99
	068					6,200					2,780	6,200	7,600	680	2,120	2,300	3.1	9.7	10.5	2.92
2	020	020				2,050	2,050				2,640	4,100	4,310	650	1,140	1,250	3.0	5.2	5.7	3.60
	020	025				2,050	2,640				2,640	4,690	4,920	651	1,250	1,380	3.0	5.7	6.3	3.75
	020	035				2,050	3,520				2,640	5,570	5,850	652	1,460	1,610	3.0	6.7	7.4	3.82
	020	050				1,980	5,080				2,640	7,060	7,420	654	1,800	1,980	3.0	8.2	9.1	3.92
	020	068				1,920	6,580				2,640	8,500	8,920	655	2,720	2,990	3.0	12.4	13.7	3.13
	025	025				2,640	2,640				2,640	5,280	5,540	656	1,350	1,490	3.0	6.2	6.8	3.91
	025	035				2,640	3,510				2,640	6,150	6,460	657	1,560	1,720	3.0	7.1	7.9	3.94
	025	050				2,550	5,100				2,640	7,650	8,030	659	2,260	2,490	3.0	10.3	11.4	3.38
	025	068				2,480	6,610				2,640	9,090	9,540	660	2,880	3,170	3.0	13.2	14.5	3.16
	035	035				3,520	3,520				2,640	7,030	7,390	661	1,770	1,950	3.0	8.1	8.9	3.97
	035	050				3,410	5,120				2,640	8,530	8,960	663	2,560	2,820	3.0	11.7	12.9	3.33
	035	068				3,320	6,640				2,640	9,960	10,460	664	3,420	3,760	3.0	15.7	17.2	2.91
	050	050				5,010	5,010				2,640	10,020	10,520	668	3,100	3,410	3.1	14.2	15.6	3.23
	050	068				4,910	6,550				2,640	11,460	12,030	669	3,520	3,870	3.1	16.1	17.7	3.26
068	068				5,800	5,800				2,640	11,600	13,100	670	3,870	4,670	3.1	17.7	21.4	3.00	
3	020	020	020			2,050	2,050	2,050			2,780	6,150	6,460	600	1,860	2,050	2.7	8.5	9.4	3.31
	020	020	025			2,050	2,050	2,640			2,780	6,740	7,080	600	2,000	2,200	2.7	9.2	10.1	3.37
	020	020	035			2,050	2,050	3,520			2,780	7,620	8,000	600	2,220	2,440	2.7	10.2	11.2	3.43
	020	020	050			2,050	2,050	5,280			2,780	9,380	9,850	600	2,750	3,030	2.7	12.6	13.9	3.41
	020	020	068			2,050	2,050	7,040			2,780	11,140	11,690	600	3,660	4,590	2.7	16.8	21.0	3.04
	020	025	025			2,050	2,640	2,640			2,780	7,330	7,690	600	2,120	2,330	2.7	9.7	10.7	3.46
	020	025	035			2,050	2,640	3,520			2,780	8,210	8,620	600	2,370	2,610	2.7	10.8	11.9	3.46
	020	025	050			2,050	2,640	5,270			2,780	9,960	10,460	600	2,890	3,180	2.7	13.2	14.6	3.45
	020	025	068			2,030	2,610	6,960			2,780	11,600	12,310	600	3,740	4,610	2.7	17.1	21.1	3.10
	020	035	035			2,050	3,520	3,520			2,780	9,090	9,540	600	2,730	3,000	2.7	12.5	13.7	3.33
	020	035	050			2,050	3,520	5,270			2,780	10,840	11,390	600	3,390	3,730	2.7	15.5	17.1	3.20
	020	035	068			1,890	3,240	6,470			2,780	11,600	13,100	600	3,870	4,670	2.7	17.7	21.4	3.00
	020	050	050			1,890	4,860	4,860			2,780	11,600	13,100	600	3,870	4,670	2.7	17.7	21.4	3.00
	020	050	068			1,660	4,260	5,680			2,780	11,600	13,100	600	3,870	4,670	2.7	17.7	21.4	3.00
	020	068	068			1,540	5,280	5,280			2,780	12,100	13,700	600	3,910	4,710	2.7	17.9	21.6	3.09
	025	025	025			2,640	2,640	2,640			2,780	7,910	8,310	600	2,220	2,440	2.7	10.2	11.2	3.56
	025	025	035			2,640	2,640	3,520			2,780	8,790	9,230	600	2,520	2,770	2.7	11.5	12.7	3.49
	025	025	050			2,640	2,640	5,280			2,780	10,550	11,080	600	3,050	3,360	2.7	14.0	15.4	3.46
	025	025	068			2,490	2,490	6,630			2,780	11,600	12,920	600	3,780	4,640	2.7	17.3	21.2	3.07
	025	035	035			2,640	3,520	3,520			2,780	9,670	10,160	600	2,870	3,160	2.7	13.1	14.5	3.37
	025	035	050			2,640	3,520	5,280			2,780	11,430	12,000	600	3,700	4,590	2.7	16.9	21.0	3.09
	025	035	068			2,320	3,090	6,190			2,780	11,600	13,100	600	3,870	4,670	2.7	17.7	21.4	3.00
	025	050	050			2,320	4,640	4,640			2,780	11,600	13,100	600	3,870	4,670	2.7	17.7	21.4	3.00
	025	050	068			2,140	4,270	5,690			2,780	12,100	13,700	600	3,910	4,710	2.7	17.9	21.6	3.09
	025	068	068			1,910	5,090	5,090			2,780	12,100	13,700	600	3,910	4,710	2.7	17.9	21.6	3.09
	035	035	035			3,520	3,520	3,520			2,780	10,550	11,080	600	3,370	3,710	2.7	15.4	17.0	3.13
	035	035	050			3,310	3,310	4,970			2,780	11,600	12,920	600	3,820	4,640	2.7	17.5	21.2	3.04
035	035	068			2,900	2,900	5,800			2,780	11,600	13,100	600	3,870	4,670	2.7	17.7	21.4	3.00	
035	050	050			2,900	4,350	4,350			2,780	11,600	13,100	600	3,870	4,670	2.7	17.7	21.4	3.00	
035	050	068			2,690	4,030	5,380			2,780	12,100	13,700	600	3,910	4,710	2.7	17.9	21.6	3.09	
035	068	068			2,420	4,840	4,840			2,780	12,100	13,700	600	3,910	4,710	2.7	17.9	21.6	3.09	
050	050	050			4,030	4,030	4,030			2,780	12,100	13,700	600	3,910	4,710	2.7	17.9	21.6	3.09	
050	050	068			3,630	3,630	4,840			2,780	12,100	13,700	600	3,910	4,710	2.7	17.9	21.6	3.09	

- Specifications may be subject to change without prior notice.
- Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
- Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
- Combination table capacity based on connecting Wind-Free AR9500 Wall mounted indoor range (AJxxxTNAPKH).
- Minimum two indoor units should be connected to outdoor unit for system operation.
- Power consumption include indoor unit power.

# Connection Combination

## AJ125TXJ5KH/EA Cooling

Unit	Indoor Unit					Cooling Capacity (W)					Capacity			Power Consumption			Current			EER
	A	B	C	D	E	A	B	C	D	E	W			W			A			W/W
											MIN	Rated	MAX	MIN	Rated	MAX	MIN	Rated	MAX	Rated
4	020	020	020	020		2,050	2,050	2,050	2,050		3,000	8,210	9,030	700	2,600	2,860	3.2	11.9	13.1	3.16
	020	020	020	025		2,050	2,050	2,050	2,640		3,000	8,790	9,670	700	2,760	3,040	3.2	12.6	13.9	3.18
	020	020	020	035		2,050	2,050	2,050	3,520		3,000	9,670	10,640	700	3,140	3,450	3.2	14.4	15.8	3.08
	020	020	020	050		2,050	2,050	2,050	5,280		3,000	11,430	12,570	700	4,080	4,490	3.2	18.7	20.5	2.80
	020	020	020	068		1,880	1,880	1,880	6,450		3,000	12,100	13,700	700	3,910	4,710	3.2	17.9	21.6	3.09
	020	020	025	025		2,050	2,050	2,640	2,640		3,000	9,380	10,320	700	2,980	3,280	3.2	13.6	15.0	3.15
	020	020	025	035		2,050	2,050	2,640	3,520		3,000	10,260	11,280	700	3,300	3,630	3.2	15.1	16.6	3.11
	020	020	025	050		2,050	2,050	2,640	5,280		3,000	12,020	13,220	700	4,100	4,510	3.2	18.8	20.6	2.93
	020	020	025	068		1,800	1,800	2,320	6,180		3,000	12,100	13,700	700	3,910	4,710	3.2	17.9	21.6	3.09
	020	020	035	035		2,050	2,050	3,520	3,520		3,000	11,140	12,250	700	4,060	4,470	3.2	18.6	20.5	2.74
	020	020	035	050		1,950	1,950	3,300	4,950		3,000	12,100	13,700	700	3,910	4,710	3.2	17.9	21.6	3.09
	020	020	035	068		1,690	1,690	2,900	5,810		3,000	12,100	13,700	700	3,910	4,710	3.2	17.9	21.6	3.09
	020	020	050	050		1,690	1,690	4,360	4,360		3,000	12,100	13,700	700	3,910	4,710	3.2	17.9	21.6	3.09
	020	020	050	068		1,560	1,560	4,020	5,360		3,000	12,500	14,100	700	3,950	4,750	3.2	18.1	21.7	3.16
	020	025	025	025		2,050	2,640	2,640	2,640		3,000	9,960	10,960	700	3,140	3,450	3.2	14.4	15.8	3.17
	020	025	025	035		2,050	2,640	2,640	3,520		3,000	10,840	11,930	700	4,030	4,430	3.2	18.4	20.3	2.69
	020	025	025	050		1,970	2,530	2,530	5,070		3,000	12,100	13,700	700	3,910	4,710	3.2	17.9	21.6	3.09
	020	025	025	068		1,730	2,220	2,220	5,930		3,000	12,100	13,700	700	3,910	4,710	3.2	17.9	21.6	3.09
	020	025	035	035		2,050	2,640	3,520	3,520		3,000	11,720	12,900	700	4,080	4,490	3.2	18.7	20.5	2.87
	020	025	035	050		1,840	2,370	3,160	4,730		3,000	12,100	13,700	700	3,910	4,710	3.2	17.9	21.6	3.09
	020	025	035	068		1,680	2,160	2,880	5,770		3,000	12,500	14,100	700	3,950	4,750	3.2	18.1	21.7	3.16
	020	025	050	050		1,680	2,160	4,330	4,330		3,000	12,500	14,100	700	3,950	4,750	3.2	18.1	21.7	3.16
	020	025	050	068		1,510	1,940	3,880	5,170		3,000	12,500	14,100	700	3,950	4,750	3.2	18.1	21.7	3.16
	020	035	035	035		1,970	3,380	3,380	3,380		3,000	12,100	13,700	700	3,910	4,710	3.2	17.9	21.6	3.09
	020	035	035	050		1,730	2,960	2,960	4,440		3,000	12,100	13,700	700	3,910	4,710	3.2	17.9	21.6	3.09
	020	035	035	068		1,590	2,730	2,730	5,450		3,000	12,500	14,100	700	3,950	4,750	3.2	18.1	21.7	3.16
	020	035	050	050		1,590	2,730	4,090	4,090		3,000	12,500	14,100	700	3,950	4,750	3.2	18.1	21.7	3.16
	020	035	050	068		1,430	2,460	3,690	4,920		3,000	12,500	14,100	700	3,950	4,750	3.2	18.1	21.7	3.16
	020	050	050	050		1,430	3,690	3,690	3,690		3,000	12,500	14,100	700	3,950	4,750	3.2	18.1	21.7	3.16
	025	025	025	025		2,640	2,640	2,640	2,640		3,000	10,550	11,610	700	3,300	3,630	3.2	15.1	16.6	3.20
	025	025	025	035		2,640	2,640	2,640	3,520		3,000	11,430	12,570	700	4,060	4,470	3.2	18.6	20.5	2.82
	025	025	025	050		2,420	2,420	2,420	4,840		3,000	12,100	13,700	700	3,910	4,710	3.2	17.9	21.6	3.09
	025	025	025	068		2,210	2,210	2,210	5,880		3,000	12,500	14,100	700	3,950	4,750	3.2	18.1	21.7	3.16
	025	025	035	035		2,590	2,590	3,460	3,460		3,000	12,100	13,540	700	3,910	4,520	3.2	17.9	20.7	3.09
	025	025	035	050		2,270	2,270	3,030	4,540		3,000	12,100	13,700	700	3,910	4,710	3.2	17.9	21.6	3.09
	025	025	035	068		2,080	2,080	2,780	5,560		3,000	12,500	14,100	700	3,950	4,750	3.2	18.1	21.7	3.16
	025	025	050	050		2,080	2,080	4,170	4,170		3,000	12,500	14,100	700	3,950	4,750	3.2	18.1	21.7	3.16
	025	025	050	068		1,880	1,880	3,750	5,000		3,000	12,500	14,100	700	3,950	4,750	3.2	18.1	21.7	3.16
	025	035	035	035		2,420	3,230	3,230	3,230		3,000	12,100	13,700	700	3,910	4,710	3.2	17.9	21.6	3.09
	025	035	035	050		2,210	2,940	2,940	4,410		3,000	12,500	14,100	700	3,950	4,750	3.2	18.1	21.7	3.16
025	035	035	068		1,970	2,630	2,630	5,260		3,000	12,500	14,100	700	3,950	4,750	3.2	18.1	21.7	3.16	
025	035	050	050		1,970	2,630	3,950	3,950		3,000	12,500	14,100	700	3,950	4,750	3.2	18.1	21.7	3.16	
025	050	050	050		1,790	3,570	3,570	3,570		3,000	12,500	14,100	700	3,950	4,750	3.2	18.1	21.7	3.16	
035	035	035	035		3,030	3,030	3,030	3,030		3,000	12,100	13,700	700	3,910	4,710	3.2	17.9	21.6	3.09	
035	035	035	050		2,780	2,780	2,780	4,170		3,000	12,500	14,100	700	3,950	4,750	3.2	18.1	21.7	3.16	
035	035	035	068		2,500	2,500	2,500	5,000		3,000	12,500	14,100	700	3,950	4,750	3.2	18.1	21.7	3.16	
035	035	050	050		2,500	2,500	3,750	3,750		3,000	12,500	14,100	700	3,950	4,750	3.2	18.1	21.7	3.16	

1. Specifications may be subject to change without prior notice.
2. Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
3. Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
4. Combination table capacity based on connecting Wind-Free AR9500 Wall mounted indoor range (AJxxxTNAPKH).
5. Minimum two indoor units should be connected to outdoor unit for system operation.
6. Power consumption include indoor unit power.

# Connection Combination

## AJ125TXJ5KH/EA Cooling

Unit	Indoor Unit					Cooling Capacity (W)					Capacity			Power Consumption			Current			EER
	A	B	C	D	E	A	B	C	D	E	W			W			A			W/W
											MIN	Rated	MAX	MIN	Rated	MAX	MIN	Rated	MAX	Rated
5	020	020	020	020	020	2,050	2,050	2,050	2,050	2,050	3,000	10,260	11,280	700	3,330	3,660	3.2	15.2	16.8	3.08
	020	020	020	020	025	2,050	2,050	2,050	2,050	2,640	3,000	10,840	11,930	700	4,060	4,470	3.2	18.6	20.5	2.67
	020	020	020	020	035	2,050	2,050	2,050	2,050	3,520	3,000	11,720	12,900	700	4,110	4,520	3.2	18.8	20.7	2.85
	020	020	020	020	050	1,900	1,900	1,900	1,900	4,890	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	020	020	020	068	1,680	1,680	1,680	1,680	5,770	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	020	020	025	025	2,050	2,050	2,050	2,640	2,640	3,000	11,430	12,570	700	4,090	4,500	3.2	18.7	20.6	2.79
	020	020	020	025	035	2,050	2,050	2,050	2,640	3,520	3,000	12,310	13,540	700	4,140	4,550	3.2	18.9	20.8	2.97
	020	020	020	025	050	1,820	1,820	1,820	2,340	4,690	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	020	020	025	068	1,620	1,620	1,620	2,080	5,560	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	020	020	035	035	1,940	1,940	1,940	3,330	3,330	3,000	12,500	14,100	700	3,950	4,750	3.2	18.1	21.7	3.16
	020	020	020	035	050	1,720	1,720	1,720	2,940	4,410	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	020	020	035	068	1,540	1,540	1,540	2,630	5,260	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	020	020	050	050	1,540	1,540	1,540	3,950	3,950	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	020	025	025	025	2,050	2,050	2,640	2,640	2,640	3,000	12,020	13,220	700	4,110	4,520	3.2	18.8	20.7	2.92
	020	020	025	025	035	1,990	1,990	2,560	2,560	3,410	3,000	12,500	14,100	700	3,950	4,750	3.2	18.1	21.7	3.16
	020	020	025	025	050	1,750	1,750	2,250	2,250	4,500	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	020	025	025	068	1,560	1,560	2,010	2,010	5,360	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	020	025	035	035	1,860	1,860	2,390	3,190	3,190	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	020	025	035	050	1,650	1,650	2,120	2,830	4,250	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	020	025	035	068	1,480	1,480	1,910	2,540	5,080	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	020	025	050	050	1,480	1,480	1,910	3,810	3,810	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	020	035	035	035	1,750	1,750	3,000	3,000	3,000	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	020	035	050	050	1,560	1,560	2,680	2,680	4,020	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	020	035	050	050	1,410	1,410	2,420	3,630	3,630	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	025	025	025	025	2,030	2,620	2,620	2,620	2,620	3,000	12,500	13,860	700	3,950	4,550	3.2	18.1	20.8	3.16
	020	025	025	025	035	1,900	2,450	2,450	2,450	3,260	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	025	025	025	050	1,680	2,160	2,160	2,160	4,330	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	025	025	025	068	1,510	1,940	1,940	1,940	5,170	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	025	025	035	035	1,790	2,300	2,300	3,060	3,060	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	025	025	035	050	1,590	2,050	2,050	2,730	4,090	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	025	025	035	068	1,430	1,840	1,840	2,460	4,920	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	025	025	050	050	1,430	1,840	1,840	3,690	3,690	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	025	035	035	035	1,680	2,160	2,880	2,880	2,880	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	025	035	035	050	1,510	1,940	2,590	2,590	3,880	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	035	035	035	035	1,590	2,730	2,730	2,730	2,730	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	020	035	035	035	050	1,430	2,460	2,460	2,460	3,690	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	025	025	025	025	025	2,500	2,500	2,500	2,500	2,500	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	025	025	025	025	035	2,340	2,340	2,340	2,340	3,130	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	025	025	025	025	050	2,080	2,080	2,080	2,080	4,170	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
	025	025	025	025	068	1,880	1,880	1,880	1,880	5,000	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16
025	025	025	035	035	2,210	2,210	2,210	2,940	2,940	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16	
025	025	025	035	050	1,970	1,970	1,970	2,630	3,950	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16	
025	025	025	050	050	1,790	1,790	1,790	3,570	3,570	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16	
025	025	035	035	035	2,080	2,080	2,780	2,780	2,780	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16	
025	025	035	035	050	1,880	1,880	2,500	2,500	3,750	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16	
025	035	035	035	035	1,970	2,630	2,630	2,630	2,630	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16	
035	035	035	035	035	2,500	2,500	2,500	2,500	2,500	3,000	12,500	14,500	700	3,950	4,870	3.2	18.1	22.3	3.16	

1. Specifications may be subject to change without prior notice.
2. Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
3. Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
4. Combination table capacity based on connecting Wind-Free AR9500 Wall mounted indoor range (AJxxxTNAPKH).
5. Minimum two indoor units should be connected to outdoor unit for system operation.
6. Power consumption include indoor unit power.