

# Slim ducted



Model			AJ026TNLDKH/EA	AJ035TNLDKH/EA	AJ052TNLDKH/EA
Rated Capacity	Cooling	kW	2.6	3.5	5.2
	Heating	kW	2.9	3.8	5.6
Air Flow Rate	H/M/L	L/s	152 / 128 / 95	158 / 130 / 103	233 / 163 / 90
Static Pressure	Min/Std/Max	Pa	0 / 19.6 / 39.2	0 / 19.6 / 39.2	0 / 19.6 / 50.0
Sound Pressure	H/M/L	dBA	32 / 27 / 22	33 / 28 / 23	33 / 29 / 23
Sound Power		dBA	50	50	50
Dimensions	WxHxD	mm	700 x 199 x 440	700 x 199 x 440	900 x 199 x 440
Unit Weight		kg	14.8	14.8	18.9
Piping Connections	Liquid	mm (inch)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)
	Gas	mm (inch)	9.52 (3/8)	9.52 (3/8)	12.7 (1/2)
Drain Pump (sold separately)			Not available		
Controls			Sold separately		

Images are for illustration purposes. Product images may be different to actual product, product sizes vary depending on model. Specifications may be subject to change without prior notice.

- 1) Capacities are based on (Equivalent refrigerant piping: 5m, Level differences: 0m).
  - Cooling: Indoor temperature: 27°C DB, 19°C WB / Outdoor temperature: 35°C DB, 24°C WB.
  - Heating: Indoor temperature: 20°C DB, 15°C WB / Outdoor temperature: 7°C DB, 6°C WB.
- 2) Select wire size based on the value of MCA.
- 3) Sound pressure level is obtained in an anechoic room.
  - Sound pressure level is a relative value, depending on the distance and acoustic environment.
  - Sound pressure level may differ depending on operation condition.
  - dBA = A-weighted sound pressure level.
  - Reference acoustic pressure 0 dB = 20uPa.
- 4) Sound power level is an absolute value that a sound source generates.
  - dBA = A-weighted sound power level.
  - Reference power: 1pW.
  - Measured according to ISO 3741.
- 5) These products contain R410A (GWP=2,088) which is fluorinated greenhouse gas.