

Wind-Free™ 1-Way Cassette



Specifications

- 2-Step Cooling: Fast Cooling & Wind-Free™ Cooling.
- Blade angle between 37° and 87°, blade width 100 mm.
- Built-in humidity sensor.
- Height of only 152 mm.
- Built-in condensation drain pump (750 mmH2O).



Indoor Unit		AC026RN1DKG/EU	AC035RN1DKG/EU	
Outdoor Unit - Mono-Phase		AC026RXADKG/EU	AC035RXADKG/EU	
Outdoor Unit - Tri-Phase				
Capacity				
Cooling (Min/Nominal/Max)	kW	0.82/2.60/3.80	0.85/3.50/4.20	
Heating @ +7 °C (Min/Nominal/Max)	kW	0.98/3.30/4.40	1.00/4.00/5.00	
Heating @ -5 °C	kW	3.2	3.9	
Heating @ -15 °C	kW	2.9	2.8	
Performance				
Energy Efficiency Cooling	SEER ¹	6.4 A++	6.2 A++	
	Power Consumption	kWh/a	142	198
	Pdesignc	kW	2.60	3.50
	EER	W/W	3.61	3.21
Energy Efficiency Heating	SCOP ¹	4.0 A+	4.0 A+	
	Power Consumption	kWh/a	700	700
	Pdesignh (average)	kW	2.0	2.0
	COP ¹	W/W	3.26	3.12
Airflow Rate	Indoor Unit (H/M/L)	m ³ /min	7.3/6.5/5.8	9.0/8.2/7.2
Sound Power	Indoor Unit	dB(A)	52	55
	Outdoor Unit	dB(A)	59	61
Sound Pressure	Indoor Unit (H/M/L/Silent)	dB(A)	32/29/26/25	35/32/29/28
	Outdoor Unit (H/L)	dB(A)	47/46	48/48
Fan/Outdoor Unit	Type		Crossflow Fan	Crossflow Fan
	Power	W	27	27
	Number of Fans	-	1	1
External Static Pressure	Min/Std/Max	Pa		
Operating Temperature Range	Cooling	°C	-15~46	-15~46
	Heating	°C	-20.0~24.0	-20.0~24.0
Electrical Data				
Power Source	Indoor Unit	Φ, #, V, Hz	1Φ, 2, 220-240 V, 50 Hz	1Φ, 2, 220-240 V, 50 Hz
	Outdoor Unit Mono-Phase	Φ, #, V, Hz	1Φ, 2, 220-240 V, 50 Hz	1Φ, 2, 220-240 V, 50 Hz
	Outdoor Unit Tri-Phase	Φ, #, V, Hz		
Compressor Type	Outdoor Unit	Type	Single BLDC	Single BLDC
Power (Min/Nominal/Max)	Cooling	kW	0.17/0.72/1.16	0.18/1.09/1.40
	Heating	kW	0.20/1.01/1.45	0.19/1.28/1.80
Current Input	Cooling (Min/Std/Max)	A	1.2/3.8/5.4	1.6/5.3/7.5
	Heating (Min/Std/Max)	A	1.4/5.0/7.0	1.3/6.2/10.5
	Cooling - Tri-Phase (Min/Std/Max)	A		
	Heating - Tri-Phase (Min/Std/Max)	A		
Dimensions				
Net Dimensions (W x H x D)	Indoor Unit	mm	970 x 135 x 410	970 x 135 x 410
	Outdoor Unit	mm	790 x 548 x 285	790 x 548 x 285
Net Weight	Indoor Unit	kg	9.2	9.2
	Outdoor Unit	kg	32.5	32.5

Indoor Unit		AC026RN1DKG/EU	AC035RN1DKG/EU
Outdoor Unit - Mono-Phase		AC026RXADKG/EU	AC035RXADKG/EU
Outdoor Unit - Tri-Phase			
Refrigerant			
Refrigerant	Type	R32 (contains fluorinated greenhouse gases. GWP = 675)	
	Factory Charging	kg	0.9/2.0 m
	Charging Ton equivalent CO ₂	tCO ₂ e	0.61
	Additional Refrigerant Charging	g/m	-
Piping Connections	Liquid Pipe	ø, inch	1/4
	Gas Pipe	ø, inch	3/8
Piping Length	Min/Max	m	3/20
Piping Height	Max	m	15
Piping Connections	Drain Pipe	ø, mm	ID 18
Others			
Panel	Model Code		PC1NWFMAN
	Net Dimensions (W x H x D)	mm	1,198 x 35 x 500
	Net Weight	kg	4.3
Accessories	Drain Pump		Included
	Max. Lifting Height/Displacement	mm / litres/h	750/24

Accessories						
Wireless Remote Controller	Simple Type Controller	Touch Controller	Advanced Wired Controller	Wi-Fi Kit	Panel (Mandatory)	External Thermostat
AR-EH03E	MWR-SH00N	MWR-SH11N	MWR-WG00JN/ MWR-WG00KN	MIM-H04EN	PC4NUNMAN	MRW-TA

¹Energy labels as shown are according to EU No 626/2011 (LOT10) label classification 2019, on a scale from D to A+++.

Copyright © 2020 Samsung Electronics Air Conditioner Europe B.V. All rights reserved. Samsung is a registered trademark of Samsung Electronics Co., Ltd. Specifications and designs are subject to change without notice and may include preliminary information. Non-metric weights and measurements are approximate. All data was deemed correct at the time of creation. Samsung is not liable for errors or omissions. Some images may be digitally altered. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognised and acknowledged.

Samsung Electronics Air Conditioner Europe B.V.
 Evert van de Beekstraat 310, 1118 CX Schiphol
 P.O. Box 75810, 1118 ZZ Schiphol
 +31 (0)8 81 41 61 00
 The Netherlands