


XÜØ

Technical Data Book

ÖXT ÀÁÚ~ çå[[!Á } ãfor Europe (GŠæ^!ÊË €P: ÊË ÆËÊË ÆË)



Model : H/P High EER type (AM*JXVHGH*EU, AM*** HXVAGH/EU)**

H/P Standard type (AM*JXVAGH*EU, AM*** HXVAGH/EU)**

H/R High EER type (AM*JXVHGR*EU)**

History

Version	Modification	Date	Remark
Ver.1.0	Released DVM S(2 Layer) TDB	15.05.22	
Ver.1.1	Modified the size of pipe connections in Specification (for 24HP)	15.06.02	
Ver.1.2	Add Note information in Specification regarding EU F-Gas regulation	15.06.16	
Ver.1.3	Added ODU combination models (H/P - High EER type) - Model added : 24HP*, 26HP*, 40HP* - Combination changed : 60HP	15.09.03	

Nomenclature

Outdoor Units

Model Names

AM	080	J	X	V	A	G	H	/	EU
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)		Buyer

(1) Classification

AM	VRF
----	-----

(2) Capacity

x 1/10 HP (3 digits)

(3) Version

F	2013
H	2014
J	2015

(4) Product Type

X	Outdoor Unit
N	Indoor Unit

(5) Feature1

V	Inverter
M	DVM S Eco

(6) Feature2

A	Standard
H	High EER



















(7) Rating Voltage

E	1Ø, 220~240V, 50Hz
G	3Ø, 380~415V, 50Hz











(8) Mode

H	Heat Pump
R	Heat Recovery







Accessory

Classification	Product	Image	Model	Remark
Integrated Management System	DMS 2.0		MIM-D00AN	-
	S-NET 3		MST-P3P	-
	PIM		MIM-B16N	-
Building Management System	BACnet Gateway		MIM-B17N	-
	LonWorks Gateway		MIM-B18N	-
Centralized Control System	On/Off controller		MCM-A202DN	-
	Touch controller		MCM-A300N	-
Individual Control System	Wireless remote controller		MR-EH00	-
	Wired remote controller		MWR-WE10N (Multi function)	A/C+VTL
			MWR-WW00N	DVM S Hydro Unit
	Simplified wired remote controller		MWR-SH00N	-
			MWR-VH02	ERV
Others	Operation mode selection switch		MCM-C200	DVM S Series (Except HR Models)
	External room sensor		MRW-TA	Cassette, Wall-mount, Ceiling, Duct, Console
	Compatible interface module		MIM-N01	Nasa-No Nasa
	ERV interface module		MIM-N10	ERV (Nasa)
	External contact interface module		MIM-B14	-
	S-Converter		MIM-C02N	-
	MTFC (Multi tenant function controller)		MCM-C210N	-
	Wireless signal receiver		MRK-A10N	-

Accessory

Product	Image	Model	Remark
Y-Joint		MXJ-YA1509M	15.0 kW and below
		MXJ-YA2512M	Over 15.0 kW~40.0 kW and below
		MXJ-YA2812M	Over 40.0 kW~45.0 kW and below
		MXJ-YA2815M	Over 45.0 kW~70.3 kW and below
		MXJ-YA3419M	Over 70.3 kW~98.4 kW and below
		MXJ-YA4119M	Over 98.4 kW~135.2 kW and below
		MXJ-YA4422M	Over 135.2 kW
Y-Joint (Only H/R)		MXJ-YA1500M	22.4 kW and below
		MXJ-YA2500M	Over 22.4 kW~70.3 kW and below
		MXJ-YA3100M	Over 70.3 kW~135.2 kW and below
		MXJ-YA3800M	Over 135.2 kW
Y-Joint Outdoor unit		MXJ-TA3419M	135.2 kW and below
		MXJ-TA4122M	140.2 kW and Over
Y-Joint (Only H/R) Outdoor unit		MXJ-TA3100M	135.2 kW and below
		MXJ-TA3800M	140.2 kW and Over
Distribution Header		MXJ-HA2512M	45.0 kW and below (for 4 rooms)
		MXJ-HA3115M	70.3 kW and below (for 8 rooms)
		MXJ-HA3819M	Over 70.3 kW~135.2 kW and below(for 8 rooms)
MCU		MCU-S6NEE1N	~56kW, ~6 indoor units
		MCU-S4NEE1N	~56kW, ~4 indoor units
		MCU-S4NEE2N	56kW, ~2 indoor units(each indoor unit for 11.2kW~28kW)
EEV KIT		MEV-E24SA	1 Indoor
		MEV-E32SA	
		MXD-E24K132A	2 Indoor
		MXD-E24K200A	
		MXD-E32K200A	
		MXD-E24K232A	3 Indoor
		MXD-E24K300A	
		MXD-E32K224A	
		MXD-E32K300A	
AHU KIT		MXD-K025AN	7.0kW~8.75kW
		MXD-K050AN	14.0kW~17.5kW
		MXD-K075AN	21.0kW~26.25kW
		MXD-K100AN	28.0kW~35.0kW
		MCM-D201N	28kW~35kW / 56kW~70kW / 84kW~105kW / 112kW~140kW

Accessory

Product	Image	Model	Remark
PDM KIT		MXD-A38K2A	8~12HP
		MXD-A12K2A	14~16HP
		MXD-A58K2A	18~26HP
S-Plasma Ion KIT		MSD-CAN1	4Way Cassette S 4Way Cassette S(600x600)
		MSD-EAN1	ERV-Plus
Motion detect Sensor		MCR-SMA	4Way Cassette S (600x600)
ERV CO2 Sensor		MOS-C1	ERV, ERV PLUS
Drain Pump		MDP-N047SNC0D	OAP Duct (14.0 kW)
		MDP-N047SNC1D	HSP Duct (22.0 / 28.0 kW) OAP Duct (22.4 / 28.0 kW)
		MDP-M075SGU1D	MSP Duct (9.0 / 11.2 kW)
		MDP-M075SGU2D	MSP Duct (12.8 / 14.0 kW) HSP Duct (11.2 / 12.8 / 14.0 kW)
		MDP-M075SGU3D	MSP Duct (5.6 / 7.1 kW)
		MDP-E075SEE3D	Slim Duct (2.0~14.0 kW)
		MDP-G075SP	Duct S (External, All Capacities)
		MDP-G075SQ	Duct S (Internal, 3.5 kW~14 kW)
Panel		PC1NUSMAN	Slim 1Way Cassette
		PC1NUPMAN	Slim 1Way Cassette (Z-sliding)
		PC1MWSKAN	1Way Cassette (1.7 kW, 2.2 kW)
		PC2NUSMEN	2Way cassette
		PC4SUSMAN	4Way Cassette S(600x600) (Waffle)
		PC4SUSMEN	4Way Cassette S(600x600) (Classic)
		PC4NUSKAN	4 Way cassette S (Waffle)
		PC4NUSKEN	4 Way cassette S (Classic)
		PC4NBSKAN	4 Way cassette S (Waffle, Black)

Outdoor

1 Line-up

2 Specifications

3 Operation limit

4 Dimensional drawing

5 Electrical wiring diagram

6 Sound pressure level

7 Sound power level

8 Cycle diagram

JAN • call • Á

1 Line-up

Heat Pump - High EER type

System Model			Outdoor Unit Selection									
Capacity	System Model Code	Number of Modules	8HP	10HP	12HP	14HP	16HP	18HP	20HP	22HP	24HP	26HP
			AM080JXVHGH/EU	AM100JXVHGH/EU	AM120JXVHGH/EU	AM140JXVHGH/EU	AM160JXVHGH/EU	AM180JXVHGH/EU	AM200JXVHGH/EU	AM220JXVHGH/EU	AM240HXVAGH/EU	AM260HXVAGH/EU
8HP	-	1	1									
10HP	-	1		1								
12HP	-	1			1							
14HP	-	1				1						
16HP	-	1					1					
18HP	-	1						1				
20HP	-	1							1			
22HP	-	1								1		
24HP	-	1									1	
26HP	-	1										1
24HP*	AM240JXVHGH1EU*	2			2							
26HP*	AM260JXVHGH1EU*	2			1	1						
28HP	AM280JXVHGH1EU	2			1		1					
30HP	AM300JXVHGH1EU	2			1			1				
32HP	AM320JXVHGH1EU	2			1				1			
34HP	AM340JXVHGH1EU	2			1					1		
36HP	AM360JXVHGH1EU	2				1				1		
38HP	AM380JXVHGH1EU	2					1			1		
40HP	AM400JXVHGH1EU	2				1						1
40HP*	AM400JXVHGH1EU*	2							2			
42HP	AM420JXVHGH1EU	2							1	1		
44HP	AM440JXVHGH1EU	2								2		
46HP	AM460JXVHGH1EU	3			2					1		
48HP	AM480JXVHGH1EU	3			1	1				1		
50HP	AM500JXVHGH1EU	3			1		1			1		
52HP	AM520JXVHGH1EU	3			1			1		1		
54HP	AM540JXVHGH1EU	3			1				1	1		
56HP	AM560JXVHGH1EU	3			1					2		
58HP	AM580JXVHGH1EU	3				1				2		
60HP	AM600JXVHGH1EU	3					1			2		
62HP	AM620JXVHGH1EU	3							2	1		
64HP	AM640JXVHGH1EU	3							1	2		
66HP	AM660JXVHGH1EU	3								3		
68HP	AM680JXVHGH1EU	4			2					2		
70HP	AM700JXVHGH1EU	4			1	1				2		
72HP	AM720JXVHGH1EU	4			1		1			2		
74HP	AM740JXVHGH1EU	4			1			1		2		
76HP	AM760JXVHGH1EU	4			1				1	2		
78HP	AM780JXVHGH1EU	4			1					3		
80HP	AM800JXVHGH1EU	4				1				3		

FOR DRYXPÖPFÖVÄU` c[[! Ä, ä/ { ä ä } Äe Ä^} Ää^äÄ

1 Line-up

Heat Pump - High EER type (Compact)

System Model			Outdoor Unit Selection									
Capacity	System Model Code	Number of Modules	8HP	10HP	12HP	14HP	16HP	18HP	20HP	22HP	24HP	26HP
			AM080JXVH GH/EU	AM100JXVH GH/EU	AM120JXVH GH/EU	AM140JXVH GH/EU	AM160JXVH GH/EU	AM180JXVH GH/EU	AM200JXVH GH/EU	AM220JXVH GH/EU	AM240HXV AGH/EU	AM260HXV AGH/EU
36HP	AM360JXVHGH2EU	2			1						1	
38HP	AM380JXVHGH2EU	2			1							1
46HP	AM460JXVHGH2EU	2							1			1
48HP	AM480JXVHGH2EU	2								1		1
50HP	AM500JXVHGH2EU	2									1	1
52HP	AM520JXVHGH2EU	2										2
58HP	AM580JXVHGH2EU	3			1				1			1
60HP	AM600JXVHGH2EU	3			1					1		1
62HP	AM620JXVHGH2EU	3			1						1	1
64HP	AM640JXVHGH2EU	3			1							2
68HP	AM680JXVHGH2EU	3								2	1	
70HP	AM700JXVHGH2EU	3								2		1
72HP	AM720JXVHGH2EU	3								1	1	1
74HP	AM740JXVHGH2EU	3								1		2
76HP	AM760JXVHGH2EU	3									1	2
78HP	AM780JXVHGH2EU	3										3

1 Line-up

Heat Pump - Standard type

System Model			Outdoor Unit Selection									
Capacity	System Model Code	Number of Modules	8HP	10HP	12HP	14HP	16HP	18HP	20HP	22HP	24HP	26HP
			AM080JXVAGH/EU	AM100JXVAGH/EU	AM120JXVAGH/EU	AM140JXVAGH/EU	AM160JXVAGH/EU	AM180JXVAGH/EU	AM200JXVAGH/EU	AM220JXVAGH/EU	AM240HXVAGH/EU	AM260HXVAGH/EU
8HP	-	1	1									
10HP	-	1		1								
12HP	-	1			1							
14HP	-	1				1						
16HP	-	1					1					
18HP	-	1						1				
20HP	-	1							1			
22HP	-	1								1		
24HP	-	1									1	
26HP	-	1										1
28HP	AM280JXVAGH1EU	2			1		1					
30HP	AM300JXVAGH1EU	2			1			1				
32HP	AM320JXVAGH1EU	2			1				1			
34HP	AM340JXVAGH1EU	2			1					1		
36HP	AM360JXVAGH1EU	2				1				1		
38HP	AM380JXVAGH1EU	2					1			1		
40HP	AM400JXVAGH1EU	2				1						1
42HP	AM420JXVAGH1EU	2							1	1		
44HP	AM440JXVAGH1EU	2								2		
46HP	AM460JXVAGH1EU	3			2					1		
48HP	AM480JXVAGH1EU	3			1	1				1		
50HP	AM500JXVAGH1EU	3			1		1			1		
52HP	AM520JXVAGH1EU	3			1			1		1		
54HP	AM540JXVAGH1EU	3			1				1	1		
56HP	AM560JXVAGH1EU	3			1					2		
58HP	AM580JXVAGH1EU	3				1				2		
60HP	AM600JXVAGH1EU	3					1			2		
62HP	AM620JXVAGH1EU	3						1		2		
64HP	AM640JXVAGH1EU	3							1	2		
66HP	AM660JXVAGH1EU	3								3		
68HP	AM680JXVAGH1EU	4			2					2		
70HP	AM700JXVAGH1EU	4			1	1				2		
72HP	AM720JXVAGH1EU	4			1		1			2		
74HP	AM740JXVAGH1EU	4			1			1		2		
76HP	AM760JXVAGH1EU	4			1				1	2		
78HP	AM780JXVAGH1EU	4			1					3		
80HP	AM800JXVAGH1EU	4				1				3		

1 Line-up

Heat Pump - Standard type (Compact)

System Model			Outdoor Unit Selection									
Capacity	System Model Code	Number of Modules	8HP	10HP	12HP	14HP	16HP	18HP	20HP	22HP	24HP	26HP
			AM080JXVAGH2EU	AM100JXVAGH2EU	AM120JXVAGH2EU	AM140JXVAGH2EU	AM160JXVAGH2EU	AM180JXVAGH2EU	AM200JXVAGH2EU	AM220JXVAGH2EU	AM240HXVAGH2EU	AM260HXVAGH2EU
36HP	AM360JXVAGH2EU	2			1						1	
38HP	AM380JXVAGH2EU	2			1							1
46HP	AM460JXVAGH2EU	2							1			1
48HP	AM480JXVAGH2EU	2								1		1
50HP	AM500JXVAGH2EU	2									1	1
52HP	AM520JXVAGH2EU	2										2
58HP	AM580JXVAGH2EU	3			1				1			1
60HP	AM600JXVAGH2EU	3			1					1		1
62HP	AM620JXVAGH2EU	3			1						1	1
64HP	AM640JXVAGH2EU	3			1							2
68HP	AM680JXVAGH2EU	3								2	1	
70HP	AM700JXVAGH2EU	3								2		1
72HP	AM720JXVAGH2EU	3								1	1	1
74HP	AM740JXVAGH2EU	3								1		2
76HP	AM760JXVAGH2EU	3									1	2
78HP	AM780JXVAGH2EU	3										3

1 Line-up

Heat Recovery - High EER type

System Model			Outdoor Unit Selection							
Capacity	System Model Code	Number of Modules	8HP	10HP	12HP	14HP	16HP	18HP	20HP	22HP
			AM080JXVH GR/EU	AM100JXVH GR/EU	AM120JXVH GR/EU	AM140JXVH GR/EU	AM160JXVH GR/EU	AM180JXVH GR/EU	AM200JXVH GR/EU	AM220JXVH GR/EU
8HP	-	1	1							
10HP	-	1		1						
12HP	-	1			1					
14HP	-	1				1				
16HP	-	1					1			
18HP	-	1						1		
20HP	-	1							1	
22HP	-	1								1
24HP	AM240JXVHGR1EU	2			2					
26HP	AM260JXVHGR1EU	2			1	1				
28HP	AM280JXVHGR1EU	2			1		1			
30HP	AM300JXVHGR1EU	2			1			1		
32HP	AM320JXVHGR1EU	2			1				1	
34HP	AM340JXVHGR1EU	2			1					1
36HP	AM360JXVHGR1EU	2				1				1
38HP	AM380JXVHGR1EU	2					1			1
40HP	AM400JXVHGR1EU	2							2	
42HP	AM420JXVHGR1EU	2							1	1
44HP	AM440JXVHGR1EU	2								2
46HP	AM460JXVHGR1EU	3			2					1
48HP	AM480JXVHGR1EU	3			1	1				1
50HP	AM500JXVHGR1EU	3			1		1			1
52HP	AM520JXVHGR1EU	3			1			1		1
54HP	AM540JXVHGR1EU	3			1				1	1
56HP	AM560JXVHGR1EU	3			1					2
58HP	AM580JXVHGR1EU	3				1				2
60HP	AM600JXVHGR1EU	3					1			2
62HP	AM620JXVHGR1EU	3							2	1
64HP	AM640JXVHGR1EU	3							1	2
66HP	AM660JXVHGR1EU	3								3
68HP	AM680JXVHGR1EU	4			2					2
70HP	AM700JXVHGR1EU	4			1	1				2
72HP	AM720JXVHGR1EU	4			1		1			2
74HP	AM740JXVHGR1EU	4			1			1		2
76HP	AM760JXVHGR1EU	4			1				1	2
78HP	AM780JXVHGR1EU	4			1					3
80HP	AM800JXVHGR1EU	4				1				3

2 Specifications : H/P - High EER type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)
Model Name			AM080JXVHGH/EU	AM100JXVHGH/EU	AM120JXVHGH/EU	AM140JXVHGH/EU
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50
Mode			-	HP	HP	HP
Performance	HP		HP	8.00	10.00	12.00
		Capacity (Nominal)	Cooling	kW	22.40	28.00
	Btu/h			76,400	95,500	114,600
			Heating	kW	25.20	31.50
Btu/h				86,000	107,500	129,000
Power	Power Input (Nominal)	Cooling 1)	kW	4.59	6.22	7.57
		Heating 2)	kW	4.59	5.89	7.56
	Current Input (Nominal)	Cooling 1)	A	7.40	10.00	12.10
		Heating 2)	A	7.40	9.40	12.10
	MCA	A	22.50	29.90	31.30	
MFA	A	30.00	40.00	40.00		
COP	EER (Nominal Cooling)		-	4.88	4.50	4.44
	COP (Nominal Heating)		-	5.49	5.35	5.00
	Energy Grade		-	ESEER 8.00	ESEER 7.43	ESEER 7.23
Compressor	Type		-	SSC Scroll x 1	SSC Scroll x 1	SSC Scroll x 1
	Output		kW x n	(5.18)	(6.39)	(6.39)
	Model Name		-	DS-GB052FAVBSGx1	DS-GB066FAVBSGx1	DS-GB066FAVBSGx1
	Oil	Type	-	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller
	Output x n		W	830.0	830.0	830.0
	Air Flow Rate		CMM	170	170	220
			l/s	2,833.33	2,833.33	3,666.67
	External Static	Max.	mmAQ	8.00	8.00	8.00
Pa			78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	9.52	9.52	12.70
			Ø, inch	3/8"	3/8"	1/2"
	Gas Pipe		Ø, mm	19.05	22.22	28.58
			Ø, inch	3/4"	7/8"	1 1/8"
	Discharge Gas Pipe		Ø, mm	-	-	-
			Ø, inch	-	-	-
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)
Max. Height		m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A
	Factory Charging		kg	6.50	6.50	7.70
Sound	Pressure		dBA	57.00	58.00	62.00
	Power			77.00	79.00	81.00
External Dimension	Net Weight		kg	201.0	201.0	235.0
	Shipping Weight		kg	217.0	217.0	254.0
	Net Dimensions (WxHxD)		mm	880x1,695x765	880x1,695x765	880x1,695x765
	Shipping Dimensions (WxHxD)		mm	948x1,887x832	948x1,887x832	1,363x1,887x832
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - High EER type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)
Model Name			AM160JXVHGH/EU	AM180JXVHGH/EU	AM200JXVHGH/EU	AM220JXVHGH/EU
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50
Mode			-	HP	HP	HP
Performance	HP		HP	16.00	18.00	20.00
			kW	45.00	50.40	56.00
	Capacity (Nominal)	Cooling	Btu/h	153,500	172,000	191,100
		Heating	kW	50.40	56.70	63.00
		Btu/h	172,000	193,500	215,000	
Power	Power Input (Nominal)	Cooling 1)	kW	10.92	11.51	13.05
		Heating 2)	kW	10.75	11.62	13.10
	Current Input (Nominal)	Cooling 1)	A	17.50	18.50	20.90
		Heating 2)	A	17.20	18.60	21.00
	MCA	A	40.00	48.90	52.50	
MFA	A	40.00	50.00	75.00		
COP	EER (Nominal Cooling)		-	4.12	4.38	4.29
	COP (Nominal Heating)		-	4.69	4.88	4.81
	Energy Grade		-	ESEER 6.82	ESEER 6.71	ESEER 6.66
Compressor	Type		-	SSC Scroll x 2	SSC Scroll x 2	SSC Scroll x 2
	Output		kW x n	(4.39 x 2)	(6.39 x 2)	(6.39 x 2)
	Model Name		-	DS-GA046FAVASGx2	DS-GB066FAVBSGx2	DS-GB066FAVBSGx2
	Oil	Type	-	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller
	Output x n		W	620.0x2	620.0x2	620.0x2
	Air Flow Rate		CMM	255	290	290
			l/s	4,250.00	4,833.33	4,833.33
	External Static	Max.	mmAQ	8.00	8.00	8.00
Pa			78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	12.70	15.88	15.88
			Ø, inch	1/2"	5/8"	5/8"
	Gas Pipe		Ø, mm	28.58	28.58	28.58
			Ø, inch	1 1/8"	1 1/8"	1 1/8"
	Discharge Gas Pipe		Ø, mm	-	-	-
			Ø, inch	-	-	-
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)
Max. Height		m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A
	Factory Charging		kg	7.70	8.40	8.40
Sound	Pressure		dBA	62.00	63.00	64.00
	Power			82.00	85.00	86.00
External Dimension	Net Weight		kg	266.0	300.0	300.0
	Shipping Weight		kg	285.0	319.0	319.0
	Net Dimensions (WxHxD)		mm	1,295x1,695x765	1,295x1,695x765	1,295x1,695x765
	Shipping Dimensions (WxHxD)		mm	1,363x1,887x832	1,363x1,887x832	1,363x1,887x832
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - High EER type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	
Model Name			AM240HXVAGH/EU	AM240JXVHGH1EU*	AM260HXVAGH/EU	AM260JXVHGH1EU*	
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50	
Mode			-	HP	HP	HP	
Performance	HP		HP	24.00	24.00	26.00	
			kW	67.20	67.20	72.80	
	Capacity (Nominal)	Cooling		Btu/h	229,300	229,300	248,400
				kW	75.60	75.60	81.90
		Heating		Btu/h	258,000	258,000	279,500
			kW	75.60	75.60	82.80	
Power	Power Input (Nominal)	Cooling 1)	kW	17.10	15.14	19.30	
		Heating 2)	kW	19.80	15.12	21.80	
	Current Input (Nominal)	Cooling 1)	A	26.83	24.20	30.28	
		Heating 2)	A	31.06	24.20	34.20	
	MCA	A	60.50	55.00	63.80		
	MFA	A	75.00	75.00	75.00		
COP	EER (Nominal Cooling)		-	3.93	4.44	3.77	
	COP (Nominal Heating)		-	3.82	5.00	3.76	
	Energy Grade		-	ESEER 6.48	ESEER 7.23	ESEER 6.26	
			-	-	-	-	
Compressor	Type		-	SSC Scroll x 2	SSC Scroll x 2	SSC Scroll x 2	
	Output		kW x n	(6.39 x 2)	(6.39)x2	(6.76 x 2)	
	Model Name		-	DS-GB066FAVBSGx2	DS-GB066FAVBSGx2	DS-GB070FAVASGx2	
	Oil	Type	-	PVE	PVE	PVE	
	Type		-	Propeller	Propeller	Propeller	
Fan	Type		-	Propeller	Propeller	Propeller	
	Output x n		W	620.0x2	(830.0)x2	620.0x2	
	Air Flow Rate		CMM	310	220.0x2	310	
			l/s	5,166.67	3,666.7x2	5,166.67	
	External Static	Max.	mmAQ	8.00	8.00	8.00	
Pa			78.40	78.40	78.40		
Piping Connections	Liquid Pipe		Ø, mm	15.88	15.88	19.05	
			Ø, inch	5/8"	5/8"	3/4"	
	Gas Pipe		Ø, mm	34.92	34.92	34.92	
			Ø, inch	1 3/8"	1 3/8"	1 3/8"	
	Discharge Gas Pipe		Ø, mm	-	-	-	
			Ø, inch	-	-	-	
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)	
		Max. Height	m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-	
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50	
Refrigerant	Type		-	R410A	R410A	R410A	
	Factory Charging		kg	14.30	13.00	14.30	
Sound	Pressure		dBA	67.00	65.00	67.00	
	Power			91.00	84.00	91.00	
External Dimension	Net Weight		kg	360.0	201.0x2	360.0	
	Shipping Weight		kg	375.0	217.0x2	375.0	
	Net Dimensions (WxHxD)		mm	1,295x1,695x765	(880x1,695x765)x2	1,295x1,695x765	
	Shipping Dimensions (WxHxD)		mm	1,363x1,887x832	(948x1,887x832)x2	1,363x1,887x832	
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0	
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0	

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

6) AM~JXVHGH1EU* : Outdoor Unit combination has been added.

2 Specifications : H/P - High EER type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)
Model Name			AM280JXVHGH1EU	AM300JXVHGH1EU	AM320JXVHGH1EU	AM340JXVHGH1EU
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50
Mode			-	HP	HP	HP
Performance	HP		HP	28.00	30.00	32.00
			kW	78.60	84.00	89.60
	Capacity (Nominal)	Cooling	Btu/h	268,200	286,600	305,700
		Heating	kW	88.20	94.50	100.80
		Btu/h	301,000	322,400	343,900	
Power	Power Input (Nominal)	Cooling 1)	kW	18.49	19.08	20.62
		Heating 2)	kW	18.31	19.18	20.66
	Current Input (Nominal)	Cooling 1)	A	29.60	30.60	33.00
		Heating 2)	A	29.30	30.70	33.10
	MCA	A	71.30	80.20	83.80	
MFA	A	75.00	90.00	90.00		
COP	EER (Nominal Cooling)		-	4.25	4.40	4.35
	COP (Nominal Heating)		-	4.82	4.93	4.88
	Energy Grade		-	ESEER 7.00	ESEER 6.92	ESEER 6.87
Compressor	Type		-	SSC Scroll x 3	SSC Scroll x 3	SSC Scroll x 3
	Output		kW x n	(6.39) + (4.39x2)	(6.39) + (6.39x2)	(6.39) + (6.39x2)
	Model Name		-	DS-GB066FAVBSGx1 + DS-GA046FAVASGx2	DS-GB066FAVBSGx3	DS-GB066FAVBSGx3
	Oil	Type	-	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller
	Output x n		W	830.0 + 620.0x2	830.0 + 620.0x2	830.0 + 620.0x2
	Air Flow Rate		CMM	220.0 + 255.0	220.0 + 290.0	220.0 + 290.0
			l/s	3,666.7 + 4,250.0	3,666.7 + 4,833.3	3,666.7 + 4,833.3
	External Static	Max.	mmAQ	8.00	8.00	8.00
Pa			78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	19.05	19.05	19.05
			Ø, inch	3/4"	3/4"	3/4"
	Gas Pipe		Ø, mm	34.92	34.92	34.92
			Ø, inch	1 3/8"	1 3/8"	1 3/8"
	Discharge Gas Pipe		Ø, mm	-	-	-
			Ø, inch	-	-	-
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)
Max. Height		m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A
	Factory Charging		kg	14.20	14.90	14.90
Sound	Pressure		dBA	65.00	66.00	67.00
	Power			85.00	86.00	87.00
External Dimension	Net Weight		kg	201.0 + 266.0	201.0 + 300.0	201.0 + 300.0
	Shipping Weight		kg	217.0 + 285.0	217.0 + 319.0	217.0 + 319.0
	Net Dimensions (WxHxD)		mm	880x1,695x765 + 1,295x1,695x765	880x1,695x765 + 1,295x1,695x765	880x1,695x765 + 1,295x1,695x765
	Shipping Dimensions (WxHxD)		mm	948x1,887x832 + 1,363x1,887x832	948x1,887x832 + 1,363x1,887x832	948x1,887x832 + 1,363x1,887x832
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - High EER type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)
Model Name			AM360JXVHGH1EU	AM380JXVHGH1EU	AM400JXVHGH1EU	AM400JXVHGH1EU*
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50
Mode			-	HP	HP	HP
Performance	HP		HP	36.00	38.00	40.00
		Capacity (Nominal)	Cooling	kW	101.60	106.60
	Btu/h			346,700	363,700	384,900
	Heating		kW	114.30	119.70	126.90
			Btu/h	390,000	408,400	433,000
Power	Power Input (Nominal)	Cooling 1)	kW	26.30	26.67	29.85
		Heating 2)	kW	25.58	26.61	31.52
	Current Input (Nominal)	Cooling 1)	A	42.20	42.80	47.18
		Heating 2)	A	41.00	42.60	49.80
	MCA	A	86.90	95.60	95.10	
MFA	A	90.00	100.00	100.00		
COP	EER (Nominal Cooling)		-	3.86	4.00	3.78
	COP (Nominal Heating)		-	4.47	4.50	4.03
	Energy Grade		-	ESEER 6.63	ESEER 6.53	ESEER 6.56
Compressor	Type		-	SSC Scroll x 3	SSC Scroll x 4	SSC Scroll x 3
	Output		kW x n	(6.39) + (6.39x2)	(4.39x2) + (6.39x2)	(6.39) + (6.76x2)
	Model Name		-	DS-GB066FAVBSGx3	DS-GA046FAVBSGx2 + DS-GB066FAVBSGx2	DS-GB066FAVBSGx1 + DS-GB070FAVBSGx2
	Oil	Type	-	PVE	PVE	PVE
	Type		-	Propeller	Propeller	Propeller
Fan	Output x n		W	(620.0x2)x2	(620.0x2)x2	(620.0x2)x2
	Air Flow Rate		CMM	255.0 + 290.0	255.0 + 290.0	255.0 + 310.0
			l/s	4,250.0 + 4,833.3	4,250.0 + 4,833.3	4,250.0 + 5,166.7
	External Static	Max.	mmAQ	8.00	8.00	8.00
			Pa	78.40	78.40	78.40
Piping Connections	Liquid Pipe		Ø, mm	19.05	19.05	19.05
			Ø, inch	3/4"	3/4"	3/4"
	Gas Pipe		Ø, mm	41.28	41.28	41.28
			Ø, inch	1 5/8"	1 5/8"	1 5/8"
	Discharge Gas Pipe		Ø, mm	-	-	-
			Ø, inch	-	-	-
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)
Max. Height		m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A
	Factory Charging		kg	16.10	16.10	22.00
Sound	Pressure		dBA	66.00	67.00	68.00
	Power			89.00	89.00	91.00
External Dimension	Net Weight		kg	235.0 + 300.0	266.0 + 300.0	235.0 + 360.0
	Shipping Weight		kg	254.0 + 319.0	285.0 + 319.0	254.0 + 375.0
	Net Dimensions (WxHxD)		mm	(1,295x1,695x765)x2	(1,295x1,695x765)x2	(1,295x1,695x765)x2
	Shipping Dimensions (WxHxD)		mm	(1,363x1,887x832)x2	(1,363x1,887x832)x2	(1,363x1,887x832)x2
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

6) AM~JXVHGH1EU* : Outdoor Unit combination has been added.

2 Specifications : H/P - High EER type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	
Model Name			AM420JXVHGH1EU	AM440JXVHGH1EU	AM460JXVHGH1EU	AM480JXVHGH1EU	
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50	
Mode			-	HP	HP	HP	
Performance	HP	Capacity (Nominal)	HP	42.00	44.00	46.00	
			Cooling	kW	117.60	123.20	128.80
				Btu/h	401,300	420,400	439,500
			Heating	kW	132.30	138.60	144.90
Btu/h	451,400	472,900		494,400			
Power	Power Input (Nominal)	Cooling 1)	kW	28.80	31.50	30.89	
		Heating 2)	kW	28.96	31.72	30.98	
	Current Input (Nominal)	Cooling 1)	A	46.20	50.60	49.50	
		Heating 2)	A	46.40	50.80	49.60	
MCA	A	108.10	111.20	118.20	118.20		
MFA	A	125.00	125.00	125.00	125.00		
COP	EER (Nominal Cooling)		-	4.08	3.91	4.17	
	COP (Nominal Heating)		-	4.57	4.37	4.68	
	Energy Grade		-	ESEER 6.48	ESEER 6.32	ESEER 6.79	
Compressor	Type		-	SSC Scroll x 4	SSC Scroll x 4	SSC Scroll x 4	
	Output		kW x n	(6.39x2) + (6.39x2)	(6.39x2)x2	(6.39)x2 + (6.39x2)	
	Model Name		-	DS-GB066FAVBSGx4	DS-GB066FAVBSGx4	DS-GB066FAVBSGx4	
	Oil	Type	-	PVE	PVE	PVE	
Fan	Type		-	Propeller	Propeller	Propeller	
	Output x n		W	(620.0x2)x2	(620.0x2)x2	(830.0)x2 + 620.0x2	
	Air Flow Rate		CMM	290.0x2	290.0x2	220.0x2 + 290.0	
			l/s	4,833.3x2	4,833.3x2	3,666.7x2 + 4,833.3	
External Static	Max.	mmAQ	8.00	8.00	8.00		
		Pa	78.40	78.40	78.40		
Piping Connections	Liquid Pipe		Ø, mm	19.05	19.05	19.05	
			Ø, inch	3/4"	3/4"	3/4"	
	Gas Pipe		Ø, mm	41.28	41.28	41.28	
			Ø, inch	1 5/8"	1 5/8"	1 5/8"	
	Discharge Gas Pipe		Ø, mm	-	-	-	
			Ø, inch	-	-	-	
Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)		
	Max. Height	m	110 (40)	110 (40)	110 (40)		
Field Wiring	Power Source Wire		mm ²	-	-	-	
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50	
Refrigerant	Type		-	R410A	R410A	R410A	
	Factory Charging		kg	16.80	16.80	21.40	
Sound	Pressure		dBA	68.00	68.00	68.00	
	Power			90.00	91.00	89.00	
External Dimension	Net Weight		kg	300.0x2	300.0x2	201.0x2 + 300.0	
	Shipping Weight		kg	319.0x2	319.0x2	217.0x2 + 319.0	
	Net Dimensions (WxHxD)		mm	(1,295x1,695x765)x2	(1,295x1,695x765)x2	(880x1,695x765)x2 + 1,295x1,695x765	
	Shipping Dimensions (WxHxD)		mm	(1,363x1,887x832)x2	(1,363x1,887x832)x2	(948x1,887x832)x2 + 1,363x1,887x832	
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0	
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0	

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - High EER type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	
Model Name			AM500JXVHGH1EU	AM520JXVHGH1EU	AM540JXVHGH1EU	AM560JXVHGH1EU	
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50	
Mode			-	HP	HP	HP	
Performance	Capacity (Nominal)	Cooling	HP	50.00	52.00	54.00	56.00
			kW	140.20	145.60	151.20	156.80
		Heating	Btu/h	478,400	496,800	515,900	535,000
			kW	157.50	163.80	170.10	176.40
			Btu/h	537,400	558,900	580,400	601,900
Power	Power Input (Nominal)	Cooling 1)	kW	34.24	34.83	36.37	39.07
		Heating 2)	kW	34.17	35.04	36.52	39.28
	Current Input (Nominal)	Cooling 1)	A	54.90	55.90	58.30	62.70
		Heating 2)	A	54.70	56.10	58.50	62.90
	MCA	A	126.90	135.80	139.40	142.50	
MFA	A	150.00	150.00	150.00	150.00		
COP	EER (Nominal Cooling)		-	4.09	4.18	4.16	4.01
	COP (Nominal Heating)		-	4.61	4.67	4.66	4.49
	Energy Grade		-	ESEER 6.70	ESEER 6.66	ESEER 6.65	ESEER 6.52
Compressor	Type		-	SSC Scroll x 5	SSC Scroll x 5	SSC Scroll x 5	SSC Scroll x 5
	Output		kW x n	(6.39) + (4.39x2) + (6.39x2)	(6.39) + (6.39x2) + (6.39x2)	(6.39) + (6.39x2) + (6.39x2)	(6.39) + (6.39x2)x2
	Model Name		-	DS-GB066FAVBSGx3 + DS-GA046FAVASGx2	DS-GB066FAVBSGx5	DS-GB066FAVBSGx5	DS-GB066FAVBSGx5
	Oil	Type	-	PVE	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller	Propeller
	Output x n		W	830.0 + (620.0x2)x2	830.0 + (620.0x2)x2	830.0 + (620.0x2)x2	830.0 + (620.0x2)x2
	Air Flow Rate		CMM	220.0 + 255.0 + 290.0	220.0 + 290.0x2	220.0 + 290.0x2	220.0 + 290.0x2
			l/s	3,666.7 + 4,250.0 + 4,833.3	3,666.7 + 4,833.3x2	3,666.7 + 4,833.3x2	3,666.7 + 4,833.3x2
	External Static	Max.	mmAQ	8.00	8.00	8.00	8.00
Pa			78.40	78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	19.05	19.05	19.05	19.05
			Ø, inch	3/4"	3/4"	3/4"	3/4"
	Gas Pipe		Ø, mm	41.28	41.28	41.28	41.28
			Ø, inch	1 5/8"	1 5/8"	1 5/8"	1 5/8"
	Discharge Gas Pipe		Ø, mm	-	-	-	-
			Ø, inch	-	-	-	-
Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)	200 (220)	
	Max. Height	m	110 (40)	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A	R410A
	Factory Charging		kg	22.60	23.30	23.30	23.30
Sound	Pressure		dBA	68.00	68.00	69.00	69.00
	Power			90.00	90.00	91.00	91.00
External Dimension	Net Weight		kg	201.0 + 266.0 + 300.0	201.0 + 300.0x2	201.0 + 300.0x2	201.0 + 300.0x2
	Shipping Weight		kg	217.0 + 285.0 + 319.0	217.0 + 319.0x2	217.0 + 319.0x2	217.0 + 319.0x2
	Net Dimensions (WxHxD)		mm	880x1,695x765 + (1,295x1,695x765)x2	880x1,695x765 + (1,295x1,695x765)x2	880x1,695x765 + (1,295x1,695x765)x2	880x1,695x765 + (1,295x1,695x765)x2
	Shipping Dimensions (WxHxD)		mm	948x1,887x832 + (1,363x1,887x832)x2	948x1,887x832 + (1,363x1,887x832)x2	948x1,887x832 + (1,363x1,887x832)x2	948x1,887x832 + (1,363x1,887x832)x2
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - High EER type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)
Model Name			AM580JXVHGH1EU	AM600JXVHGH1EU	AM620JXVHGH1EU	AM640JXVHGH1EU
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50
Mode			-	HP	HP	HP
Performance	HP		HP	58.00	60.00	62.00
		Capacity (Nominal)	Cooling	kW	163.20	168.20
	Btu/h			556,900	573,900	592,300
		Heating	kW	183.60	189.00	195.30
Btu/h			626,500	644,900	666,400	
Power	Power Input (Nominal)	Cooling 1)	kW	42.05	42.42	41.85
		Heating 2)	kW	41.44	42.47	42.06
	Current Input (Nominal)	Cooling 1)	A	67.50	68.10	67.10
		Heating 2)	A	66.40	68.00	67.40
	MCA	A	142.50	151.20	161.90	
MFA	A	150.00	200.00	200.00		
COP	EER (Nominal Cooling)		-	3.88	3.97	4.15
	COP (Nominal Heating)		-	4.43	4.45	4.64
	Energy Grade		-	ESEER 6.52	ESEER 6.45	ESEER 6.54
Compressor	Type		-	SSC Scroll x 5	SSC Scroll x 6	SSC Scroll x 6
	Output		kW x n	(6.39) + (6.39x2)x2	(4.39x2) + (6.39x2)x2	(6.39x2) + (6.39x2)x2
	Model Name		-	DS-GB066FAVBSGx5	DS-GA046FAVASGx2 + DS-GB066FAVBSGx4	DS-GB066FAVBSGx6
	Oil	Type	-	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller
	Output x n		W	(620.0x2)x3	(620.0x2)x3	(620.0x2)x3
	Air Flow Rate		CMM	255.0 + 290.0x2	255.0 + 290.0x2	290.0x3
			l/s	4,250.0 + 4,833.3x2	4,250.0 + 4,833.3x2	4,833.3x3
	External Static	Max.	mmAQ	8.00	8.00	8.00
Pa			78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	19.05	19.05	22.22
			Ø, inch	3/4"	3/4"	7/8"
	Gas Pipe		Ø, mm	41.28	41.28	53.98
			Ø, inch	1 5/8"	1 5/8"	2 1/8"
	Discharge Gas Pipe		Ø, mm	-	-	-
			Ø, inch	-	-	-
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)
Max. Height		m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A
	Factory Charging		kg	24.50	24.50	25.20
Sound	Pressure		dBA	69.00	69.00	69.00
	Power			91.00	92.00	92.00
External Dimension	Net Weight		kg	235.0 + 300.0x2	266.0 + 300.0x2	300.0x3
	Shipping Weight		kg	254.0 + 319.0x2	285.0 + 319.0x2	319.0x3
	Net Dimensions (WxHxD)		mm	(1,295x1,695x765)x3	(1,295x1,695x765)x3	(1,295x1,695x765)x3
	Shipping Dimensions (WxHxD)		mm	(1,363x1,887x832)x3	(1,363x1,887x832)x3	(1,363x1,887x832)x3
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - High EER type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)
Model Name			AM660JXVHGH1EU	AM680JXVHGH1EU	AM700JXVHGH1EU	AM720JXVHGH1EU
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50
Mode			-	HP	HP	HP
Performance	HP		HP	66.00	68.00	70.00
			kW	184.80	190.40	196.80
	Capacity (Nominal)	Cooling	Btu/h	630,600	649,700	671,500
		Heating	kW	207.90	214.20	221.40
		Btu/h	709,400	730,900	755,400	
Power	Power Input (Nominal)	Cooling 1)	kW	47.25	46.64	49.62
		Heating 2)	kW	47.58	46.84	49.00
	Current Input (Nominal)	Cooling 1)	A	75.90	74.80	79.60
		Heating 2)	A	76.20	75.00	78.50
	MCA	A	166.80	173.80	173.80	
MFA	A	200.00	200.00	200.00		
COP	EER (Nominal Cooling)		-	3.91	4.08	3.97
	COP (Nominal Heating)		-	4.37	4.57	4.52
	Energy Grade		-	ESEER 6.32	ESEER 6.64	ESEER 6.64
Compressor	Type		-	SSC Scroll x 6	SSC Scroll x 6	SSC Scroll x 6
	Output		kW x n	(6.39x2)x3	(6.39)x2 + (6.39x2)x2	(6.39) + (6.39) + (6.39x2)x2
	Model Name		-	DS-GB066FAVBSGx6	DS-GB066FAVBSGx6	DS-GB066FAVBSGx6
	Oil	Type	-	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller
	Output x n		W	(620.0x2)x3	(830.0)x2 + (620.0x2)x2	830.0 + (620.0x2)x3
	Air Flow Rate		CMM	290.0x3	220.0x2 + 290.0x2	220.0 + 255.0 + 290.0x2
			l/s	4,833.3x3	3,666.7x2 + 4,833.3x2	3,666.7 + 4,250.0 + 4,833.3x2
	External Static	Max.	mmAQ	8.00	8.00	8.00
Pa			78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	22.22	22.22	22.22
			Ø, inch	7/8"	7/8"	7/8"
	Gas Pipe		Ø, mm	53.98	53.98	53.98
			Ø, inch	2 1/8"	2 1/8"	2 1/8"
	Discharge Gas Pipe		Ø, mm	-	-	-
			Ø, inch	-	-	-
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)
Max. Height		m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A
	Factory Charging		kg	25.20	29.80	31.00
Sound	Pressure		dBA	70.00	70.00	70.00
	Power			93.00	92.00	92.00
External Dimension	Net Weight		kg	300.0x3	201.0x2 + 300.0x2	201.0 + 235.0 + 300.0x2
	Shipping Weight		kg	319.0x3	217.0x2 + 319.0x2	217.0 + 254.0 + 319.0x2
	Net Dimensions (WxHxD)		mm	(1,295x1,695x765)x3	(880x1,695x765)x2 + (1,295x1,695x765)x2	880x1,695x765 + (1,295x1,695x765)x3
	Shipping Dimensions (WxHxD)		mm	(1,363x1,887x832)x3	(948x1,887x832)x2 + (1,363x1,887x832)x2	948x1,887x832 + (1,363x1,887x832)x3
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - High EER type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)
Model Name			AM740JXVHGH1EU	AM760JXVHGH1EU	AM780JXVHGH1EU	AM800JXVHGH1EU
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50
Mode			-	HP	HP	HP
Performance	HP		HP	74.00	76.00	78.00
			kW	207.20	212.80	218.40
	Capacity (Nominal)	Cooling	Btu/h	707,000	726,100	745,200
		Heating	kW	233.10	239.40	245.70
		Btu/h	795,400	816,900	838,400	
Power	Power Input (Nominal)	Cooling 1)	kW	50.58	52.12	54.82
		Heating 2)	kW	50.90	52.38	55.14
	Current Input (Nominal)	Cooling 1)	A	81.20	83.60	88.00
		Heating 2)	A	81.50	83.90	88.30
	MCA	A	191.40	195.00	198.10	
MFA	A	200.00	200.00	200.00		
COP	EER (Nominal Cooling)		-	4.10	4.08	3.98
	COP (Nominal Heating)		-	4.58	4.57	4.46
	Energy Grade		-	ESEER 6.56	ESEER 6.55	ESEER 6.46
Compressor	Type		-	SSC Scroll x 7	SSC Scroll x 7	SSC Scroll x 7
	Output		kW x n	(6.39) + (6.39x2) + (6.39x2)x2	(6.39) + (6.39x2)x2 + (6.39x2)	(6.39) + (6.39x2)x3
	Model Name		-	DS-GB066FAVBSGx7	DS-GB066FAVBSGx7	DS-GB066FAVBSGx7
	Oil	Type	-	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller
	Output x n		W	830.0 + (620.0x2)x3	830.0 + (620.0x2)x3	830.0 + (620.0x2)x3
	Air Flow Rate		CMM	220.0 + 290.0x3	220.0 + 290.0x3	220.0 + 290.0x3
			l/s	3,666.7 + 4,833.3x3	3,666.7 + 4,833.3x3	3,666.7 + 4,833.3x3
	External Static	Max.	mmAQ	8.00	8.00	8.00
Pa			78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	22.22	22.22	22.22
			Ø, inch	7/8"	7/8"	7/8"
	Gas Pipe		Ø, mm	53.98	53.98	53.98
			Ø, inch	2 1/8"	2 1/8"	2 1/8"
	Discharge Gas Pipe		Ø, mm	-	-	-
			Ø, inch	-	-	-
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)
Max. Height		m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A
	Factory Charging		kg	31.70	31.70	32.90
Sound	Pressure		dBA	70.00	70.00	70.00
	Power			92.00	93.00	93.00
External Dimension	Net Weight		kg	201.0 + 300.0x3	201.0 + 300.0x3	201.0 + 300.0x3
	Shipping Weight		kg	217.0 + 319.0x3	217.0 + 319.0x3	217.0 + 319.0x3
	Net Dimensions (WxHxD)		mm	880x1,695x765 + (1,295x1,695x765)x3	880x1,695x765 + (1,295x1,695x765)x3	880x1,695x765 + (1,295x1,695x765)x3
	Shipping Dimensions (WxHxD)		mm	948x1,887x832 + (1,363x1,887x832)x3	948x1,887x832 + (1,363x1,887x832)x3	948x1,887x832 + (1,363x1,887x832)x3
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - High EER type (Compact)

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	
Model Name			AM360JXVHGH2EU	AM380JXVHGH2EU	AM460JXVHGH2EU	AM480JXVHGH2EU	
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50	
Mode			-	HP	HP	HP	
Performance	HP		HP	36.00	38.00	46.00	
			kW	100.80	106.40	128.80	
	Capacity (Nominal)	Cooling		Btu/h	343,900	363,100	439,500
				kW	113.40	119.70	144.90
		Heating		Btu/h	386,900	408,400	494,400
Power	Power Input (Nominal)	Cooling 1)	kW	24.67	26.87	32.35	
		Heating 2)	kW	27.36	29.36	34.90	
	Current Input (Nominal)	Cooling 1)	A	38.93	42.38	51.18	
		Heating 2)	A	43.16	46.30	55.20	
	MCA	A	91.80	95.10	116.30		
MFA	A	100.00	100.00	125.00			
COP	EER (Nominal Cooling)		-	4.09	3.96	3.98	
	COP (Nominal Heating)		-	4.14	4.08	4.15	
	Energy Grade		-	ESEER 6.73	ESEER 6.57	ESEER 6.43	
Compressor	Type		-	SSC Scroll x 3	SSC Scroll x 3	SSC Scroll x 4	
	Output		kW x n	(6.39) + (6.39x2)	(6.39) + (6.76x2)	(6.39x2) + (6.76x2)	
	Model Name		-	DS-GB066FAVBSGx3	DS-GB066FAVBSGx1 + DS-GB070FAVASGx2	DS-GB066FAVBSGx2 + DS-GB070FAVASGx2	
	Oil	Type	-	PVE	PVE	PVE	
	Type		-	Propeller	Propeller	Propeller	
Fan	Output x n		W	830.0 + 620.0x2	830.0 + 620.0x2	(620.0x2)x2	
	Air Flow Rate		CMM	220.0 + 310.0	220.0 + 310.0	290.0 + 310.0	
			l/s	3,666.7 + 5,166.7	3,666.7 + 5,166.7	4,833.3 + 5,166.7	
	External Static	Max.	mmAQ	8.00	8.00	8.00	
			Pa	78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	19.05	19.05	19.05	
			Ø, inch	3/4"	3/4"	3/4"	
	Gas Pipe		Ø, mm	41.28	41.28	41.28	
			Ø, inch	1 5/8"	1 5/8"	1 5/8"	
	Discharge Gas Pipe		Ø, mm	-	-	-	
			Ø, inch	-	-	-	
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)	
Max. Height		m	110 (40)	110 (40)	110 (40)		
Field Wiring	Power Source Wire		mm ²	-	-	-	
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50	
Refrigerant	Type		-	R410A	R410A	R410A	
	Factory Charging		kg	20.80	20.80	22.70	
Sound	Pressure		dBA	68.00	68.00	69.00	
	Power			91.00	91.00	92.00	
External Dimension	Net Weight		kg	201.0 + 360.0	201.0 + 360.0	300.0 + 360.0	
	Shipping Weight		kg	217.0 + 375.0	217.0 + 375.0	319.0 + 375.0	
	Net Dimensions (WxHxD)		mm	880x1,695x765 + 1,295x1,695x765	880x1,695x765 + 1,295x1,695x765	(1,295x1,695x765)x2	
	Shipping Dimensions (WxHxD)		mm	948x1,887x832 + 1,363x1,887x832	948x1,887x832 + 1,363x1,887x832	(1,363x1,887x832)x2	
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0	
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0	

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - High EER type (Compact)

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)
Model Name			AM500JXVHGH2EU	AM520JXVHGH2EU	AM580JXVHGH2EU	AM600JXVHGH2EU
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50
Mode			-	HP	HP	HP
Performance	HP		HP	50.00	52.00	58.00
		Capacity (Nominal)	Cooling	kW	140.00	145.60
	Btu/h			477,700	496,800	554,100
		Heating	kW	157.50	163.80	182.70
Btu/h			537,400	558,900	623,400	
Power	Power Input (Nominal)	Cooling 1)	kW	36.40	38.60	39.92
		Heating 2)	kW	41.60	43.60	42.46
	Current Input (Nominal)	Cooling 1)	A	57.11	60.56	63.28
		Heating 2)	A	65.26	68.40	67.30
	MCA	A	124.30	127.60	147.60	
MFA	A	150.00	150.00	150.00		
COP	EER (Nominal Cooling)		-	3.85	3.77	4.07
	COP (Nominal Heating)		-	3.79	3.76	4.30
	Energy Grade		-	ESEER 6.37	ESEER 6.26	ESEER 6.60
Compressor	Type		-	SSC Scroll x 4	SSC Scroll x 4	SSC Scroll x 5
	Output		kW x n	(6.39x2) + (6.76x2)	(6.76x2)x2	(6.39) + (6.39x2) + (6.76x2)
	Model Name		-	DS-GB066FAVBSGx2 + DS-GB070FAVASGx2	DS-GB070FAVASGx4	DS-GB066FAVBSGx3 + DS-GB070FAVASGx2
	Oil	Type	-	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller
	Output x n		W	(620.0x2)x2	(620.0x2)x2	830.0 + (620.0x2)x2
	Air Flow Rate		CMM	310.0x2	310.0x2	220.0 + 290.0 + 310.0
			l/s	5,166.7x2	5,166.7x2	3,666.7 + 4,833.3 + 5,166.7
External Static	Max.	mmAQ	8.00	8.00	8.00	
		Pa	78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	19.05	19.05	19.05
			Ø, inch	3/4"	3/4"	3/4"
	Gas Pipe		Ø, mm	41.28	41.28	41.28
			Ø, inch	1 5/8"	1 5/8"	1 5/8"
	Discharge Gas Pipe		Ø, mm	-	-	-
			Ø, inch	-	-	-
Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)	
	Max. Height	m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A
	Factory Charging		kg	28.60	28.60	29.20
Sound	Pressure		dBA	70.00	70.00	70.00
	Power			93.00	93.00	93.00
External Dimension	Net Weight		kg	360.0x2	360.0x2	201.0 + 300.0 + 360.0
	Shipping Weight		kg	375.0x2	375.0x2	217.0 + 319.0 + 375.0
	Net Dimensions (WxHxD)		mm	(1,295x1,695x765)x2	(1,295x1,695x765)x2	880x1,695x765 + (1,295x1,695x765)x2
	Shipping Dimensions (WxHxD)		mm	(1,363x1,887x832)x2	(1,363x1,887x832)x2	948x1,887x832 + (1,363x1,887x832)x2
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - High EER type (Compact)

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)
Model Name			AM620JXVHGH2EU	AM640JXVHGH2EU	AM680JXVHGH2EU	AM700JXVHGH2EU
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50
Mode			-	HP	HP	HP
Performance	HP		HP	62.00	64.00	68.00
			kW	173.60	179.20	190.40
	Capacity (Nominal)	Cooling	Btu/h	592,300	611,500	649,700
		Heating	kW	195.30	201.60	214.20
		Btu/h	666,400	687,900	730,900	
Power	Power Input (Nominal)	Cooling 1)	kW	43.97	46.17	48.60
		Heating 2)	kW	49.16	51.16	51.52
	Current Input (Nominal)	Cooling 1)	A	69.21	72.66	77.43
		Heating 2)	A	77.36	80.50	81.86
	MCA	A	155.60	158.90	171.70	
MFA	A	200.00	200.00	200.00		
COP	EER (Nominal Cooling)		-	3.95	3.88	3.92
	COP (Nominal Heating)		-	3.97	3.94	4.16
	Energy Grade		-	ESEER 6.53	ESEER 6.44	ESEER 6.38
Compressor	Type		-	SSC Scroll x 5	SSC Scroll x 5	SSC Scroll x 6
	Output		kW x n	(6.39) + (6.39x2) + (6.76x2)	(6.39) + (6.76x2)x2	(6.39x2)x2 + (6.39x2)
	Model Name		-	DS-GB066FAVBSGx3 + DS-GB070FAVASGx2	DS-GB066FAVBSGx1 + DS-GB070FAVASGx4	DS-GB066FAVBSGx6 + DS-GB070FAVASGx2
	Oil	Type	-	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller
	Output x n		W	830.0 + (620.0x2)x2	830.0 + (620.0x2)x2	(620.0x2)x3
	Air Flow Rate		CMM	220.0 + 310.0x2	220.0 + 310.0x2	290.0x2 + 310.0
			l/s	3,666.7 + 5,166.7x2	3,666.7 + 5,166.7x2	4,833.3x2 + 5,166.7
	External Static	Max.	mmAQ	8.00	8.00	8.00
Pa			78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	22.22	22.22	22.22
			Ø, inch	7/8"	7/8"	7/8"
	Gas Pipe		Ø, mm	53.98	53.98	53.98
			Ø, inch	2 1/8"	2 1/8"	2 1/8"
	Discharge Gas Pipe		Ø, mm	-	-	-
			Ø, inch	-	-	-
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)
Max. Height		m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A
	Factory Charging		kg	35.10	35.10	31.10
Sound	Pressure		dBA	71.00	71.00	71.00
	Power			94.00	94.00	94.00
External Dimension	Net Weight		kg	201.0 + 360.0x2	201.0 + 360.0x2	300.0x2 + 360.0
	Shipping Weight		kg	217.0 + 375.0x2	217.0 + 375.0x2	319.0x2 + 375.0
	Net Dimensions (WxHxD)		mm	880x1,695x765 + (1,295x1,695x765)x2	880x1,695x765 + (1,295x1,695x765)x2	(1,295x1,695x765)x3
	Shipping Dimensions (WxHxD)		mm	948x1,887x832 + (1,363x1,887x832)x2	948x1,887x832 + (1,363x1,887x832)x2	(1,363x1,887x832)x3
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - High EER type (Compact)

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)
Model Name			AM720JXVHGH2EU	AM740JXVHGH2EU	AM760JXVHGH2EU	AM780JXVHGH2EU
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50
Mode			-	HP	HP	HP
Performance	HP		HP	72.00	74.00	76.00
			kW	201.60	207.20	212.80
	Capacity (Nominal)	Cooling	Btu/h	687,900	707,000	726,100
		Heating	kW	226.80	233.10	239.40
		Btu/h	773,900	795,400	816,900	
Power	Power Input (Nominal)	Cooling 1)	kW	52.15	54.35	55.70
		Heating 2)	kW	57.46	59.46	63.40
	Current Input (Nominal)	Cooling 1)	A	82.41	85.86	87.39
		Heating 2)	A	90.66	93.80	99.46
	MCA	A	179.90	183.20	188.10	
MFA	A	200.00	200.00	200.00		
COP	EER (Nominal Cooling)		-	3.87	3.81	3.82
	COP (Nominal Heating)		-	3.95	3.92	3.78
	Energy Grade		-	ESEER 6.35	ESEER 6.28	ESEER 6.33
Compressor	Type		-	SSC Scroll x 6	SSC Scroll x 6	SSC Scroll x 6
	Output		kW x n	(6.39x2) + (6.39x2) + (6.76x2)	(6.39x2) + (6.76x2)x2	(6.39x2) + (6.76x2)x2
	Model Name		-	DS-GB066FAVBSGx4 + DS-GB070FAVASGx2	DS-GB066FAVBSGx2 + DS-GB070FAVASGx4	DS-GB066FAVBSGx2 + DS-GB070FAVASGx4
	Oil	Type	-	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller
	Output x n		W	(620.0x2)x3	(620.0x2)x3	(620.0x2)x3
	Air Flow Rate		CMM	290.0 + 310.0x2	290.0 + 310.0x2	310.0x3
			l/s	4,833.3 + 5,166.7x2	4,833.3 + 5,166.7x2	5,166.7x3
	External Static	Max.	mmAQ	8.00	8.00	8.00
Pa			78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	22.22	22.22	22.22
			Ø, inch	7/8"	7/8"	7/8"
	Gas Pipe		Ø, mm	53.98	53.98	53.98
			Ø, inch	2 1/8"	2 1/8"	2 1/8"
	Discharge Gas Pipe		Ø, mm	-	-	-
			Ø, inch	-	-	-
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)
Max. Height		m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A
	Factory Charging		kg	37.00	37.00	42.90
Sound	Pressure		dBA	71.00	71.00	72.00
	Power			95.00	95.00	96.00
External Dimension	Net Weight		kg	300.0 + 360.0x2	300.0 + 360.0x2	360.0x3
	Shipping Weight		kg	319.0 + 375.0x2	319.0 + 375.0x2	375.0x3
	Net Dimensions (WxHxD)		mm	(1,295x1,695x765)x3	(1,295x1,695x765)x3	(1,295x1,695x765)x3
	Shipping Dimensions (WxHxD)		mm	(1,363x1,887x832)x3	(1,363x1,887x832)x3	(1,363x1,887x832)x3
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - Standard type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)
Model Name			AM080JXVAGH/EU	AM100JXVAGH/EU	AM120JXVAGH/EU	AM140JXVAGH/EU
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50
Mode			-	HP	HP	HP
Performance	HP		HP	8.00	10.00	12.00
		Capacity (Nominal)	kW	22.40	28.00	33.60
	Cooling		Btu/h	76,400	95,500	114,600
		Heating	kW	25.20	31.50	37.80
		Btu/h	86,000	107,500	129,000	
Power	Power Input (Nominal)	Cooling 1)	kW	5.00	6.85	8.16
		Heating 2)	kW	5.10	6.65	8.03
	Current Input (Nominal)	Cooling 1)	A	8.00	11.00	13.10
		Heating 2)	A	8.20	10.70	12.90
	MCA	A	22.50	29.90	31.30	
MFA	A	30.00	40.00	40.00		
COP	EER (Nominal Cooling)		-	4.48	4.09	4.12
	COP (Nominal Heating)		-	4.94	4.74	4.71
	Energy Grade		-	ESEER 7.85	ESEER 7.25	ESEER 7.03
Compressor	Type		-	SSC Scroll x 1	SSC Scroll x 1	SSC Scroll x 1
	Output		kW x n	(4.39)	(6.39)	(6.39)
	Model Name		-	DS-GA046FAVAx1	DS-GB066FAVBx1	DS-GB066FAVBx1
	Oil	Type	-	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller
	Output x n		W	830.0	830.0	830.0
	Air Flow Rate		CMM	170	170	220
			l/s	2,833.33	2,833.33	3,666.67
	External Static	Max.	mmAQ	8.00	8.00	8.00
Pa			78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	9.52	9.52	12.70
			Ø, inch	3/8"	3/8"	1/2"
	Gas Pipe		Ø, mm	19.05	22.22	28.58
			Ø, inch	3/4"	7/8"	1 1/8"
	Discharge Gas Pipe		Ø, mm	-	-	-
			Ø, inch	-	-	-
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)
Max. Height		m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A
	Factory Charging		kg	5.50	5.50	6.50
Sound	Pressure		dBA	57.00	58.00	62.00
	Power			77.00	79.00	81.00
External Dimension	Net Weight		kg	186.0	197.0	210.0
	Shipping Weight		kg	202.0	213.0	223.0
	Net Dimensions (WxHxD)		mm	880x1,695x765	880x1,695x765	880x1,695x765
	Shipping Dimensions (WxHxD)		mm	948x1,887x832	948x1,887x832	948x1,887x832
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - Standard type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)
Model Name			AM160JXVAGH/EU	AM180JXVAGH/EU	AM200JXVAGH/EU	AM220JXVAGH/EU
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50
Mode			-	HP	HP	HP
Performance	HP		HP	16.00	18.00	20.00
			kW	45.00	50.40	56.00
	Capacity (Nominal)	Cooling	Btu/h	153,500	172,000	191,100
		Heating	kW	50.40	56.70	63.00
		Btu/h	172,000	193,500	215,000	
Power	Power Input (Nominal)	Cooling 1)	kW	11.98	12.45	14.59
		Heating 2)	kW	11.60	11.90	13.90
	Current Input (Nominal)	Cooling 1)	A	19.20	20.00	23.40
		Heating 2)	A	18.60	19.10	22.30
	MCA	A	40.00	48.90	52.50	
MFA	A	40.00	50.00	75.00		
COP	EER (Nominal Cooling)		-	3.76	4.05	3.84
	COP (Nominal Heating)		-	4.34	4.76	4.53
	Energy Grade		-	ESEER 6.78	ESEER 6.59	ESEER 6.56
Compressor	Type		-	SSC Scroll x 2	SSC Scroll x 2	SSC Scroll x 2
	Output		kW x n	(4.39 x 2)	(6.39 x 2)	(6.39 x 2)
	Model Name		-	DS-GA046FAVAx2	DS-GB066FAVBx2	DS-GB066FAVBx2
	Oil	Type	-	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller
	Output x n		W	620.0x2	620.0x2	620.0x2
	Air Flow Rate		CMM	255	290	290
			l/s	4,250.00	4,833.33	4,833.33
	External Static	Max.	mmAQ	8.00	8.00	8.00
Pa			78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	12.70	15.88	15.88
			Ø, inch	1/2"	5/8"	5/8"
	Gas Pipe		Ø, mm	28.58	28.58	28.58
			Ø, inch	1 1/8"	1 1/8"	1 1/8"
	Discharge Gas Pipe		Ø, mm	-	-	-
			Ø, inch	-	-	-
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)
Max. Height		m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A
	Factory Charging		kg	7.70	8.40	8.40
Sound	Pressure		dBA	63.00	64.00	65.00
	Power			83.00	86.00	87.00
External Dimension	Net Weight		kg	269.0	307.0	307.0
	Shipping Weight		kg	288.0	326.0	326.0
	Net Dimensions (WxHxD)		mm	1,295x1,695x765	1,295x1,695x765	1,295x1,695x765
	Shipping Dimensions (WxHxD)		mm	1,363x1,887x832	1,363x1,887x832	1,363x1,887x832
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - Standard type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)
Model Name			AM240HXVAGH/EU	AM260HXVAGH/EU	AM280JXVAGH1EU	AM300JXVAGH1EU
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50
Mode			-	HP	HP	HP
Performance	HP		HP	24.00	26.00	28.00
			kW	67.20	72.80	78.60
	Capacity (Nominal)	Cooling	Btu/h	229,300	248,400	268,200
		Heating	kW	75.60	81.90	88.20
		Btu/h	258,000	279,500	301,000	
Power	Power Input (Nominal)	Cooling 1)	kW	17.10	19.30	20.14
		Heating 2)	kW	19.80	21.80	19.63
	Current Input (Nominal)	Cooling 1)	A	26.83	30.28	32.30
		Heating 2)	A	31.06	34.20	31.50
MCA	A	60.50	63.80	71.30		
MFA	A	75.00	75.00	75.00		
COP	EER (Nominal Cooling)		-	3.93	3.77	3.90
	COP (Nominal Heating)		-	3.82	3.76	4.49
	Energy Grade		-	ESEER 6.48	ESEER 6.26	ESEER 6.89
Compressor	Type		-	SSC Scroll x 2	SSC Scroll x 2	SSC Scroll x 3
	Output		kW x n	(6.39 x 2)	(6.76 x 2)	(6.39) + (4.39x2)
	Model Name		-	DS-GB066FAVBSGx2	DS-GB070FAVASGx2	DS-GB066FAVBx1 + DS-GA046FAVAx2
	Oil	Type	-	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller
	Output x n		W	620.0x2	620.0x2	830.0 + 620.0x2
	Air Flow Rate		CMM	310	310	220.0 + 255.0
			l/s	5,166.67	5,166.67	3,666.7 + 4,250.0
External Static	Max.	mmAQ	8.00	8.00	8.00	
		Pa	78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	15.88	19.05	19.05
			Ø, inch	5/8"	3/4"	3/4"
	Gas Pipe		Ø, mm	34.92	34.92	34.92
			Ø, inch	1 3/8"	1 3/8"	1 3/8"
	Discharge Gas Pipe		Ø, mm	-	-	-
			Ø, inch	-	-	-
Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)	
	Max. Height	m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A
	Factory Charging		kg	14.30	14.30	14.20
Sound	Pressure		dBA	67.00	67.00	66.00
	Power			91.00	91.00	85.00
External Dimension	Net Weight		kg	360.0	360.0	210.0 + 269.0
	Shipping Weight		kg	375.0	375.0	223.0 + 288.0
	Net Dimensions (WxHxD)		mm	1,295x1,695x765	1,295x1,695x765	880x1,695x765 + 1,295x1,695x765
	Shipping Dimensions (WxHxD)		mm	1,363x1,887x832	1,363x1,887x832	948x1,887x832 + 1,363x1,887x832
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - Standard type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	
Model Name			AM320JXVAGH1EU	AM340JXVAGH1EU	AM360JXVAGH1EU	AM380JXVAGH1EU	
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50	
Mode			-	HP	HP	HP	
Performance	HP		HP	32.00	34.00	36.00	
			kW	89.60	95.20	101.60	
	Capacity (Nominal)	Cooling		Btu/h	305,700	324,800	346,700
				kW	100.80	107.10	114.30
		Heating		Btu/h	343,900	365,400	390,000
Power	Power Input (Nominal)	Cooling 1)	kW	22.75	25.51	28.28	
		Heating 2)	kW	21.93	24.73	26.85	
	Current Input (Nominal)	Cooling 1)	A	36.50	40.90	45.30	
		Heating 2)	A	35.20	39.70	43.10	
	MCA	A	83.80	86.90	86.90		
MFA	A	90.00	90.00	90.00			
COP	EER (Nominal Cooling)		-	3.94	3.73	3.59	
	COP (Nominal Heating)		-	4.60	4.33	4.26	
	Energy Grade		-	ESEER 6.74	ESEER 6.53	ESEER 6.55	
Compressor	Type		-	SSC Scroll x 3	SSC Scroll x 3	SSC Scroll x 3	
	Output		kW x n	(6.39) + (6.39x2)	(6.39) + (6.39x2)	(6.39) + (6.39x2)	
	Model Name		-	DS-GB066FAVBx3	DS-GB066FAVBx3	DS-GB066FAVBx3	
	Oil	Type	-	PVE	PVE	PVE	
Fan	Type		-	Propeller	Propeller	Propeller	
	Output x n		W	830.0 + 620.0x2	830.0 + 620.0x2	(620.0x2)x2	
	Air Flow Rate		CMM	220.0 + 290.0	220.0 + 290.0	255.0 + 290.0	
			l/s	3,666.7 + 4,833.3	3,666.7 + 4,833.3	4,250.0 + 4,833.3	
	External Static	Max.	mmAQ	8.00	8.00	8.00	
Pa			78.40	78.40	78.40		
Piping Connections	Liquid Pipe		Ø, mm	19.05	19.05	19.05	
			Ø, inch	3/4"	3/4"	3/4"	
	Gas Pipe		Ø, mm	34.92	34.92	41.28	
			Ø, inch	1 3/8"	1 3/8"	1 5/8"	
	Discharge Gas Pipe		Ø, mm	-	-	-	
			Ø, inch	-	-	-	
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)	
Max. Height		m	110 (40)	110 (40)	110 (40)		
Field Wiring	Power Source Wire		mm ²	-	-	-	
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50	
Refrigerant	Type		-	R410A	R410A	R410A	
	Factory Charging		kg	14.90	14.90	16.10	
Sound	Pressure		dBA	67.00	67.00	67.00	
	Power			88.00	90.00	90.00	
External Dimension	Net Weight		kg	210.0 + 307.0	210.0 + 307.0	239.0 + 307.0	
	Shipping Weight		kg	223.0 + 326.0	223.0 + 326.0	258.0 + 326.0	
	Net Dimensions (WxHxD)		mm	880x1,695x765 + 1,295x1,695x765	880x1,695x765 + 1,295x1,695x765	(1,295x1,695x765)x2	
	Shipping Dimensions (WxHxD)		mm	948x1,887x832 + 1,363x1,887x832	948x1,887x832 + 1,363x1,887x832	(1,363x1,887x832)x2	
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0	
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0	

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - Standard type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)		
Model Name			AM400JXVAGH1EU	AM420JXVAGH1EU	AM440JXVAGH1EU	AM460JXVAGH1EU		
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50		
Mode			-	HP	HP	HP		
Performance	HP	Capacity (Nominal)	HP	40.00	42.00	44.00	46.00	
			Cooling	kW	112.80	117.60	123.20	128.80
				Btu/h	384,900	401,300	420,400	439,500
			Heating	kW	126.90	132.30	138.60	144.90
Btu/h	433,000	451,400		472,900	494,400			
Power	Power Input (Nominal)	Cooling 1)	kW	30.23	31.94	34.70	33.67	
		Heating 2)	kW	31.95	30.60	33.40	32.76	
	Current Input (Nominal)	Cooling 1)	A	47.78	51.20	55.60	54.00	
		Heating 2)	A	50.50	49.10	53.60	52.60	
	MCA	A	95.10	108.10	111.20	118.20		
MFA	A	100.00	125.00	125.00	125.00			
COP	EER (Nominal Cooling)		-	3.73	3.68	3.55	3.83	
	COP (Nominal Heating)		-	3.97	4.32	4.15	4.42	
	Energy Grade		-	ESEER 6.53	ESEER 6.40	ESEER 6.25	ESEER 6.66	
Compressor	Type		-	SSC Scroll x 3	SSC Scroll x 4	SSC Scroll x 4	SSC Scroll x 4	
	Output		kW x n	(6.39) + (6.76x2)	(6.39x2) + (6.39x2)	(6.39x2)x2	(6.39)x2 + (6.39x2)	
	Model Name		-	DS-GB066FAVBx1 + DS-GB070FAVASGx2	DS-GB066FAVBx4	DS-GB066FAVBx4	DS-GB066FAVBx4	
	Oil	Type	-	PVE	PVE	PVE	PVE	
Fan	Type		-	Propeller	Propeller	Propeller	Propeller	
	Output x n		W	(620.0x2)x2	(620.0x2)x2	(620.0x2)x2	(830.0)x2 + 620.0x2	
	Air Flow Rate		CMM	255.0 + 310.0	290.0x2	290.0x2	220.0x2 + 290.0	
			l/s	4,250.0 + 5,166.7	4,833.3x2	4,833.3x2	3,666.7x2 + 4,833.3	
	External Static	Max.	mmAQ	8.00	8.00	8.00	8.00	
Pa			78.40	78.40	78.40	78.40		
Piping Connections	Liquid Pipe		Ø, mm	19.05	19.05	19.05	19.05	
			Ø, inch	3/4"	3/4"	3/4"	3/4"	
	Gas Pipe		Ø, mm	41.28	41.28	41.28	41.28	
			Ø, inch	1 5/8"	1 5/8"	1 5/8"	1 5/8"	
	Discharge Gas Pipe		Ø, mm	-	-	-	-	
			Ø, inch	-	-	-	-	
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)	200 (220)	
Max. Height			m	110 (40)	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-	-	
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50	
Refrigerant	Type		-	R410A	R410A	R410A	R410A	
	Factory Charging		kg	22.00	16.80	16.80	21.40	
Sound	Pressure		dBA	68.00	69.00	69.00	69.00	
	Power			91.00	91.00	92.00	90.00	
External Dimension	Net Weight		kg	239.0 + 360.0	307.0x2	307.0x2	210.0x2 + 307.0	
	Shipping Weight		kg	258.0 + 375.0	326.0x2	326.0x2	223.0x2 + 326.0	
	Net Dimensions (WxHxD)		mm	(1,295x1,695x765)x2	(1,295x1,695x765)x2	(1,295x1,695x765)x2	(880x1,695x765)x2 + 1,295x1,695x765	
	Shipping Dimensions (WxHxD)		mm	(1,363x1,887x832)x2	(1,363x1,887x832)x2	(1,363x1,887x832)x2	(948x1,887x832)x2 + 1,363x1,887x832	
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0	
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0	

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - Standard type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	
Model Name			AM480JXVAGH1EU	AM500JXVAGH1EU	AM520JXVAGH1EU	AM540JXVAGH1EU	
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50	
Mode			-	HP	HP	HP	
Performance	Capacity (Nominal)	Cooling	HP	48.00	50.00	52.00	54.00
			kW	135.20	140.20	145.60	151.20
		Heating	Btu/h	461,300	478,400	496,800	515,900
			kW	152.10	157.50	163.80	170.10
Power	Power Input (Nominal)	Cooling 1)	kW	36.44	37.49	37.96	40.10
		Heating 2)	kW	34.88	36.33	36.63	38.63
	Current Input (Nominal)	Cooling 1)	A	58.40	60.10	60.90	64.30
		Heating 2)	A	56.00	58.30	58.80	62.00
	MCA	A	118.20	126.90	135.80	139.40	
	MFA	A	125.00	150.00	150.00	150.00	
COP	EER (Nominal Cooling)		-	3.71	3.74	3.84	3.77
	COP (Nominal Heating)		-	4.36	4.34	4.47	4.40
	Energy Grade		-	ESEER 6.67	ESEER 6.61	ESEER 6.55	ESEER 6.54
Compressor	Type		-	SSC Scroll x 4	SSC Scroll x 5	SSC Scroll x 5	SSC Scroll x 5
	Output		kW x n	(6.39) + (6.39) + (6.39x2)	(6.39) + (4.39x2) + (6.39x2)	(6.39) + (6.39x2) + (6.39x2)	(6.39) + (6.39x2) + (6.39x2)
	Model Name		-	DS-GB066FAVBx4	DS-GB066FAVBx3 + DS-GA046FAVAX2	DS-GB066FAVBx5	DS-GB066FAVBx5
	Oil	Type	-	PVE	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller	Propeller
	Output x n		W	830.0 + (620.0x2)x2	830.0 + (620.0x2)x2	830.0 + (620.0x2)x2	830.0 + (620.0x2)x2
	Air Flow Rate		CMM	220.0 + 255.0 + 290.0	220.0 + 255.0 + 290.0	220.0 + 290.0x2	220.0 + 290.0x2
			l/s	3,666.7 + 4,250.0 + 4,833.3	3,666.7 + 4,250.0 + 4,833.3	3,666.7 + 4,833.3x2	3,666.7 + 4,833.3x2
	External Static	Max.	mmAQ	8.00	8.00	8.00	8.00
Pa			78.40	78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	19.05	19.05	19.05	19.05
			Ø, inch	3/4"	3/4"	3/4"	3/4"
	Gas Pipe		Ø, mm	41.28	41.28	41.28	41.28
			Ø, inch	1 5/8"	1 5/8"	1 5/8"	1 5/8"
	Discharge Gas Pipe		Ø, mm	-	-	-	-
			Ø, inch	-	-	-	-
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)	200 (220)
Max. Height		m	110 (40)	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A	R410A
	Factory Charging		kg	22.60	22.60	23.30	23.30
Sound	Pressure		dBA	68.00	69.00	69.00	69.00
	Power			90.00	90.00	91.00	92.00
External Dimension	Net Weight		kg	210.0 + 239.0 + 307.0	210.0 + 269.0 + 307.0	210.0 + 307.0x2	210.0 + 307.0x2
	Shipping Weight		kg	223.0 + 258.0 + 326.0	223.0 + 288.0 + 326.0	223.0 + 326.0x2	223.0 + 326.0x2
	Net Dimensions (WxHxD)		mm	880x1,695x765 + (1,295x1,695x765)x2	880x1,695x765 + (1,295x1,695x765)x2	880x1,695x765 + (1,295x1,695x765)x2	880x1,695x765 + (1,295x1,695x765)x2
	Shipping Dimensions (WxHxD)		mm	948x1,887x832 + (1,363x1,887x832)x2	948x1,887x832 + (1,363x1,887x832)x2	948x1,887x832 + (1,363x1,887x832)x2	948x1,887x832 + (1,363x1,887x832)x2
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - Standard type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)
Model Name			AM560JXVAGH1EU	AM580JXVAGH1EU	AM600JXVAGH1EU	AM620JXVAGH1EU
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50
Mode			-	HP	HP	HP
Performance	HP		HP	56.00	58.00	60.00
			kW	156.80	163.20	168.20
	Capacity (Nominal)	Cooling	Btu/h	535,000	556,900	573,900
		Heating	kW	176.40	183.60	189.00
		Btu/h	601,900	626,500	644,900	
Power	Power Input (Nominal)	Cooling 1)	kW	42.86	45.63	46.68
		Heating 2)	kW	41.43	43.55	45.00
	Current Input (Nominal)	Cooling 1)	A	68.70	73.10	74.80
		Heating 2)	A	66.50	69.90	72.20
MCA	A	142.50	142.50	151.20	160.10	
MFA	A	150.00	150.00	150.00	200.00	
COP	EER (Nominal Cooling)		-	3.66	3.58	3.60
	COP (Nominal Heating)		-	4.26	4.22	4.20
	Energy Grade		-	ESEER 6.42	ESEER 6.44	ESEER 6.39
Compressor	Type		-	SSC Scroll x 5	SSC Scroll x 5	SSC Scroll x 6
	Output		kW x n	(6.39) + (6.39x2)x2	(6.39) + (6.39x2)x2	(4.39x2) + (6.39x2)x2
	Model Name		-	DS-GB066FAVBx5	DS-GB066FAVBx5	DS-GA046FAVAx2 + DS-GB066FAVBx4
	Oil	Type	-	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller
	Output x n		W	830.0 + (620.0x2)x2	(620.0x2)x3	(620.0x2)x3
	Air Flow Rate		CMM	220.0 + 290.0x2	255.0 + 290.0x2	255.0 + 290.0x2
			l/s	3,666.7 + 4,833.3x2	4,250.0 + 4,833.3x2	4,250.0 + 4,833.3x2
	External Static	Max.	mmAQ	8.00	8.00	8.00
Pa			78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	19.05	19.05	22.22
			Ø, inch	3/4"	3/4"	7/8"
	Gas Pipe		Ø, mm	41.28	41.28	41.28
			Ø, inch	1 5/8"	1 5/8"	1 5/8"
	Discharge Gas Pipe		Ø, mm	-	-	-
			Ø, inch	-	-	-
Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)	
	Max. Height	m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A
	Factory Charging		kg	23.30	24.50	24.50
Sound	Pressure		dBA	70.00	70.00	70.00
	Power			92.00	92.00	93.00
External Dimension	Net Weight		kg	210.0 + 307.0x2	239.0 + 307.0x2	269.0 + 307.0x2
	Shipping Weight		kg	223.0 + 326.0x2	258.0 + 326.0x2	288.0 + 326.0x2
	Net Dimensions (WxHxD)		mm	880x1,695x765 + (1,295x1,695x765)x2	(1,295x1,695x765)x3	(1,295x1,695x765)x3
	Shipping Dimensions (WxHxD)		mm	948x1,887x832 + (1,363x1,887x832)x2	(1,363x1,887x832)x3	(1,363x1,887x832)x3
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - Standard type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)
Model Name			AM640JXVAGH1EU	AM660JXVAGH1EU	AM680JXVAGH1EU	AM700JXVAGH1EU
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50
Mode			-	HP	HP	HP
Performance	HP		HP	64.00	66.00	68.00
		Capacity (Nominal)	Cooling	kW	179.20	184.80
	Btu/h			611,500	630,600	649,700
		Heating	kW	201.60	207.90	214.20
Btu/h			687,900	709,400	730,900	
Power	Power Input (Nominal)	Cooling 1)	kW	49.29	52.05	51.02
		Heating 2)	kW	47.30	50.10	49.46
	Current Input (Nominal)	Cooling 1)	A	79.00	83.40	81.80
		Heating 2)	A	75.90	80.40	79.40
MCA	A	163.70	166.80	173.80	173.80	
MFA	A	200.00	200.00	200.00	200.00	
COP	EER (Nominal Cooling)		-	3.64	3.55	3.73
	COP (Nominal Heating)		-	4.26	4.15	4.33
	Energy Grade		-	ESEER 6.35	ESEER 6.25	ESEER 6.53
Compressor	Type		-	SSC Scroll x 6	SSC Scroll x 6	SSC Scroll x 6
	Output		kW x n	(6.39x2) + (6.39x2)x2	(6.39x2)x3	(6.39)x2 + (6.39x2)x2
	Model Name		-	DS-GB066FAVBx6	DS-GB066FAVBx6	DS-GB066FAVBx6
	Oil	Type	-	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller
	Output x n		W	(620.0x2)x3	(620.0x2)x3	(830.0)x2 + (620.0x2)x2
	Air Flow Rate		CMM	290.0x3	290.0x3	220.0x2 + 290.0x2
			l/s	4,833.3x3	4,833.3x3	3,666.7x2 + 4,833.3x2
External Static	Max.	mmAQ	8.00	8.00	8.00	
		Pa	78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	22.22	22.22	22.22
			Ø, inch	7/8"	7/8"	7/8"
	Gas Pipe		Ø, mm	53.98	53.98	53.98
			Ø, inch	2 1/8"	2 1/8"	2 1/8"
	Discharge Gas Pipe		Ø, mm	-	-	-
			Ø, inch	-	-	-
Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)	
	Max. Height	m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A
	Factory Charging		kg	25.20	25.20	29.80
Sound	Pressure		dBA	70.00	71.00	70.00
	Power			93.00	94.00	93.00
External Dimension	Net Weight		kg	307.0x3	307.0x3	210.0x2 + 307.0x2
	Shipping Weight		kg	326.0x3	326.0x3	223.0x2 + 326.0x2
	Net Dimensions (WxHxD)		mm	(1,295x1,695x765)x3	(1,295x1,695x765)x3	(880x1,695x765)x2 + (1,295x1,695x765)x2
	Shipping Dimensions (WxHxD)		mm	(1,363x1,887x832)x3	(1,363x1,887x832)x3	(948x1,887x832)x2 + (1,363x1,887x832)x2
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - Standard type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)
Model Name			AM720JXVAGH1EU	AM740JXVAGH1EU	AM760JXVAGH1EU	AM780JXVAGH1EU
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50
Mode			-	HP	HP	HP
Performance	HP		HP	72.00	74.00	76.00
		Capacity (Nominal)	Cooling	kW	201.80	207.20
	Btu/h			688,600	707,000	726,100
		Heating	kW	226.80	233.10	239.40
Btu/h			773,900	795,400	816,900	
Power	Power Input (Nominal)	Cooling 1)	kW	54.84	55.31	57.45
		Heating 2)	kW	53.03	53.33	55.33
	Current Input (Nominal)	Cooling 1)	A	87.90	88.70	92.10
		Heating 2)	A	85.10	85.60	88.80
	MCA	A	182.50	191.40	195.00	
MFA	A	200.00	200.00	200.00		
COP	EER (Nominal Cooling)		-	3.68	3.75	3.70
	COP (Nominal Heating)		-	4.28	4.37	4.33
	Energy Grade		-	ESEER 6.50	ESEER 6.46	ESEER 6.45
Compressor	Type		-	SSC Scroll x 7	SSC Scroll x 7	SSC Scroll x 7
	Output		kW x n	(6.39) + (4.39x2) + (6.39x2)x2	(6.39) + (6.39x2) + (6.39x2)x2	(6.39) + (6.39x2) + (6.39x2)x2
	Model Name		-	DS-GB066FAVBx5 + DS-GA046FAVAx2	DS-GB066FAVBx7	DS-GB066FAVBx7
	Oil	Type	-	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller
	Output x n		W	830.0 + (620.0x2)x3	830.0 + (620.0x2)x3	830.0 + (620.0x2)x3
	Air Flow Rate		CMM	220.0 + 255.0 + 290.0x2	220.0 + 290.0x3	220.0 + 290.0x3
			l/s	3,666.7 + 4,250.0 + 4,833.3x2	3,666.7 + 4,833.3x3	3,666.7 + 4,833.3x3
External Static	Max.	mmAQ	8.00	8.00	8.00	
Piping Connections	Liquid Pipe		Ø, mm	22.22	22.22	22.22
			Ø, inch	7/8"	7/8"	7/8"
	Gas Pipe		Ø, mm	53.98	53.98	53.98
			Ø, inch	2 1/8"	2 1/8"	2 1/8"
	Discharge Gas Pipe		Ø, mm	-	-	-
			Ø, inch	-	-	-
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)
Max. Height		m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A
	Factory Charging		kg	31.00	31.70	31.70
Sound	Pressure		dBA	71.00	71.00	71.00
	Power			93.00	93.00	93.00
External Dimension	Net Weight		kg	210.0 + 269.0 + 307.0x2	210.0 + 307.0x3	210.0 + 307.0x3
	Shipping Weight		kg	223.0 + 288.0 + 326.0x2	223.0 + 326.0x3	223.0 + 326.0x3
	Net Dimensions (WxHxD)		mm	880x1,695x765 + (1,295x1,695x765)x3	880x1,695x765 + (1,295x1,695x765)x3	880x1,695x765 + (1,295x1,695x765)x3
	Shipping Dimensions (WxHxD)		mm	948x1,887x832 + (1,363x1,887x832)x3	948x1,887x832 + (1,363x1,887x832)x3	948x1,887x832 + (1,363x1,887x832)x3
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - Standard type

Outdoor

Type			DVM S(NEW)	
Model Name			AM800JXVAGH1EU	
Power Supply		Ø, #, V, Hz	3,4,380-415,50	
Mode			HP	
Performance	HP	HP	80.00	
	Capacity (Nominal)	Cooling	kW	224.80
			Btu/h	767,000
		Heating	kW	252.90
			Btu/h	862,900
Power	Power Input (Nominal)	Cooling 1)	kW	62.98
		Heating 2)	kW	60.25
	Current Input (Nominal)	Cooling 1)	A	100.90
		Heating 2)	A	96.70
	MCA	A	198.10	
MFA	A	200.00		
COP	EER (Nominal Cooling)		-	3.57
	COP (Nominal Heating)		-	4.20
	Energy Grade		-	ESEER 6.39
Compressor	Type		-	SSC Scroll x 7
	Output		kW x n	(6.39) + (6.39x2)x3
	Model Name		-	DS-GB066FAVBx7
	Oil	Type	-	PVE
Fan	Type		-	Propeller
	Output x n		W	(620.0x2)x4
	Air Flow Rate		CMM	255.0 + 290.0x3
			l/s	4,250.0 + 4,833.3x3
	External Static	Max.	mmAQ	8.00
Pa			78.40	
Piping Connections	Liquid Pipe		Ø, mm	22.22
			Ø, inch	7/8"
	Gas Pipe		Ø, mm	53.98
			Ø, inch	2 1/8"
	Discharge Gas Pipe		Ø, mm	-
			Ø, inch	-
	Installation Limitation	Max. Length	m	200 (220)
Max. Height		m	110 (40)	
Field Wiring	Power Source Wire		mm ²	-
	Transmission Cable		mm ²	0.75 ~ 1.50
Refrigerant	Type		-	R410A
	Factory Charging		kg	32.90
Sound	Pressure		dBA	71.00
	Power			94.00
External Dimension	Net Weight		kg	239.0 + 307.0x3
	Shipping Weight		kg	258.0 + 326.0x3
	Net Dimensions (WxHxD)		mm	(1,295x1,695x765)x4
	Shipping Dimensions (WxHxD)		mm	(1,363x1,887x832)x4
Operating Temp.	Cooling		°C	-5.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - Standard type (Compact)

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	
Model Name			AM360JXVAGH2EU	AM380JXVAGH2EU	AM460JXVAGH2EU	AM480JXVAGH2EU	
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50	
Mode			-	HP	HP	HP	
Performance	HP		HP	36.00	38.00	46.00	
			kW	100.80	106.40	128.80	
	Capacity (Nominal)	Cooling		Btu/h	343,900	363,100	439,500
				kW	113.40	119.70	144.90
		Heating		Btu/h	386,900	408,400	494,400
			kW	113.40	119.70	144.90	
Power	Power Input (Nominal)	Cooling 1)	kW	25.26	27.46	33.89	
		Heating 2)	kW	27.83	29.83	35.70	
	Current Input (Nominal)	Cooling 1)	A	39.93	43.38	53.68	
		Heating 2)	A	43.96	47.10	56.50	
	MCA	A	91.80	95.10	116.30		
MFA	A	125.00	125.00	125.00			
COP	EER (Nominal Cooling)		-	3.99	3.87	3.80	
	COP (Nominal Heating)		-	4.07	4.01	4.06	
	Energy Grade		-	ESEER 6.66	ESEER 6.50	ESEER 6.39	
Compressor	Type		-	SSC Scroll x 3	SSC Scroll x 3	SSC Scroll x 4	
	Output		kW x n	(6.39) + (6.39x2)	(6.39) + (6.76x2)	(6.39x2) + (6.76x2)	
	Model Name		-	DS-GB066FAVBx1 + DS-GB066FAVBx2	DS-GB066FAVBx1 + DS-GB070FAVASGx2	DS-GB066FAVBx2 + DS-GB070FAVASGx2	
	Oil	Type	-	PVE	PVE	PVE	
	Type		-	Propeller	Propeller	Propeller	
Fan	Type		-	Propeller	Propeller	Propeller	
	Output x n		W	830.0 + 620.0x2	830.0 + 620.0x2	(620.0x2)x2	
	Air Flow Rate		CMM	220.0 + 310.0	220.0 + 310.0	290.0 + 310.0	
			l/s	3,666.7 + 5,166.7	3,666.7 + 5,166.7	4,833.3 + 5,166.7	
	External Static	Max.	mmAQ	8.00	8.00	8.00	
Pa			78.40	78.40	78.40		
Piping Connections	Liquid Pipe		Ø, mm	19.05	19.05	19.05	
			Ø, inch	3/4"	3/4"	3/4"	
	Gas Pipe		Ø, mm	41.28	41.28	41.28	
			Ø, inch	1 5/8"	1 5/8"	1 5/8"	
	Discharge Gas Pipe		Ø, mm	-	-	-	
			Ø, inch	-	-	-	
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)	
Max. Height		m	110 (40)	110 (40)	110 (40)		
Field Wiring	Power Source Wire		mm ²	-	-	-	
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50	
Refrigerant	Type		-	R410A	R410A	R410A	
	Factory Charging		kg	20.80	20.80	22.70	
Sound	Pressure		dBA	68.00	68.00	69.00	
	Power			91.00	91.00	92.00	
External Dimension	Net Weight		kg	210.0 + 360.0	210.0 + 360.0	307.0 + 360.0	
	Shipping Weight		kg	223.0 + 375.0	223.0 + 375.0	326.0 + 375.0	
	Net Dimensions (WxHxD)		mm	880x1,695x765 + 1,295x1,695x765	880x1,695x765 + 1,295x1,695x765	(1,295x1,695x765)x2	
	Shipping Dimensions (WxHxD)		mm	948x1,887x832 + 1,363x1,887x832	948x1,887x832 + 1,363x1,887x832	(1,363x1,887x832)x2	
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0	
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0	

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - Standard type (Compact)

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)
Model Name			AM500JXVAGH2EU	AM520JXVAGH2EU	AM580JXVAGH2EU	AM600JXVAGH2EU
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50
Mode			-	HP	HP	HP
Performance	HP		HP	50.00	52.00	58.00
			kW	140.00	145.60	162.40
	Capacity (Nominal)	Cooling	Btu/h	477,700	496,800	554,100
		Heating	kW	157.50	163.80	182.70
		Btu/h	537,400	558,900	623,400	
Power	Power Input (Nominal)	Cooling 1)	kW	36.40	38.60	42.05
		Heating 2)	kW	41.60	43.60	43.73
	Current Input (Nominal)	Cooling 1)	A	57.11	60.56	66.78
		Heating 2)	A	65.26	68.40	69.40
MCA	A	124.30	127.60	147.60		
MFA	A	150.00	150.00	200.00		
COP	EER (Nominal Cooling)		-	3.85	3.77	3.86
	COP (Nominal Heating)		-	3.79	3.76	4.18
	Energy Grade		-	ESEER 6.37	ESEER 6.26	ESEER 6.52
Compressor	Type		-	SSC Scroll x 4	SSC Scroll x 4	SSC Scroll x 5
	Output		kW x n	(6.39x2) + (6.76x2)	(6.76x2)x2	(6.39) + (6.39x2) + (6.76x2)
	Model Name		-	DS-GB066FAVBSGx2 + DS-GB070FAVASGx2	DS-GB070FAVASGx4	DS-GB066FAVBx3 + DS-GB070FAVASGx2
	Oil	Type	-	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller
	Output x n		W	(620.0x2)x2	(620.0x2)x2	830.0 + (620.0x2)x2
	Air Flow Rate		CMM	310.0x2	310.0x2	220.0 + 290.0 + 310.0
			l/s	5,166.7x2	5,166.7x2	3,666.7 + 4,833.3 + 5,166.7
External Static	Max.	mmAQ	8.00	8.00	8.00	
		Pa	78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	19.05	19.05	19.05
			Ø, inch	3/4"	3/4"	3/4"
	Gas Pipe		Ø, mm	41.28	41.28	41.28
			Ø, inch	1 5/8"	1 5/8"	1 5/8"
	Discharge Gas Pipe		Ø, mm	-	-	-
			Ø, inch	-	-	-
Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)	
	Max. Height	m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A
	Factory Charging		kg	28.60	28.60	29.20
Sound	Pressure		dBA	70.00	70.00	70.00
	Power			93.00	93.00	93.00
External Dimension	Net Weight		kg	360.0x2	360.0x2	210.0 + 307.0 + 360.0
	Shipping Weight		kg	375.0x2	375.0x2	223.0 + 326.0 + 375.0
	Net Dimensions (WxHxD)		mm	(1,295x1,695x765)x2	(1,295x1,695x765)x2	880x1,695x765 + (1,295x1,695x765)x2
	Shipping Dimensions (WxHxD)		mm	(1,363x1,887x832)x2	(1,363x1,887x832)x2	948x1,887x832 + (1,363x1,887x832)x2
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - Standard type (Compact)

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)
Model Name			AM620JXVAGH2EU	AM640JXVAGH2EU	AM680JXVAGH2EU	AM700JXVAGH2EU
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50
Mode			-	HP	HP	HP
Performance	HP		HP	62.00	64.00	68.00
			kW	173.60	179.20	190.40
	Capacity (Nominal)	Cooling	Btu/h	592,300	611,500	649,700
		Heating	kW	195.30	201.60	214.20
		Btu/h	666,400	687,900	730,900	
Power	Power Input (Nominal)	Cooling 1)	kW	44.56	46.76	51.80
		Heating 2)	kW	49.63	51.63	53.20
	Current Input (Nominal)	Cooling 1)	A	70.21	73.66	82.43
		Heating 2)	A	78.16	81.30	84.66
MCA	A	155.60	158.90	171.70	175.00	
MFA	A	200.00	200.00	200.00	200.00	
COP	EER (Nominal Cooling)		-	3.90	3.83	3.68
	COP (Nominal Heating)		-	3.94	3.90	4.03
	Energy Grade		-	ESEER 6.49	ESEER 6.40	ESEER 6.33
Compressor	Type		-	SSC Scroll x 5	SSC Scroll x 5	SSC Scroll x 6
	Output		kW x n	(6.39) + (6.39x2) + (6.76x2)	(6.39) + (6.76x2)x2	(6.39x2)x2 + (6.39x2)
	Model Name		-	DS-GB066FAVBx1 + DS-GB066FAVBx2 + DS-GB070FAVAGx2	DS-GB066FAVBx1 + DS-GB070FAVAGx4	DS-GB066FAVBx4 + DS-GB066FAVBx2
	Oil	Type	-	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller
	Output x n		W	830.0 + (620.0x2)x2	830.0 + (620.0x2)x2	(620.0x2)x3
	Air Flow Rate		CMM	220.0 + 310.0x2	220.0 + 310.0x2	290.0x2 + 310.0
			l/s	3,666.7 + 5,166.7x2	3,666.7 + 5,166.7x2	4,833.3x2 + 5,166.7
External Static	Max.	mmAQ	8.00	8.00	8.00	
		Pa	78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	22.22	22.22	22.22
			Ø, inch	7/8"	7/8"	7/8"
	Gas Pipe		Ø, mm	53.98	53.98	53.98
			Ø, inch	2 1/8"	2 1/8"	2 1/8"
	Discharge Gas Pipe		Ø, mm	-	-	-
			Ø, inch	-	-	-
Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)	
	Max. Height	m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A
	Factory Charging		kg	35.10	35.10	31.10
Sound	Pressure		dBA	71.00	71.00	71.00
	Power			94.00	94.00	95.00
External Dimension	Net Weight		kg	210.0 + 360.0x2	210.0 + 360.0x2	307.0x2 + 360.0
	Shipping Weight		kg	223.0 + 375.0x2	223.0 + 375.0x2	326.0x2 + 375.0
	Net Dimensions (WxHxD)		mm	880x1,695x765 + (1,295x1,695x765)x2	880x1,695x765 + (1,295x1,695x765)x2	(1,295x1,695x765)x3
	Shipping Dimensions (WxHxD)		mm	948x1,887x832 + (1,363x1,887x832)x2	948x1,887x832 + (1,363x1,887x832)x2	(1,363x1,887x832)x3
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/P - Standard type (Compact)

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)			
Model Name			AM720JXVAGH2EU	AM740JXVAGH2EU	AM760JXVAGH2EU	AM780JXVAGH2EU			
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50			
Mode			-	HP	HP	HP			
Performance	HP	Capacity (Nominal)	HP	72.00	74.00	76.00	78.00		
			Cooling	kW	201.60	207.20	212.80	218.40	
				Btu/h	687,900	707,000	726,100	745,200	
				Heating	kW	226.80	233.10	239.40	245.70
					Btu/h	773,900	795,400	816,900	838,400
Power	Power Input (Nominal)	Cooling 1)	kW	53.75	55.95	55.70	57.90		
		Heating 2)	kW	58.30	60.30	63.40	65.40		
	Current Input (Nominal)	Cooling 1)	A	84.91	88.36	87.39	90.84		
		Heating 2)	A	92.06	95.20	99.46	102.60		
	MCA	A	179.90	183.20	188.10	191.40			
MFA	A	200.00	200.00	200.00	200.00				
COP	EER (Nominal Cooling)		-	3.75	3.70	3.82	3.77		
	COP (Nominal Heating)		-	3.89	3.87	3.78	3.76		
	Energy Grade		-	ESEER 6.33	ESEER 6.26	ESEER 6.33	ESEER 6.26		
Compressor	Type		-	SSC Scroll x 6	SSC Scroll x 6	SSC Scroll x 6	SSC Scroll x 6		
	Output		kW x n	(6.39x2) + (6.39x2) + (6.76x2)	(6.39x2) + (6.76x2)x2	(6.39x2) + (6.76x2)x2	(6.76x2)x3		
	Model Name		-	DS-GB066FAVBx2 + DS-GB066FAVBSGx2 + DS-GB070FAVASGx2	DS-GB066FAVBx2 + DS-GB070FAVASGx4	DS-GB066FAVBSGx2 + DS-GB070FAVASGx4	DS-GB070FAVASGx6		
	Oil	Type	-	PVE	PVE	PVE	PVE		
	Type		-	Propeller	Propeller	Propeller	Propeller		
Fan	Output x n		W	(620.0x2)x3	(620.0x2)x3	(620.0x2)x3	(620.0x2)x3		
	Air Flow Rate		CMM	290.0 + 310.0x2	290.0 + 310.0x2	310.0x3	310.0x3		
			l/s	4,833.3 + 5,166.7x2	4,833.3 + 5,166.7x2	5,166.7x3	5,166.7x3		
	External Static	Max.	mmAQ	8.00	8.00	8.00	8.00		
			Pa	78.40	78.40	78.40	78.40		
Piping Connections	Liquid Pipe		Ø, mm	22.22	22.22	22.22	22.22		
			Ø, inch	7/8"	7/8"	7/8"	7/8"		
	Gas Pipe		Ø, mm	53.98	53.98	53.98	53.98		
			Ø, inch	2 1/8"	2 1/8"	2 1/8"	2 1/8"		
	Discharge Gas Pipe		Ø, mm	-	-	-	-		
			Ø, inch	-	-	-	-		
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)	200 (220)		
Max. Height		m	110 (40)	110 (40)	110 (40)	110 (40)			
Field Wiring	Power Source Wire		mm ²	-	-	-	-		
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50		
Refrigerant	Type		-	R410A	R410A	R410A	R410A		
	Factory Charging		kg	37.00	37.00	42.90	42.90		
Sound	Pressure		dBA	71.00	71.00	72.00	72.00		
	Power			95.00	95.00	96.00	96.00		
External Dimension	Net Weight		kg	307.0 + 360.0x2	307.0 + 360.0x2	360.0x3	360.0x3		
	Shipping Weight		kg	326.0 + 375.0x2	326.0 + 375.0x2	375.0x3	375.0x3		
	Net Dimensions (WxHxD)		mm	(1,295x1,695x765)x3	(1,295x1,695x765)x3	(1,295x1,695x765)x3	(1,295x1,695x765)x3		
	Shipping Dimensions (WxHxD)		mm	(1,363x1,887x832)x3	(1,363x1,887x832)x3	(1,363x1,887x832)x3	(1,363x1,887x832)x3		
Operating Temp.	Cooling		°C	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0	-5.0 ~ 48.0		
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0		

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/R - High EER type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	
Model Name			AM080JXVHGR/EU	AM100JXVHGR/EU	AM120JXVHGR/EU	AM140JXVHGR/EU	
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50	
Mode			-	HR	HR	HR	
Performance	HP	HP	8.00	10.00	12.00	14.00	
		Capacity (Nominal)	Cooling	kW	22.40	28.00	33.60
	Heating		Btu/h	76,400	95,500	114,600	
	MCA	MFA	kW	25.20	31.50	37.80	45.00
Btu/h			86,000	107,500	129,000	153,500	
Power	Power Input (Nominal)	Cooling 1)	kW	4.59	6.22	7.57	10.55
		Heating 2)	kW	4.59	5.89	7.56	9.72
	Current Input (Nominal)	Cooling 1)	A	7.40	10.00	12.10	16.90
		Heating 2)	A	7.40	9.40	12.10	15.60
MCA	A	22.50	29.90	31.30	31.30		
MFA	A	30.00	40.00	40.00	40.00		
COP	EER (Nominal Cooling)		-	4.88	4.50	4.44	3.79
	COP (Nominal Heating)		-	5.49	5.35	5.00	4.63
	Energy Grade		-	ESEER 8.00	ESEER 7.43	ESEER 7.23	ESEER 7.12
Compressor	Type		-	SSC Scroll x 1	SSC Scroll x 1	SSC Scroll x 1	SSC Scroll x 1
	Output		kW x n	(5.18)	(6.39)	(6.39)	(6.39)
	Model Name		-	DS-GB052FAVBSGx1	DS-GB066FAVBSGx1	DS-GB066FAVBSGx1	DS-GB066FAVBSGx1
	Oil	Type	-	PVE	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller	Propeller
	Output x n		W	830.0	830.0	830.0	620.0x2
	Air Flow Rate		CMM	170	170	220	255
			l/s	2,833.33	2,833.33	3,666.67	4,250.00
External Static	Max.	mmAQ	8.00	8.00	8.00	8.00	
		Pa	78.40	78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	9.52	9.52	12.70	12.70
			Ø, inch	3/8"	3/8"	1/2"	1/2"
	Gas Pipe		Ø, mm	19.05	22.22	28.58	28.58
			Ø, inch	3/4"	7/8"	1 1/8"	1 1/8"
	Discharge Gas Pipe		Ø, mm	15.88	19.05	19.05	22.22
			Ø, inch	5/8"	3/4"	3/4"	7/8"
Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)	200 (220)	
	Max. Height	m	110 (40)	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A	R410A
	Factory Charging		kg	6.50	6.50	6.50	7.70
Sound	Pressure		dBA	57.00	58.00	62.00	61.00
	Power			77.00	79.00	81.00	81.00
External Dimension	Net Weight		kg	206.0	206.0	206.0	241.0
	Shipping Weight		kg	222.0	222.0	222.0	260.0
	Net Dimensions (WxHxD)		mm	880x1,695x765	880x1,695x765	880x1,695x765	1,295x1,695x765
	Shipping Dimensions (WxHxD)		mm	948x1,887x832	948x1,887x832	948x1,887x832	1,363x1,887x832
Operating Temp.	Cooling		°C	-15.0 ~ 48.0	-15.0 ~ 48.0	-15.0 ~ 48.0	-15.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/R - High EER type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	
Model Name			AM160JXVHGR/EU	AM180JXVHGR/EU	AM200JXVHGR/EU	AM220JXVHGR/EU	
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50	
Mode			-	HR	HR	HR	
Performance	HP	HP	16.00	18.00	20.00	22.00	
		Capacity (Nominal)	kW	45.00	50.40	56.00	61.60
	Cooling	Btu/h	153,500	172,000	191,100	210,200	
		Heating	kW	50.40	56.70	63.00	69.30
Power	Power Input (Nominal)	Cooling 1)	kW	10.92	11.51	13.05	15.75
		Heating 2)	kW	10.75	11.62	13.10	15.86
	Current Input (Nominal)	Cooling 1)	A	17.50	18.50	20.90	25.30
		Heating 2)	A	17.20	18.60	21.00	25.40
MCA	A	40.00	48.90	52.50	55.60		
MFA	A	40.00	50.00	75.00	75.00		
COP	EER (Nominal Cooling)		-	4.12	4.38	4.29	3.91
	COP (Nominal Heating)		-	4.69	4.88	4.81	4.37
	Energy Grade		-	ESEER 6.82	ESEER 6.71	ESEER 6.66	ESEER 6.32
Compressor	Type		-	SSC Scroll x 2	SSC Scroll x 2	SSC Scroll x 2	SSC Scroll x 2
	Output		kW x n	(4.39 x 2)	(6.39 x 2)	(6.39 x 2)	(6.39 x 2)
	Model Name		-	DS-GA046FAVASGx2	DS-GB066FAVBSGx2	DS-GB066FAVBSGx2	DS-GB066FAVBSGx2
	Oil	Type	-	PVE	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller	Propeller
	Output x n		W	620.0x2	620.0x2	620.0x2	620.0x2
	Air Flow Rate		CMM	255	290	290	290
			l/s	4,250.00	4,833.33	4,833.33	4,833.33
External Static	Max.	mmAQ	8.00	8.00	8.00	8.00	
		Pa	78.40	78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	12.70	15.88	15.88	15.88
			Ø, inch	1/2"	5/8"	5/8"	5/8"
	Gas Pipe		Ø, mm	28.58	28.58	28.58	28.58
			Ø, inch	1 1/8"	1 1/8"	1 1/8"	1 1/8"
	Discharge Gas Pipe		Ø, mm	22.22	22.22	28.58	28.58
			Ø, inch	7/8"	7/8"	1 1/8"	1 1/8"
Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)	200 (220)	
	Max. Height	m	110 (40)	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A	R410A
	Factory Charging		kg	7.70	8.40	8.40	8.40
Sound	Pressure		dBA	62.00	63.00	64.00	65.00
	Power			82.00	85.00	86.00	88.00
External Dimension	Net Weight		kg	272.0	306.0	306.0	306.0
	Shipping Weight		kg	291.0	325.0	325.0	325.0
	Net Dimensions (WxHxD)		mm	1,295x1,695x765	1,295x1,695x765	1,295x1,695x765	1,295x1,695x765
	Shipping Dimensions (WxHxD)		mm	1,363x1,887x832	1,363x1,887x832	1,363x1,887x832	1,363x1,887x832
Operating Temp.	Cooling		°C	-15.0 ~ 48.0	-15.0 ~ 48.0	-15.0 ~ 48.0	-15.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/R - High EER type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	
Model Name			AM240JXVHGR1EU	AM260JXVHGR1EU	AM280JXVHGR1EU	AM300JXVHGR1EU	
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50	
Mode			-	HR	HR	HR	
Performance	HP	HP	24.00	26.00	28.00	30.00	
		kW	67.20	73.60	78.60	84.00	
	Capacity (Nominal)	Cooling	Btu/h	229,300	251,100	268,200	286,600
			Heating	kW	75.60	82.80	88.20
			Btu/h	258,000	282,500	301,000	
Power	Power Input (Nominal)	Cooling 1)	kW	15.14	18.12	18.49	19.08
		Heating 2)	kW	15.12	17.28	18.31	19.18
	Current Input (Nominal)	Cooling 1)	A	24.20	29.00	29.60	30.60
		Heating 2)	A	24.20	27.70	29.30	30.70
	MCA	A	60.50	63.80	71.30	80.20	
MFA	A	75.00	75.00	75.00	90.00		
COP	EER (Nominal Cooling)		-	4.44	4.06	4.25	4.40
	COP (Nominal Heating)		-	5.00	4.79	4.82	4.93
	Energy Grade		-	ESEER 7.23	ESEER 7.17	ESEER 7.00	ESEER 6.92
Compressor	Type		-	SSC Scroll x 2	SSC Scroll x 2	SSC Scroll x 3	SSC Scroll x 3
	Output		kW x n	(6.39)x2	(6.39) + (6.39)	(6.39) + (4.39x2)	(6.39) + (6.39x2)
	Model Name		-	DS-GB066FAVBSGx2	DS-GB066FAVBSGx2	DS-GB066FAVBSGx1 + DS-GA046FAVASGx2	DS-GB066FAVBSGx3
	Oil	Type	-	PVE	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller	Propeller
	Output x n		W	(830.0)x2	620.0x2 + 830.0	830.0 + 620.0x2	830.0 + 620.0x2
	Air Flow Rate		CMM	220.0x2	255.0 + 220.0	220.0 + 255.0	220.0 + 290.0
			l/s	3,666.7x2	4,250.0 + 3,666.7	3,666.7 + 4,250.0	3,666.7 + 4,833.3
	External Static	Max.	mmAQ	8.00	8.00	8.00	8.00
Pa			78.40	78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	15.88	19.05	19.05	19.05
			Ø, inch	5/8"	3/4"	3/4"	3/4"
	Gas Pipe		Ø, mm	34.92	34.92	34.92	34.92
			Ø, inch	1 3/8"	1 3/8"	1 3/8"	1 3/8"
	Discharge Gas Pipe		Ø, mm	28.58	28.58	28.58	28.58
			Ø, inch	1 1/8"	1 1/8"	1 1/8"	1 1/8"
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)	200 (220)
Max. Height		m	110 (40)	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A	R410A
	Factory Charging		kg	13.00	14.20	14.20	14.90
Sound	Pressure		dBA	65.00	65.00	65.00	66.00
	Power			84.00	84.00	85.00	86.00
External Dimension	Net Weight		kg	206.0x2	241.0 + 206.0	206.0 + 272.0	206.0 + 306.0
	Shipping Weight		kg	222.0x2	260.0 + 222.0	222.0 + 291.0	222.0 + 325.0
	Net Dimensions (WxHxD)		mm	(880x1,695x765)x2	1,295x1,695x765 + 880x1,695x765	880x1,695x765 + 1,295x1,695x765	880x1,695x765 + 1,295x1,695x765
	Shipping Dimensions (WxHxD)		mm	(948x1,887x832)x2	1,363x1,887x832 + 948x1,887x832	948x1,887x832 + 1,363x1,887x832	948x1,887x832 + 1,363x1,887x832
Operating Temp.	Cooling		°C	-15.0 ~ 48.0	-15.0 ~ 48.0	-15.0 ~ 48.0	-15.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/R - High EER type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	
Model Name			AM320JXVHGR1EU	AM340JXVHGR1EU	AM360JXVHGR1EU	AM380JXVHGR1EU	
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50	
Mode			-	HR	HR	HR	
Performance	HP	HP	32.00	34.00	36.00	38.00	
		kW	89.60	95.20	101.60	106.60	
	Capacity (Nominal)	Cooling	Btu/h	305,700	324,800	346,700	363,700
			kW	100.80	107.10	114.30	119.70
		Heating	Btu/h	343,900	365,400	390,000	408,400
Power	Power Input (Nominal)	Cooling 1)	kW	20.62	23.32	26.30	26.67
		Heating 2)	kW	20.66	23.42	25.58	26.61
	Current Input (Nominal)	Cooling 1)	A	33.00	37.40	42.20	42.80
		Heating 2)	A	33.10	37.50	41.00	42.60
	MCA	A	83.80	86.90	86.90	95.60	
MFA	A	90.00	90.00	90.00	100.00		
COP	EER (Nominal Cooling)		-	4.35	4.08	3.86	4.00
	COP (Nominal Heating)		-	4.88	4.57	4.47	4.50
	Energy Grade		-	ESEER 6.87	ESEER 6.64	ESEER 6.63	ESEER 6.53
Compressor	Type		-	SSC Scroll x 3	SSC Scroll x 3	SSC Scroll x 3	SSC Scroll x 4
	Output		kW x n	(6.39) + (6.39x2)	(6.39) + (6.39x2)	(6.39) + (6.39x2)	(4.39x2) + (6.39x2)
	Model Name		-	DS-GB066FAVBSGx3	DS-GB066FAVBSGx3	DS-GB066FAVBSGx3	DS-GA046FAVASGx2 + DS-GB066FAVBSGx2
	Oil	Type	-	PVE	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller	Propeller
	Output x n		W	830.0 + 620.0x2	830.0 + 620.0x2	(620.0x2)x2	(620.0x2)x2
	Air Flow Rate		CMM	220.0 + 290.0	220.0 + 290.0	255.0 + 290.0	255.0 + 290.0
			l/s	3,666.7 + 4,833.3	3,666.7 + 4,833.3	4,250.0 + 4,833.3	4,250.0 + 4,833.3
	External Static	Max.	mmAQ	8.00	8.00	8.00	8.00
Pa			78.40	78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	19.05	19.05	19.05	19.05
			Ø, inch	3/4"	3/4"	3/4"	3/4"
	Gas Pipe		Ø, mm	34.92	34.92	41.28	41.28
			Ø, inch	1 3/8"	1 3/8"	1 5/8"	1 5/8"
	Discharge Gas Pipe		Ø, mm	28.58	28.58	34.92	34.92
			Ø, inch	1 1/8"	1 1/8"	1 3/8"	1 3/8"
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)	200 (220)
Max. Height		m	110 (40)	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A	R410A
	Factory Charging		kg	14.90	14.90	16.10	16.10
Sound	Pressure		dBA	66.00	67.00	66.00	67.00
	Power			87.00	89.00	89.00	89.00
External Dimension	Net Weight		kg	206.0 + 306.0	206.0 + 306.0	241.0 + 306.0	272.0 + 306.0
	Shipping Weight		kg	222.0 + 325.0	222.0 + 325.0	260.0 + 325.0	291.0 + 325.0
	Net Dimensions (WxHxD)		mm	880x1,695x765 + 1,295x1,695x765	880x1,695x765 + 1,295x1,695x765	(1,295x1,695x765)x2	(1,295x1,695x765)x2
	Shipping Dimensions (WxHxD)		mm	948x1,887x832 + 1,363x1,887x832	948x1,887x832 + 1,363x1,887x832	(1,363x1,887x832)x2	(1,363x1,887x832)x2
Operating Temp.	Cooling		°C	-15.0 ~ 48.0	-15.0 ~ 48.0	-15.0 ~ 48.0	-15.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/R - High EER type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)
Model Name			AM400JXVHGR1EU	AM420JXVHGR1EU	AM440JXVHGR1EU	AM460JXVHGR1EU
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50
Mode			-	HR	HR	HR
Performance	HP	HP	40.00	42.00	44.00	46.00
		Capacity (Nominal)	Cooling	kW	112.00	117.60
	Btu/h			382,200	401,300	420,400
	Heating		kW	126.00	132.30	138.60
			Btu/h	429,900	451,400	472,900
Power	Power Input (Nominal)	Cooling 1)	kW	26.10	28.80	31.50
		Heating 2)	kW	26.20	28.96	31.72
	Current Input (Nominal)	Cooling 1)	A	41.80	46.20	50.60
		Heating 2)	A	42.00	46.40	50.80
	MCA	A	95.10	108.10	111.20	
MFA	A	100.00	125.00	125.00		
COP	EER (Nominal Cooling)		-	4.29	4.08	3.91
	COP (Nominal Heating)		-	4.81	4.57	4.37
	Energy Grade		-	ESEER 6.66	ESEER 6.48	ESEER 6.32
Compressor	Type		-	SSC Scroll x 4	SSC Scroll x 4	SSC Scroll x 4
	Output		kW x n	(6.39x2)x2	(6.39x2) + (6.39x2)	(6.39x2)x2
	Model Name		-	DS-GB066FAVBSGx4	DS-GB066FAVBSGx4	DS-GB066FAVBSGx4
	Oil	Type	-	PVE	PVE	PVE
				-	-	-
Fan	Type		-	Propeller	Propeller	Propeller
	Output x n		W	(620.0x2)x2	(620.0x2)x2	(620.0x2)x2
	Air Flow Rate		CMM	290.0x2	290.0x2	290.0x2
			l/s	4,833.3x2	4,833.3x2	4,833.3x2
	External Static	Max.	mmAQ	8.00	8.00	8.00
Pa			78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	19.05	19.05	19.05
			Ø, inch	3/4"	3/4"	3/4"
	Gas Pipe		Ø, mm	41.28	41.28	41.28
			Ø, inch	1 5/8"	1 5/8"	1 5/8"
	Discharge Gas Pipe		Ø, mm	34.92	34.92	34.92
			Ø, inch	1 3/8"	1 3/8"	1 3/8"
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)
Max. Height		m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A
	Factory Charging		kg	16.80	16.80	21.40
Sound	Pressure		dBA	67.00	68.00	68.00
	Power			89.00	90.00	91.00
External Dimension	Net Weight		kg	306.0x2	306.0x2	206.0x2 + 306.0
	Shipping Weight		kg	325.0x2	325.0x2	222.0x2 + 325.0
	Net Dimensions (WxHxD)		mm	(1,295x1,695x765)x2	(1,295x1,695x765)x2	(1,295x1,695x765)x2 + (880x1,695x765)x2 + 1,295x1,695x765
	Shipping Dimensions (WxHxD)		mm	(1,363x1,887x832)x2	(1,363x1,887x832)x2	(1,363x1,887x832)x2 + (948x1,887x832)x2 + 1,363x1,887x832
Operating Temp.	Cooling		°C	-15.0 ~ 48.0	-15.0 ~ 48.0	-15.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/R - High EER type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)
Model Name			AM480JXVHGR1EU	AM500JXVHGR1EU	AM520JXVHGR1EU	AM540JXVHGR1EU
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50
Mode			-	HR	HR	HR
Performance	HP	HP	48.00	50.00	52.00	54.00
		Capacity (Nominal)	Cooling	kW	135.20	140.20
	Btu/h			461,300	478,400	496,800
	Heating		kW	152.10	157.50	163.80
			Btu/h	519,000	537,400	558,900
Power	Power Input (Nominal)	Cooling 1)	kW	33.87	34.24	34.83
		Heating 2)	kW	33.14	34.17	35.04
	Current Input (Nominal)	Cooling 1)	A	54.30	54.90	55.90
		Heating 2)	A	53.10	54.70	56.10
	MCA	A	118.20	126.90	135.80	
MFA	A	125.00	150.00	150.00		
COP	EER (Nominal Cooling)		-	3.99	4.09	4.18
	COP (Nominal Heating)		-	4.59	4.61	4.67
	Energy Grade		-	ESEER 6.78	ESEER 6.70	ESEER 6.66
Compressor	Type		-	SSC Scroll x 4	SSC Scroll x 5	SSC Scroll x 5
	Output		kW x n	(6.39) + (6.39) + (6.39x2)	(6.39) + (4.39x2) + (6.39x2)	(6.39) + (6.39x2) + (6.39x2)
	Model Name		-	DS-GB066FAVBSGx4	DS-GB066FAVBSGx3 + DS-GA046FAVASGx2	DS-GB066FAVBSGx5
	Oil	Type	-	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller
	Output x n		W	(620.0x2)x2 + 830.0	830.0 + (620.0x2)x2	830.0 + (620.0x2)x2
	Air Flow Rate		CMM	255.0 + 220.0 + 290.0	220.0 + 255.0 + 290.0	220.0 + 290.0x2
			l/s	4,250.0 + 3,666.7 + 4,833.3	3,666.7 + 4,250.0 + 4,833.3	3,666.7 + 4,833.3x2
	External Static	Max.	mmAQ	8.00	8.00	8.00
Pa			78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	19.05	19.05	19.05
			Ø, inch	3/4"	3/4"	3/4"
	Gas Pipe		Ø, mm	41.28	41.28	41.28
			Ø, inch	1 5/8"	1 5/8"	1 5/8"
	Discharge Gas Pipe		Ø, mm	34.92	34.92	34.92
			Ø, inch	1 3/8"	1 3/8"	1 3/8"
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)
Max. Height		m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A
	Factory Charging		kg	22.60	22.60	23.30
Sound	Pressure		dBA	68.00	68.00	68.00
	Power			89.00	90.00	91.00
External Dimension	Net Weight		kg	241.0 + 206.0 + 306.0	206.0 + 272.0 + 306.0	206.0 + 306.0x2
	Shipping Weight		kg	260.0 + 222.0 + 325.0	222.0 + 291.0 + 325.0	222.0 + 325.0x2
	Net Dimensions (WxHxD)		mm	(1,295x1,695x765)x2 + 880x1,695x765	880x1,695x765 + (1,295x1,695x765)x2	880x1,695x765 + (1,295x1,695x765)x2
	Shipping Dimensions (WxHxD)		mm	(1,363x1,887x832)x2 + 948x1,887x832	948x1,887x832 + (1,363x1,887x832)x2	948x1,887x832 + (1,363x1,887x832)x2
Operating Temp.	Cooling		°C	-15.0 ~ 48.0	-15.0 ~ 48.0	-15.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/R - High EER type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)
Model Name			AM560JXVHGR1EU	AM580JXVHGR1EU	AM600JXVHGR1EU	AM620JXVHGR1EU
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50
Mode			-	HR	HR	HR
Performance	HP	HP	56.00	58.00	60.00	62.00
		Capacity (Nominal)	Cooling	kW	156.80	163.20
	Btu/h			535,000	556,900	573,900
	Heating		kW	176.40	183.60	189.00
			Btu/h	601,900	626,500	644,900
Power	Power Input (Nominal)	Cooling 1)	kW	39.07	42.05	42.42
		Heating 2)	kW	39.28	41.44	42.47
	Current Input (Nominal)	Cooling 1)	A	62.70	67.50	68.10
		Heating 2)	A	62.90	66.40	68.00
	MCA	A	142.50	142.50	151.20	
MFA	A	150.00	150.00	200.00		
COP	EER (Nominal Cooling)		-	4.01	3.88	3.97
	COP (Nominal Heating)		-	4.49	4.43	4.45
	Energy Grade		-	ESEER 6.52	ESEER 6.52	ESEER 6.45
Compressor	Type		-	SSC Scroll x 5	SSC Scroll x 5	SSC Scroll x 6
	Output		kW x n	(6.39) + (6.39x2)x2	(6.39) + (6.39x2)x2	(4.39x2) + (6.39x2)x2
	Model Name		-	DS-GB066FAVBSGx5	DS-GB066FAVBSGx5	DS-GA046FAVASGx2 + DS-GB066FAVBSGx4
	Oil	Type	-	PVE	PVE	PVE
	Type		-	Propeller	Propeller	Propeller
Fan	Output x n		W	830.0 + (620.0x2)x2	(620.0x2)x3	(620.0x2)x3
	Air Flow Rate		CMM	220.0 + 290.0x2	255.0 + 290.0x2	255.0 + 290.0x2
			l/s	3,666.7 + 4,833.3x2	4,250.0 + 4,833.3x2	4,250.0 + 4,833.3x2
	External Static	Max.	mmAQ	8.00	8.00	8.00
			Pa	78.40	78.40	78.40
Piping Connections	Liquid Pipe		Ø, mm	19.05	19.05	22.22
			Ø, inch	3/4"	3/4"	7/8"
	Gas Pipe		Ø, mm	41.28	41.28	41.28
			Ø, inch	1 5/8"	1 5/8"	2 1/8"
	Discharge Gas Pipe		Ø, mm	34.92	34.92	41.28
			Ø, inch	1 3/8"	1 3/8"	1 5/8"
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)
Max. Height		m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A
	Factory Charging		kg	23.30	24.50	25.20
Sound	Pressure		dBA	69.00	69.00	69.00
	Power		dBA	91.00	91.00	92.00
External Dimension	Net Weight		kg	206.0 + 306.0x2	241.0 + 306.0x2	272.0 + 306.0x2
	Shipping Weight		kg	222.0 + 325.0x2	260.0 + 325.0x2	291.0 + 325.0x2
	Net Dimensions (WxHxD)		mm	880x1,695x765 + (1,295x1,695x765)x2	(1,295x1,695x765)x3	(1,295x1,695x765)x3
	Shipping Dimensions (WxHxD)		mm	948x1,887x832 + (1,363x1,887x832)x2	(1,363x1,887x832)x3	(1,363x1,887x832)x3
Operating Temp.	Cooling		°C	-15.0 ~ 48.0	-15.0 ~ 48.0	-15.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/R - High EER type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)
Model Name			AM640JXVHGR1EU	AM660JXVHGR1EU	AM680JXVHGR1EU	AM700JXVHGR1EU
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50
Mode			-	HR	HR	HR
Performance	HP		HP	64.00	66.00	68.00
		Capacity (Nominal)	Cooling	kW	179.20	184.80
	Btu/h			611,500	630,600	649,700
	Heating		kW	201.60	207.90	214.20
			Btu/h	687,900	709,400	730,900
Power	Power Input (Nominal)	Cooling 1)	kW	44.55	47.25	46.64
		Heating 2)	kW	44.82	47.58	46.84
	Current Input (Nominal)	Cooling 1)	A	71.50	75.90	74.80
		Heating 2)	A	71.80	76.20	75.00
	MCA	A	163.70	166.80	173.80	
MFA	A	200.00	200.00	200.00		
COP	EER (Nominal Cooling)		-	4.02	3.91	4.08
	COP (Nominal Heating)		-	4.50	4.37	4.57
	Energy Grade		-	ESEER 6.43	ESEER 6.32	ESEER 6.64
Compressor	Type		-	SSC Scroll x 6	SSC Scroll x 6	SSC Scroll x 6
	Output		kW x n	(6.39x2) + (6.39x2)x2	(6.39x2)x3	(6.39)x2 + (6.39x2)x2
	Model Name		-	DS-GB066FAVBSGx6	DS-GB066FAVBSGx6	DS-GB066FAVBSGx6
	Oil	Type	-	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller
	Output x n		W	(620.0x2)x3	(620.0x2)x3	(830.0)x2 + (620.0x2)x2
	Air Flow Rate		CMM	290.0x3	290.0x3	220.0x2 + 290.0x2
			l/s	4,833.3x3	4,833.3x3	3,666.7x2 + 4,833.3x2
	External Static	Max.	mmAQ	8.00	8.00	8.00
Pa			78.40	78.40	78.40	
Piping Connections	Liquid Pipe		Ø, mm	22.22	22.22	22.22
			Ø, inch	7/8"	7/8"	7/8"
	Gas Pipe		Ø, mm	53.98	53.98	53.98
			Ø, inch	2 1/8"	2 1/8"	2 1/8"
	Discharge Gas Pipe		Ø, mm	41.28	41.28	41.28
			Ø, inch	1 5/8"	1 5/8"	1 5/8"
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)
Max. Height		m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A
	Factory Charging		kg	25.20	25.20	29.80
Sound	Pressure		dBA	69.00	70.00	70.00
	Power			92.00	92.00	92.00
External Dimension	Net Weight		kg	306.0x3	306.0x3	206.0x2 + 306.0x2
	Shipping Weight		kg	325.0x3	325.0x3	222.0x2 + 325.0x2
	Net Dimensions (WxHxD)		mm	(1,295x1,695x765)x3	(1,295x1,695x765)x3	(880x1,695x765)x2 + (1,295x1,695x765)x2
	Shipping Dimensions (WxHxD)		mm	(1,363x1,887x832)x3	(1,363x1,887x832)x3	(948x1,887x832)x2 + (1,363x1,887x832)x2
Operating Temp.	Cooling		°C	-15.0 ~ 48.0	-15.0 ~ 48.0	-15.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/R - High EER type

Outdoor

Type			DVM S(NEW)	DVM S(NEW)	DVM S(NEW)	DVM S(NEW)
Model Name			AM720JXVHGR1EU	AM740JXVHGR1EU	AM760JXVHGR1EU	AM780JXVHGR1EU
Power Supply			Ø, #, V, Hz	3,4,380-415,50	3,4,380-415,50	3,4,380-415,50
Mode			-	HR	HR	HR
Performance	HP	HP	72.00	74.00	76.00	78.00
		Capacity (Nominal)	Cooling	kW	201.80	207.20
	Heating		Btu/h	688,600	707,000	726,100
	Capacity (Nominal)	Heating	kW	226.80	233.10	239.40
Btu/h			773,900	795,400	816,900	
Power	Power Input (Nominal)	Cooling 1)	kW	49.99	50.58	52.12
		Heating 2)	kW	50.03	50.90	52.38
	Current Input (Nominal)	Cooling 1)	A	80.20	81.20	83.60
		Heating 2)	A	80.10	81.50	83.90
	MCA	A	182.50	191.40	195.00	
MFA	A	200.00	200.00	200.00		
COP	EER (Nominal Cooling)		-	4.04	4.10	4.08
	COP (Nominal Heating)		-	4.53	4.58	4.57
	Energy Grade		-	ESEER 6.58	ESEER 6.56	ESEER 6.55
Compressor	Type		-	SSC Scroll x 7	SSC Scroll x 7	SSC Scroll x 7
	Output		kW x n	(6.39) + (4.39x2) + (6.39x2)x2	(6.39) + (6.39x2) + (6.39x2)x2	(6.39) + (6.39x2) + (6.39x2)x2
	Model Name		-	DS-GB066FAVBSGx5 + DS-GA046FAVASGx2	DS-GB066FAVBSGx7	DS-GB066FAVBSGx7
	Oil	Type	-	PVE	PVE	PVE
Fan	Type		-	Propeller	Propeller	Propeller
	Output x n		W	830.0 + (620.0x2)x3	830.0 + (620.0x2)x3	830.0 + (620.0x2)x3
	Air Flow Rate		CMM	220.0 + 255.0 + 290.0x2	220.0 + 290.0x3	220.0 + 290.0x3
			l/s	3,666.7 + 4,250.0 + 4,833.3x2	3,666.7 + 4,833.3x3	3,666.7 + 4,833.3x3
External Static	Max.	mmAQ	8.00	8.00	8.00	
Piping Connections	Liquid Pipe		Ø, mm	22.22	22.22	22.22
			Ø, inch	7/8"	7/8"	7/8"
	Gas Pipe		Ø, mm	53.98	53.98	53.98
			Ø, inch	2 1/8"	2 1/8"	2 1/8"
	Discharge Gas Pipe		Ø, mm	41.28	41.28	41.28
			Ø, inch	1 5/8"	1 5/8"	1 5/8"
	Installation Limitation	Max. Length	m	200 (220)	200 (220)	200 (220)
Max. Height		m	110 (40)	110 (40)	110 (40)	
Field Wiring	Power Source Wire		mm ²	-	-	-
	Transmission Cable		mm ²	0.75 ~ 1.50	0.75 ~ 1.50	0.75 ~ 1.50
Refrigerant	Type		-	R410A	R410A	R410A
	Factory Charging		kg	31.00	31.70	31.70
Sound	Pressure		dBA	70.00	70.00	70.00
	Power		dBA	92.00	92.00	93.00
External Dimension	Net Weight		kg	206.0 + 272.0 + 306.0x2	206.0 + 306.0x3	206.0 + 306.0x3
	Shipping Weight		kg	222.0 + 291.0 + 325.0x2	222.0 + 325.0x3	222.0 + 325.0x3
	Net Dimensions (WxHxD)		mm	880x1,695x765 + (1,295x1,695x765)x3	880x1,695x765 + (1,295x1,695x765)x3	880x1,695x765 + (1,295x1,695x765)x3
	Shipping Dimensions (WxHxD)		mm	948x1,887x832 + (1,363x1,887x832)x3	948x1,887x832 + (1,363x1,887x832)x3	948x1,887x832 + (1,363x1,887x832)x3
Operating Temp.	Cooling		°C	-15.0 ~ 48.0	-15.0 ~ 48.0	-15.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0	-25.0 ~ 24.0	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.

5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)

*PDM kit: Pressure Drop Modulation kit

2 Specifications : H/R - High EER type

Outdoor

Type			DVM S(NEW)	
Model Name			AM800JXVHGR1EU	
Power Supply		Ø, #, V, Hz	3,4,380-415,50	
Mode			HR	
Performance	HP	HP	80.00	
	Capacity (Nominal)	Cooling	kW	224.80
			Btu/h	767,000
		Heating	kW	252.90
			Btu/h	862,900
Power	Power Input (Nominal)	Cooling 1)	kW	57.80
		Heating 2)	kW	57.30
	Current Input (Nominal)	Cooling 1)	A	92.80
		Heating 2)	A	91.80
	MCA	A	198.10	
	MFA	A	200.00	
COP	EER (Nominal Cooling)		-	3.89
	COP (Nominal Heating)		-	4.41
	Energy Grade		-	ESEER 6.46
			-	-
Compressor	Type		-	SSC Scroll x 7
	Output		kW x n	(6.39) + (6.39x2)x3
	Model Name		-	DS-GB066FAVBSGx7
	Oil	Type	-	PVE
Fan	Type		-	Propeller
	Output x n		W	(620.0x2)x4
	Air Flow Rate		CMM	255.0 + 290.0x3
			l/s	4,250.0 + 4,833.3x3
	External Static	Max.	mmAQ	8.00
Pa			78.40	
Piping Connections	Liquid Pipe		Ø, mm	22.22
			Ø, inch	7/8"
	Gas Pipe		Ø, mm	53.98
			Ø, inch	2 1/8"
	Discharge Gas Pipe		Ø, mm	41.28
			Ø, inch	1 5/8"
	Installation Limitation	Max. Length	m	200 (220)
		Max. Height	m	110 (40)
Field Wiring	Power Source Wire		mm ²	-
	Transmission Cable		mm ²	0.75 ~ 1.50
Refrigerant	Type		-	R410A
	Factory Charging		kg	32.90
Sound	Pressure		dBA	70.00
	Power			93.00
External Dimension	Net Weight		kg	241.0 + 306.0x3
	Shipping Weight		kg	260.0 + 325.0x3
	Net Dimensions (WxHxD)		mm	(1,295x1,695x765)x4
	Shipping Dimensions (WxHxD)		mm	(1,363x1,887x832)x4
Operating Temp.	Cooling		°C	-15.0 ~ 48.0
	Heating		°C	-25.0 ~ 24.0

* Specifications may be subject to change without prior notice.

1) Nominal cooling capacities are based on;

- Indoor temperature : 27°C DB, 19°C WB

- Outdoor temperature : 35°C DB, 24°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

2) Nominal heating capacities are based on;

- Indoor temperature : 20°C DB, 15°C WB

- Outdoor temperature : 7°C DB, 6°C WB, Equivalent refrigerant piping : 7.5m, Level differences : 0m

3) Sound pressure was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.

4) These products contain R410A which is fluorinated greenhouse gas.


5) If outdoor unit is located in a higher position than indoor unit, level difference is 110m or under.

(If the level difference is higher than 50m, make a decision by PDM kit installation Guide software whether the PDM kit should be installed or not.)


*PDM kit: Pressure Drop Modulation kit

3 Operation limit

Cooling



Heating




Defrosting correction factor

On heating operation, frost can be formed on heat exchanger according to outdoor temperature. (Frost on heat exchanger results in decreasing the performance.)
 To remove frost on heat exchanger of outdoor unit, defrost operation is carried out periodically.
 During defrost operation, capacity of outdoor unit may decrease.
 The decrement is not considered to the individual capacity tables.

Outdoor temperature (°C, DB)	-10	-8	-6	-4	-2	0	2	5	7
Capacity coefficient	0.99	0.98	0.96	0.95	0.91	0.88	0.86	0.91	1.00

$$\text{Corrected Heating Capacity} = \text{Heating Capacity} \times \text{Capacity Coefficient}$$



4 Dimensional drawing

Heat Pump - High EER type

AM080JXVHGH/EU, AM100JXVHGH/EU, AM120JXVHGH/EU

Units : mm / inches




Table of descriptions

1	Refrigerant gas pipe	7	Knock-out Hole for Ref. Piping
2	Refrigerant liquid pipe	8	Anchor Bolt Hole
3	Power wiring conduit	9	
4	Communication wiring conduit	10	
5	Power wiring conduit	11	
6	Communication wiring conduit	12	

4 Dimensional drawing

Heat Pump - High EER type

AM140JXVHGH/EU, AM160JXVHGH/EU, AM180JXVHGH/EU, AM200JXVHGH/EU, AM220JXVHGH/EU, AM240HXVAGH/EU, AM260HXVAGH/EU

Units : mm / inches




Table of descriptions

1	Gas Ref. pipe	7	Knock-out Hole for Ref. Piping
2	Liquid Ref. pipe	8	Anchor Bolt Hole
3	Power wiring conduit	9	
4	Communication wiring conduit	10	
5	Power wiring conduit	11	
6	Communication wiring conduit	12	

4 Dimensional drawing

Heat Pump - Standard type

AM080JXVAGH/EU, AM100JXVAGH/EU, AM120JXVAGH/EU

Units : mm / inches




Table of descriptions

1	Refrigerant gas pipe	7	Knock-out Hole for Ref. Piping
2	Refrigerant liquid pipe	8	Anchor Bolt Hole
3	Power wiring conduit	9	
4	Communication wiring conduit	10	
5	Power wiring conduit	11	
6	Communication wiring conduit	12	

4 Dimensional drawing

Heat Pump - Standard type

AM140JXVAGH/EU, AM160JXVAGH/EU, AM180JXVAGH/EU, AM200JXVAGH/EU, AM220JXVAGH/EU

Units : mm / inches




Table of descriptions

1	Gas Ref. pipe	7	Knock-out Hole for Ref. Piping
2	Liquid Ref. pipe	8	Anchor Bolt Hole
3	Power wiring conduit	9	
4	Communication wiring conduit	10	
5	Power wiring conduit	11	
6	Communication wiring conduit	12	

4 Dimensional drawing

Heat Recovery - High EER type

AM080JXVHGR/EU, AM100JXVHGR/EU, AM120JXVHGR/EU

Units : mm / inches




Table of descriptions

1	Low pressure gas pipe	7	Knock-out Hole for Ref. Piping
2	High pressure gas pipe	8	Anchor Bolt Hole
3	Liquid pipe	9	Power wiring conduit
4	Communication wiring conduit	10	
5	Power wiring conduit	11	
6	Communication wiring conduit	12	

4 Dimensional drawing

Heat Recovery - High EER type

AM140JXVHGR/EU, AM160JXVHGR/EU, AM180JXVHGR/EU, AM200JXVHGR/EU, AM220JXVHGR/EU

Units : mm / inches





Table of descriptions

1	Low Pressure Gas Ref. pipe	7	Knock-out Hole for Ref. Piping
2	High Pressure Gas Ref. pipe	8	Anchor Bolt Hole
3	Liquid Ref. pipe	9	Power wiring conduit
4	Communication wiring conduit	10	
5	Power wiring conduit	11	
6	Communication wiring conduit	12	

5 Electrical wiring diagram

Outdoor


AM080~220JXVAGH/EU



5 Electrical wiring diagram


Outdoor

AM080~220JXVHGH/EU, AM240~260HXVAGH/EU, AM080~220JXVHGR/EU



6 Sound pressure level

Heat Pump - High EER type



Unit: dB(A)

Model	Pressure
AM080JXVHGH/EU	57.0
AM100JXVHGH/EU	58.0
AM120JXVHGH/EU	62.0
AM140JXVHGH/EU	61.0

Note


Measuring place: Anechoic chamber (conversion value)

These operation values were obtained in an anechoic room. Sound pressure level will vary depending on a factors such as the construction of the particular room where the equipment is installed.


Operation sound level may differ depending on operation and ambient conditions.

NC curve


1) AM080JXVHGH/EU




2) AM100JXVHGH/EU



3) AM120JXVHGH/EU




4) AM140JXVHGH/EU



6 Sound pressure level

Heat Pump - High EER type



Unit: dB(A)

Model	Pressure
AM160JXVHGH/EU	62.0
AM180JXVHGH/EU	63.0
AM200JXVHGH/EU	64.0
AM220JXVHGH/EU	65.0

Note


Measuring place: Anechoic chamber (conversion value)

These operation values were obtained in an anechoic room. Sound pressure level will vary depending on a factors such as the construction of the particular room where the equipment is installed.


Operation sound level may differ depending on operation and ambient conditions.

NC curve


1) AM160JXVHGH/EU




2) AM180JXVHGH/EU



3) AM200JXVHGH/EU




4) AM220JXVHGH/EU



6 Sound pressure level

Heat Pump - High EER type



Unit: dB(A)

Model	Pressure
AM240HXVAGH/EU	67.0
AM260HXVAGH/EU	67.0

Note


Measuring place: Anechoic chamber (conversion value)

These operation values were obtained in an anechoic room. Sound pressure level will vary depending on a factors such as the construction of the particular room where the equipment is installed.


Operation sound level may differ depending on operation and ambient conditions.

NC curve

1) AM240HXVAGH/EU




2) AM260HXVAGH/EU



6 Sound pressure level

Heat Pump - Standard type



Unit: dB(A)

Model	Pressure
AM080JXVAGH/EU	57.0
AM100JXVAGH/EU	58.0
AM120JXVAGH/EU	62.0
AM140JXVAGH/EU	61.0

Note


Measuring place: Anechoic chamber (conversion value)

These operation values were obtained in an anechoic room. Sound pressure level will vary depending on a factors such as the construction of the particular room where the equipment is installed.


Operation sound level may differ depending on operation and ambient conditions.

NC curve


1) AM080JXVAGH/EU




2) AM100JXVAGH/EU



3) AM120JXVAGH/EU




4) AM140JXVAGH/EU



6 Sound pressure level

Heat Pump - Standard type



Unit: dB(A)

Model	Pressure
AM160JXVAGH/EU	63.0
AM180JXVAGH/EU	64.0
AM200JXVAGH/EU	65.0
AM220JXVAGH/EU	66.0

Note


Measuring place: Anechoic chamber (conversion value)

These operation values were obtained in an anechoic room. Sound pressure level will vary depending on a factors such as the construction of the particular room where the equipment is installed.


Operation sound level may differ depending on operation and ambient conditions.

NC curve


1) AM160JXVAGH/EU




2) AM180JXVAGH/EU



3) AM200JXVAGH/EU




4) AM220JXVAGH/EU



6 Sound pressure level

Heat Pump - Standard type



Unit: dB(A)

Model	Pressure
AM240HXVAGH/EU	67.0
AM260HXVAGH/EU	67.0

Note


Measuring place: Anechoic chamber (conversion value)

These operation values were obtained in an anechoic room. Sound pressure level will vary depending on a factors such as the construction of the particular room where the equipment is installed.


Operation sound level may differ depending on operation and ambient conditions.

NC curve

1) AM240HXVAGH/EU




2) AM260HXVAGH/EU



6 Sound pressure level

Heat Recovery - High EER type



Unit: dB(A)

Model	Pressure
AM080JXVHGR/EU	57.0
AM100JXVHGR/EU	58.0
AM120JXVHGR/EU	62.0
AM140JXVHGR/EU	61.0

Note


Measuring place: Anechoic chamber (conversion value)

These operation values were obtained in an anechoic room. Sound pressure level will vary depending on a factors such as the construction of the particular room where the equipment is installed.


Operation sound level may differ depending on operation and ambient conditions.

NC curve


1) AM080JXVHGR/EU




2) AM100JXVHGR/EU



3) AM120JXVHGR/EU




4) AM140JXVHGR/EU



6 Sound pressure level

Heat Recovery - High EER type



Unit: dB(A)

Model	Pressure
AM160JXVHGR/EU	62.0
AM180JXVHGR/EU	63.0
AM200JXVHGR/EU	64.0
AM220JXVHGR/EU	65.0

Note


Measuring place: Anechoic chamber (conversion value)

These operation values were obtained in an anechoic room. Sound pressure level will vary depending on a factors such as the construction of the particular room where the equipment is installed.


Operation sound level may differ depending on operation and ambient conditions.

NC curve


1) AM160JXVHGR/EU




2) AM180JXVHGR/EU



3) AM200JXVHGR/EU



4) AM220JXVHGR/EU



7 Sound power level

Heat Pump - High EER type


Note

dBA = A-weighted sound power level.
Reference power : 1pW.
Measured according to ISO 3741.


Unit: dB(A)

Model	Power
AM080JXVHGH/EU	77.0
AM100JXVHGH/EU	79.0
AM120JXVHGH/EU	81.0
AM140JXVHGH/EU	81.0


1)AM080JXVHGH/EU




2)AM100JXVHGH/EU



3)AM120JXVHGH/EU



4)AM140JXVHGH/EU



7 Sound power level

Heat Pump - High EER type


Note

dBA = A-weighted sound power level.
Reference power : 1pW.
Measured according to ISO 3741.


Unit: dB(A)

Model	Power
AM160JXVHGH/EU	82.0
AM180JXVHGH/EU	85.0
AM200JXVHGH/EU	86.0
AM220JXVHGH/EU	88.0


1)AM160JXVHGH/EU




2)AM180JXVHGH/EU



3)AM200JXVHGH/EU



4)AM220JXVHGH/EU



7 Sound power level

Heat Pump - High EER type


Note

dBA = A-weighted sound power level.
Reference power : 1pW.
Measured according to ISO 3741.


Unit: dB(A)

Model	Power
AM240HXVAGH/EU	91.0
AM260HXVAGH/EU	91.0

1)AM240HXVAGH/EU



2)AM260HXVAGH/EU



7 Sound power level

Heat Pump - Standard type


Note

dBA = A-weighted sound power level.
Reference power : 1pW.
Measured according to ISO 3741.


Unit: dB(A)

Model	Power
AM080JXVAGH/EU	77.0
AM100JXVAGH/EU	79.0
AM120JXVAGH/EU	81.0
AM140JXVAGH/EU	81.0


1)AM080JXVAGH/EU




2)AM100JXVAGH/EU



3)AM120JXVAGH/EU



4)AM140JXVAGH/EU



7 Sound power level

Heat Pump - Standard type


Note

dBA = A-weighted sound power level.
Reference power : 1pW.
Measured according to ISO 3741.


Unit: dB(A)

Model	Power
AM160JXVAGH/EU	83.0
AM180JXVAGH/EU	86.0
AM200JXVAGH/EU	87.0
AM220JXVAGH/EU	89.0


1)AM160JXVAGH/EU




2)AM180JXVAGH/EU



3)AM200JXVAGH/EU



4)AM220JXVAGH/EU



7 Sound power level

Heat Pump - Standard type


Note

dBA = A-weighted sound power level.
Reference power : 1pW.
Measured according to ISO 3741.


Unit: dB(A)

Model	Power
AM240HXVAGH/EU	91.0
AM260HXVAGH/EU	91.0

1)AM240HXVAGH/EU



2)AM260HXVAGH/EU



7 Sound power level

Heat Recovery - High EER type


Note

dBA = A-weighted sound power level.
Reference power : 1pW.
Measured according to ISO 3741.


Unit: dB(A)

Model	Power
AM080JXVHGR/EU	77.0
AM100JXVHGR/EU	79.0
AM120JXVHGR/EU	81.0
AM140JXVHGR/EU	81.0


1)AM080JXVHGR/EU




2)AM100JXVHGR/EU



3)AM120JXVHGR/EU



4)AM140JXVHGR/EU



7 Sound power level

Heat Recovery - High EER type


Note

dBA = A-weighted sound power level.
Reference power : 1pW.
Measured according to ISO 3741.


Unit: dB(A)

Model	Power
AM160JXVHGR/EU	82.0
AM180JXVHGR/EU	85.0
AM200JXVHGR/EU	86.0
AM220JXVHGR/EU	88.0


1)AM160JXVHGR/EU




2)AM180JXVHGR/EU



3)AM200JXVHGR/EU




4)AM220JXVHGR/EU



8 Cycle diagram

Heat Pump

AM080JXV*GH/EU, AM100JXV*GH/EU, AM120JXV*GH/EU




Classification	Description
INV	Inverter Compressor
OFM	Outdoor Fan Motor
OHX	Outdoor Heat Exchanger
AC	Accumulator
OS	Oil Separator
IC	Intercooler
IPMC	IPM Cooler
CH	Crank Case Heater
HPS	High Pressure Sensor
LPS	Low Pressure Sensor
HPSW	High Pressure Switch
E_M	Main EEV
E_EV	EVI EEV
V_ES	EVI Solenoid Valve
V_EB	EVI Bypass Valve

Classification	Description
V_HG	Hot Gas Bypass Valve
V_4W	4way Valve
V_AR	Accumulator Oil Return Valve
CV_E	EEV Bypass Check Valve
CV_D	Discharge Check Valve
T_D	Discharge Temperature Sensor
T_S	Suction Temperature Sensor
T_CO	Condenser Out Temperature Sensor
T_EI	EVI In Temperature Sensor
T_EO	EVI Out Temperature Sensor
T_L	Liquid Tube Temperature Sensor
T_CT	Compressor Top Temperature Sensor
T_A	Ambient Temperature Sensor
SV_G	Gas Pipe Service Valve
SV_L	Liquid Pipe Service Valve

8 Cycle diagram

Heat Pump

AM140JXV*GH/EU




Classification	Description
INV	Inverter Compressor
OFM	Outdoor Fan Motor
OHX	Outdoor Heat Exchanger
AC	Accumulator
OS	Oil Separator
IC	Intercooler
IPMC	IPM Cooler
CH	Crank Case Heater
HPS	High Pressure Sensor
LPS	Low Pressure Sensor
HPSW	High Pressure Switch
E_M	Main EEV
E_EV	EVI EEV
V_ES	EVI Solenoid Valve
V_EB	EVI Bypass Valve

Classification	Description
V_HG	Hot Gas Bypass Valve
V_4W	4way Valve
V_AR	Accumulator Oil Return Valve
CV_E	EEV Bypass Check Valve
CV_D	Discharge Check Valve
T_D	Discharge Temperature Sensor
T_S	Suction Temperature Sensor
T_CO	Condenser Out Temperature Sensor
T_EI	EVI In Temperature Sensor
T_EO	EVI Out Temperature Sensor
T_L	Liquid Tube Temperature Sensor
T_CT	Compressor Top Temperature Sensor
T_A	Ambient Temperature Sensor
SV_G	Gas Pipe Service Valve
SV_L	Liquid Pipe Service Valve

8 Cycle diagram

Heat Pump

AM160JXV*GH/EU, AM180JXV*GH/EU, AM200JXV*GH/EU, AM220JXV*GH/EU




Classification	Description
INV	Inverter Compressor
OFM	Outdoor Fan Motor
OHX	Outdoor Heat Exchanger
AC	Accumulator
OS	Oil Separator
IC	Intercooler
IPMC	IPM Cooler
CH	Crank Case Heater
HPS	High Pressure Sensor
LPS	Low Pressure Sensor
HPSW	High Pressure Switch
E_M	Main EEV
E_EV	EVI EEV
V_ES	EVI Solenoid Valve
V_EB	EVI Bypass Valve

Classification	Description
V_HG	Hot Gas Bypass Valve
V_4W	4way Valve
V_AR	Accumulator Oil Return Valve
CV_E	EEV Bypass Check Valve
CV_D	Discharge Check Valve
T_D	Discharge Temperature Sensor
T_S	Suction Temperature Sensor
T_CO	Condenser Out Temperature Sensor
T_EI	EVI In Temperature Sensor
T_EO	EVI Out Temperature Sensor
T_L	Liquid Tube Temperature Sensor
T_CT	Compressor Top Temperature Sensor
T_A	Ambient Temperature Sensor
SV_G	Gas Pipe Service Valve
SV_L	Liquid Pipe Service Valve

8 Cycle diagram

Heat Pump

AM240HXVAGH/EU, AM260HXVAGH/EU




Classification	Description
INV	Inverter Compressor
OFM	Outdoor Fan Motor
OHX	Outdoor Heat Exchanger
AC	Accumulator
OS	Oil Separator
IC	Intercooler
IPMC	IPM Cooler
CH	Crank Case Heater
HPS	High Pressure Sensor
LPS	Low Pressure Sensor
HPSW	High Pressure Switch
E_M	Main EEV
E_EV	EVI EEV
V_ES	EVI Solenoid Valve
V_EB	EVI Bypass Valve

Classification	Description
V_HG	Hot Gas Bypass Valve
V_4W	4way Valve
V_AR	Accumulator Oil Return Valve
CV_E	EEV Bypass Check Valve
CV_D	Discharge Check Valve
T_D	Discharge Temperature Sensor
T_S	Suction Temperature Sensor
T_CO	Condenser Out Temperature Sensor
T_EI	EVI In Temperature Sensor
T_EO	EVI Out Temperature Sensor
T_L	Liquid Tube Temperature Sensor
T_CT	Compressor Top Temperature Sensor
T_A	Ambient Temperature Sensor
SV_G	Gas Pipe Service Valve
SV_L	Liquid Pipe Service Valve

8 Cycle diagram

Heat Recovery

AM080JXVHGR/EU, AM100JXVHGR/EU, AM120JXVHGR/EU




Classification	Description
INV	Inverter Compressor
OFM	Outdoor Fan Motor
OHX	Outdoor Heat Exchanger
AC	Accumulator
OS	Oil Separator
IC	Intercooler
IPMC	IPM Cooler
CH	Crank Case Heater
HPS	High Pressure Sensor
LPS	Low Pressure Sensor
HPSW	High Pressure Switch
E_M	Main EEV
E_EV	EVI EEV
V_MC	Main Cooling Valve
V_ES	EVI Solenoid Valve
V_EB	EVI Bypass Valve
V_HG1	Hot Gas Bypass Valve 1
V_HG2	Hot Gas Bypass Valve 2

Classification	Description
V_4W	4Way Valve
V_AR	Accumulator Oil Return Valve
V_OE	Outdoor EEV Valve
CV_E	EEV Bypass Check Valve
CV_D	Discharge Check Valve
CV_H	HR Check valve
CV_MC	Main Cooling Check Valve
T_D	Discharge Temp. Sensor
T_S1	Suction Temp. Sensor 1
T_S2	Suction Temp. Sensor 2
T_CO	Cond Out Temp. Sensor
T_EI	EVI In Temp. Sensor
T_EO	EVI Out Temp. Sensor
T_L	Liquid Tube Temp. Sensor
T_CT	Comp. Top Temp. Sensor
T_A	Ambient Temp. Sensor
SV_HG	Low Gas Pipe Service Valve
SV_LG	Ambient Temp. Sensor
SV_L	Liquid Pipe Service Valve

8 Cycle diagram

Heat Recovery

AM140JXVHGR/EU




Classification	Description
INV	Inverter Compressor
OFM	Outdoor Fan Motor
OHX	Outdoor Heat Exchanger
AC	Accumulator
OS	Oil Separator
IC	Intercooler
IPMC	IPM Cooler
CH	Crank Case Heater
HPS	High Pressure Sensor
LPS	Low Pressure Sensor
HPSW	High Pressure Switch
E_M	Main EEV
E_EV	EVI EEV
V_MC	Main Cooling Valve
V_ES	EVI Solenoid Valve
V_EB	EVI Bypass Valve
V_HG1	Hot Gas Bypass Valve 1
V_HG2	Hot Gas Bypass Valve 2

Classification	Description
V_4W	4Way Valve
V_AR	Accumulator Oil Return Valve
V_OE	Outdoor EEV Valve
CV_E	EEV Bypass Check Valve
CV_D	Discharge Check Valve
CV_H	HR Check valve
CV_MC	Main Cooling Check Valve
T_D	Discharge Temp. Sensor
T_S1	Suction Temp. Sensor 1
T_S2	Suction Temp. Sensor 2
T_CO	Cond Out Temp. Sensor
T_EI	EVI In Temp. Sensor
T_EO	EVI Out Temp. Sensor
T_L	Liquid Tube Temp. Sensor
T_CT	Comp. Top Temp. Sensor
T_A	Ambient Temp. Sensor
SV_HG	Low Gas Pipe Service Valve
SV_LG	Ambient Temp. Sensor
SV_L	Liquid Pipe Service Valve

8 Cycle diagram

Heat Recovery

AM160JXVHGR/EU, AM180JXVHGR/EU, AM200JXVHGR/EU, AM220JXVHGR/EU




Classification	Description
INV	Inverter Compressor
OFM	Outdoor Fan Motor
OHX	Outdoor Heat Exchanger
AC	Accumulator
OS	Oil Separator
IC	Intercooler
IPMC	IPM Cooler
CH	Crank Case Heater
HPS	High Pressure Sensor
LPS	Low Pressure Sensor
HPSW	High Pressure Switch
E_M	Main EEV
E_EV	EVI EEV
V_MC	Main Cooling Valve
V_ES	EVI Solenoid Valve
V_EB	EVI Bypass Valve
V_HG1	Hot Gas Bypass Valve 1
V_HG2	Hot Gas Bypass Valve 2

Classification	Description
V_4W	4Way Valve
V_AR	Accumulator Oil Return Valve
V_OE	Outdoor EEV Valve
CV_E	EEV Bypass Check Valve
CV_D	Discharge Check Valve
CV_H	HR Check valve
CV_MC	Main Cooling Check Valve
T_D	Discharge Temp. Sensor
T_S1	Suction Temp. Sensor 1
T_S2	Suction Temp. Sensor 2
T_CO	Cond Out Temp. Sensor
T_EI	EVI In Temp. Sensor
T_EO	EVI Out Temp. Sensor
T_L	Liquid Tube Temp. Sensor
T_CT	Comp. Top Temp. Sensor
T_A	Ambient Temp. Sensor
SV_HG	Low Gas Pipe Service Valve
SV_LG	Ambient Temp. Sensor
SV_L	Liquid Pipe Service Valve


9 Installation

1. Space requirement for installation

1) Single installation




<Case 1>




<Case 2>


2) Module installation



<Case 1>




<Case 2>



<Case 3>

▶ For <Case 1> or <Case 3>



- Height of the wall on the front side should not be higher than 1500mm.
- Height of the wall on the air inlet side should not be higher than 500mm.
- Height of the wall on the side is not limited.
- If the height of the wall exceeds by certain value (h_1 , h_2), additional clearance $[(h_1)/2, (h_2)/2]$: Half of the exceeded distance] should be added to the service space (S_1 , S_2)

✓ Note


- ◆ Space requirement was decided based on following conditions: Cooling mode, outdoor temperature of 35 °C. Larger space is required if the outdoor temperature is higher than 35 °C or if the place is heated easily by quantity of solar radiation.
- ◆ When you secure installation space, consider path for people and the direction of the wind.
- ◆ Secure installation space as shown in the below illustration, considering ventilation and the service space.
- ◆ If the installation space is narrow, installer or other worker may get injured during work and may also cause problem to the product.
- ◆ If you install multiple number of outdoor units in one space, make sure to secure enough ventilation space if there's any walls around the product that may disturb the air flow. If enough ventilation space is not secured, product may malfunction.
- ◆ You may install the outdoor units with 20mm of space between the product, but product's performance may decrease depending on the installation environment.

9 Installation


2. Base construction and installation of the outdoor unit

- ◆ Make sure that the height of the base ground is 200mm or higher to protect the outdoor unit from rain water or other external conditions. Also, install a draining pit around the base ground and connect the drain pipe to the drainage.
- ◆ Considering the vibration and weight of the outdoor unit, strength of the base ground must be strong to prevent noise and the top surface of it should be flat.
- ◆ Base ground should be 1.5 times larger than the bottom of the outdoor unit.
- ◆ Outdoor unit must be fixed firmly so that it can withstand the wind speed of 30m/s. If you cannot fix the outdoor unit on the base ground, fix it by side or use extra structure.
- ◆ In heating operation, defrost water may form so you must really care about the drainage and waterproofing the floor. To prevent defrost water from stagnating or freezing, construct a drainage with over 1/50 slope. (Ice may form on the floor in winter time.)
- ◆ It is necessary to add wire mesh or steel bar during concrete construction for the base ground to prevent damages or cracks.
- ◆ When installing multiple outdoor units at the same place, construct a H beam or an anti-vibration frame on the base ground to install the outdoor unit.
- ◆ After installing a H beam or an anti-vibration frame, apply corrosion protection and other necessary coating.
- ◆ When concrete construction for outdoor unit installation is completed, install an anti-vibration pad (t=20mm or more) or an anti-vibration frame to prevent vibration of the outdoor unit from transferring to the base ground.
- ◆ Place the outdoor unit on a H beam or an anti-vibration frame and fix it with the bolt, nut and washer. (The bearing force has to be over 3.5kN)


1) Base ground construction



2) Outdoor unit installation



3) Outdoor unit base mount and anchor bolt position






(Unit : mm)		
Classification	Small type	Large type
Models	AM080/100/120* <i>XV</i> * <i>G</i> *	AM140/160/180/200/220/240/260* <i>XV</i> * <i>G</i> *
A	880	1,295
B	740	1,150

* Refer to the blueprints in technical data book to make a holes for connecting the anti-vibration pad.

9 Installation

4) Examples of draining work

- ▶ Construct the drainage ditch with reinforced concretes and make sure that water-proofing work is done.
- ▶ For smooth draining of defrost water, make sure to apply 1/50 slope.
- ▶ Construct a drainage around the outdoor unit to prevent the defrost water (from the outdoor unit) from stagnating, overflowing or freezing near the installation space.
- ▶ When the outdoor unit is installed on the roof, check the strength and waterproof status of the roof.



(Unit : mm)



Classification	Small type	Large type
Models	AM080/100/120*XV*G*	AM140/160/180/200/220/240/260*XV*G*
A	940	1,350
B	740	1,150

9 Installation

5) Installing the wind/snow prevention duct

(1) Installing the outdoor unit around the obstacles

- ▶ It is necessary to install a wind/snow prevention duct (field supply) to direct exhaust from the fan horizontally, when it is difficult to provide a minimum space of 2m between the air outlet and a nearby obstacle.




(2) Installing the outdoor unit in cold region

- ▶ In cold regions with lots of snowfall, install a snow prevention duct, as a sufficient countermeasure, to prevent snow from accumulating on the outdoor unit. When the snow prevention duct is not installed, frost may accumulate on the heat exchanger and heating operation may not work normally.
- ▶ Air outlet of the duct should not be directed to the enclosed space.



Cautions regarding on installing the frame and selecting the base ground

- Height (h) of the frame and the base ground should be higher than the "heaviest expected snowfall".
- Area of the frame and the base ground should not be larger than the area of the outdoor unit. Snow may accumulate if the area of the frame or the base ground is larger.



9 Installation

(3) Installing the outdoor unit in windy region

- ▶ In windy regions such as near sea shores, protection wall or wind protection duct must be installed for normal operation of the outdoor unit. (Refer to the illustration of the snow prevention duct, for installing the wind protection duct.)
- ▶ Install the wind prevention duct with the consideration of major wind direction. If the direction of the discharge part is same as major direction of the wind, it could cause product's performance decrease.






CAUTION




Cautions regarding on installing the frame and selecting the base ground

- The base ground must be solid and the outdoor unit must be fixed with anchor bolts.
- Make sure to install outdoor unit in a place strong enough to withstand its weight. If the place cannot withstand the weight of the outdoor unit, outdoor unit may fall and cause personal injury.
- When installing on a rooftop subject to strong wind, countermeasures must be taken to prevent the unit from falling down.
- Use a frame that is resistant to corrosion.

(Unit : mm)



<AM080/100/120*XB*G*>



<AM140/160/180/200/220/240/260*XB*G*>

9 Installation


3. Refrigerant pipe installation

1) Refrigerant pipe work

- ▶ The length of refrigerant pipe should be as short as possible and the height difference between an indoor and outdoor unit should be minimized.
- ▶ Piping work must be done within allowable piping length, height difference, and the allowable length after branching.
- ▶ The pressure of the R-410A is high. Use only certified refrigerant pipe and follow the installation method.
- ▶ After installing the pipes, calculate the total length of the pipe to check if additional refrigerant is needed. When you need to charge the additional refrigerant, make sure to use R-410A refrigerant.
- ▶ Use clean refrigerant pipe and there shouldn't be any harmful ion, oxide, dust, iron content or moisture inside pipe.
- ▶ Use tools and accessories that fit on R-410A only

Tool	Installation process/purpose	Compatibility with conventional tool	
Pipe cutter	Refrigerant pipe installation	Pipe cutting	Compatible
Flaring tool		Pipe flaring	
Refrigerant machine oil		Apply refrigerant oil on flared part	Exclusive ether oil, ester oil, alkali benzene oil or synthetic oil
Torque wrench		Connect flare nut with pipe	Compatible
Pipe bender		Pipe bending	
Nitrogen gas		Prevent oxidation within the pipe	
Welder	Air tightness test	Pipe welding	
Manifold gage	Air tightness test ~ additional refrigerant charging	Vacuuming, charging refrigerant and checking operation	Need exclusive one to prevent mixture of R-22 refrigerant oil use and also the measurement is not available due to high pressure
Refrigerant charging hose			Need exclusive one since there is risk of refrigerant leakage or inflow of impurities
Vacuum pump	Pipe drying		Compatible (Use products which contain the check valve to prevent the oil from flowing backward into the outdoor unit.) Use the one that can be vacuumed up to -100.7kpa(5Torr).
Scale for refrigerant charging			Compatible
Gas leak detector		Gas leak test	Need exclusive one (Ones used for R-134a is compatible)
Flare nut	Must use the flare nut equipped with the product . Refrigerant leakage may occur when the conventional flare nut for R-22 is used		


2) Selecting refrigerant pipe



- ▶ Install the refrigerant pipe according to main pipe size of each outdoor unit capacity.
- ▶ When the pipe length (including elbow) between an outdoor unit and the farthest indoor unit exceeds 90m, you must increase the size of the pipe (main pipe) by one grade which connects between the outdoor unit to the first branch joint.
- ▶ For H/R model, When the pipe length (including elbow) between an outdoor unit and the farthest indoor unit exceeds 90m, you must increase the size of the liquid pipe by one grade among the pipes(main pipe) which connects between the outdoor unit to the first branch joint.

9 Installation

(1) Heat Pump



Ex.) 135.2 kW

Capacity (kW)	No.	Pipe size (mm)	
		Liquid pipe	Gas pipe
33.6kW	(1)	Ø 12.70	Ø 28.58
73.6kW	(2)	Ø 19.05	Ø 34.92
135.2kW	(3)	Ø 19.05	Ø 41.28

① Size of the pipe connected to the outdoor unit (A)

Select the size of the pipe according to the below table.

Outdoor unit capacity (kW)	*Maximum pipe length within 90m (Main pipe diameter)		*Maximum pipe length over 90m (Main pipe diameter)		
	Liquid pipe (mm)	gas pipe (mm)	Liquid pipe (mm)	gas pipe (mm)	
22.4 kW	Ø 9.52	Ø 19.05	Ø 12.70	Ø 22.22	
28.0 kW		Ø 22.22		Ø 25.40 ^{note1)}	
33.6 kW	Ø 12.70	Ø 28.58	Ø 15.88	Ø 28.58	
40.0 kW				Ø 19.05	Ø 31.75 ^{note2)}
45.0 kW					
50.4 kW	Ø 15.88	Ø 34.92	Ø 19.05	Ø 38.10 ^{note3)}	
56.0 kW					
61.6 kW	Ø 19.05	Ø 41.28	Ø 22.22	Ø 41.28	
67.2 kW					
72.8 kW ~ 84.0 kW	Ø 22.22	Ø 53.98	Ø 25.40 ^{note1)}	Ø 53.98	
89.6 kW ~ 95.2 kW					
101.6 kW	Ø 22.22	Ø 53.98	Ø 25.40 ^{note1)}	Ø 53.98	
106.6 kW ~ 135.2 kW					
140.2 kW ~ 168.2 kW	Ø 22.22	Ø 53.98	Ø 25.40 ^{note1)}	Ø 53.98	
173.6 kW ~ 224.8 kW					

*Maximum pipe length : The pipe length between an outdoor unit and the farthest indoor unit

② Size of the pipe between branch joints (B)

Select the pipe size according to the sum of indoor unit capacity which will be connected after the branch.


Indoor unit capacity (kW)	Branch pipe length within 45m		Branch pipe length between 45~90m	
	Liquid pipe (mm)	Gas pipe (mm)	Liquid pipe (mm)	Gas pipe (mm)
15.0 kW and below	Ø 9.52	Ø 15.88	Ø 12.70	Ø 19.05
Over 15.0 kW ~ 22.4 kW and below		Ø 19.05		Ø 22.22
Over 22.4 kW ~ 28.1 kW and below		Ø 22.22		Ø 25.40 ^{note1)}
Over 28.1 kW ~ 40.0 kW and below	Ø 12.70	Ø 28.58	Ø 15.88	Ø 28.58
Over 40.0 kW ~ 45.0 kW and below				Ø 31.75 ^{note2)}
Over 45.0 kW ~ 63.3 kW and below	Ø 15.88	Ø 34.92	Ø 19.05	Ø 38.10 ^{note3)}
Over 63.3 kW ~ 70.3 kW and below				
Over 70.3 kW ~ 98.4 kW and below	Ø 19.05	Ø 41.28	Ø 22.22	Ø 41.28
Over 98.4 kW ~ 135.2 kW and below				
Over 135.2 kW ~ 169.0 kW and below	Ø 22.22	Ø 53.98	Ø 25.40 ^{note1)}	Ø 53.98
Over 169.0 kW				

Note1) If Ø 25.40 pipe is not available on site, use Ø 28.58 pipe.

Note2) If Ø 31.75 pipe is not available on site, use Ø 34.92 pipe.

Note3) If Ø 38.10 pipe is not available on site, use Ø 41.28 pipe.

9 Installation



- ③ Size of the pipe between the branch joint and the indoor unit
Make a selection according to outdoor unit capacity.

Indoor unit capacity (kW)	Pipe size (O.D. mm)	
	Liquid pipe	Gas pipe
6.0 kW and below	Ø 6.35	Ø 12.70
7.1 kW ~ 16.0 kW and below	Ø 9.52	Ø 15.88
20.0 kW ~ 23.0 kW and below	Ø 9.52	Ø 19.05
Over 23.0 kW	Ø 9.52	Ø 22.22

- ④ Branch joint

▶ Branch joint between outdoor units (C)

Classification	Model name	Specification (kW)
Y-joint for outdoor unit (C)	MXJ-TA3419M	135.2 kW and below
	MXJ-TA4122M	Over 140.2 kW

▶ First branch joint (D)

Make a selection according to outdoor unit capacity.

Classification	Outdoor unit capacity (kW)	Model name of the branch joint
Y-joint (D)	40.0 kW and below	MXJ-YA2512M
	45.0 kW	MXJ-YA2812M
	50.4 kW ~ 67.2 kW	MXJ-YA2815M
	73.6 kW ~ 95.2 kW	MXJ-YA3419M
	101.6 kW ~ 135.2 kW	MXJ-YA4119M
	140.2 kW and over	MXJ-YA4422M

▶ Branch joint (E)

Select a branch joint according to the sum of indoor unit capacity which will be connected after the branch.

< Y-joint >


Classification	Model name	Specification (kW)
Y-joint (E)	MXJ-YA1509M	15.0 kW and below
	MXJ-YA2512M	Over 15.0 kW ~ 40.0 kW and below
	MXJ-YA2812M	Over 40.0 kW ~ 45.0 kW and below
	MXJ-YA2815M	Over 45.0 kW ~ 70.3 kW and below
	MXJ-YA3419M	Over 70.3 kW ~ 98.4 kW and below
	MXJ-YA4119M	Over 98.4 kW ~ 135.2 kW and below
	MXJ-YA4422M	Over 135.2 kW

< Distribution header >

Classification	Model name	Specification (kW)
Distribution header (E)	MXJ-HA2512M	45.0 kW and below (for 4 rooms)
	MXJ-HA3115M	70.3 kW and below (for 8 rooms)
	MXJ-HA3819M	Over 70.3 kW ~ 135.2 kW and below (for 8 rooms)

9 Installation

(2) Heat Recovery



Ex.) 135.2 kW

Capacity	No.	Pipe size (mm)		
		Liquid pipe	Gas pipe	High pressure gas pipe
33.6 kW	(1)	Ø 12.70	Ø 28.58	Ø 19.05
73.6 kW	(2)	Ø 19.05	Ø 34.92	Ø 28.58
135.2 kW	(3)	Ø 19.05	Ø 41.28	Ø 34.92

① Size of the pipe connected to the outdoor unit (A)

Select the size of the pipe according to the below table.

Outdoor unit capacity (kW)	Main pipe length within 90m			Size Up (Main pipe length over 90m)		
	Liquid pipe (mm)	Low pressure gas pipe (mm)	High pressure gas pipe (mm)	Liquid pipe (mm)	Low pressure gas pipe (mm)	High pressure gas pipe (mm)
22.4 kW	Ø 9.52	Ø 19.05	Ø 15.88	Ø 12.70	Ø 19.05	Ø 15.88
28.0 kW		Ø 22.22	Ø 19.05		Ø 22.22	Ø 19.05
33.6 kW	Ø 12.70	Ø 28.58	Ø 22.22	Ø 15.88	Ø 28.58	Ø 22.22
40.0 kW						
45.0 kW						
50.4 kW	Ø 15.88	Ø 28.58	Ø 28.58	Ø 19.05	Ø 28.58	Ø 28.58
56.0 kW						
61.6 kW	Ø 19.05	Ø 34.92	Ø 28.58	Ø 19.05	Ø 34.92	Ø 28.58
67.2 kW						
72.8 kW ~ 84.0 kW						
89.6 kW ~ 95.2 kW						
101.6 kW	Ø 22.22	Ø 41.28	Ø 34.92	Ø 22.22	Ø 41.28	Ø 34.92
106.6 kW ~ 135.2 kW						
140.2 kW ~ 168.2 kW						
173.6 kW ~ 224.8 kW	Ø 22.22	Ø 53.98	Ø 41.28	Ø 25.40	Ø 53.98	Ø 41.28

Note1) If Ø 25.40 pipe is not available on site, use Ø 28.58 pipe


※For HR model, only increase the size of the liquid pipe if pipe length exceeds 90m

② Size of the pipe between branch joints (B)

Select the pipe size according to the sum of indoor unit capacity which will be connected after the branch.

Indoor unit capacity (kW)	Pipe size (mm)		
	Liquid pipe	Low pressure gas pipe	High pressure gas pipe
15.0 kW and below	Ø 9.52	Ø 15.88	Ø 15.88
Over 15.0 kW ~ 22.4 kW and below		Ø 19.05	
Over 22.4 kW ~ 28.1 kW and below		Ø 22.22	
Over 28.1 kW ~ 33.6 kW and below	Ø 12.70	Ø 28.58	Ø 19.05
Over 33.6 kW ~ 45.0 kW and below			
Over 45.0 kW ~ 50.4 kW and below	Ø 15.88	Ø 34.92	Ø 22.22
Over 50.4 kW ~ 63.3 kW and below			
Over 63.3 kW ~ 70.3 kW and below			
Over 70.3 kW ~ 98.4 kW and below	Ø 19.05	Ø 41.28	Ø 28.58
Over 98.4 kW ~ 105.5 kW and below			
Over 105.5 kW ~ 135.2 kW and below			
Over 135.2 kW ~ 169.0 kW and below	Ø 22.22	Ø 53.98	Ø 34.92
Over 169.0 kW			

9 Installation



- ③ Size of the pipe between the branch joint and the indoor unit
Make a selection according to outdoor unit capacity.

Indoor unit capacity (kW)	Pipe size (O.D. mm)	
	Liquid pipe	Gas pipe
6.0 kW and below	∅ 6.35	∅ 12.70
7.1 kW ~ 16.0 kW and below	∅ 9.52	∅ 15.88
20.0 kW ~ 23.0 kW and below	∅ 9.52	∅ 19.05
Over 23.0 kW	∅ 9.52	∅ 22.22

- ④ Branch joint

► Branch joint between outdoor units (C)

Classification	Model name	Specification (kW)
Liquid/Low pressure Y-joint (C)	MXJ-TA3419M	135.2 kW and below
	MXJ-TA4122M	Over 140.2 kW
High pressure Y-joint (C)	MXJ-TA3100M	135.2 kW and below
	MXJ-TA3800M	Over 140.2 kW

► First branch joint (D)

Make a selection according to outdoor unit capacity.

Classification	Outdoor unit capacity (kW)	Model name of the branch joint
Liquid/Low pressure Y-joint (C)	40.0 kW and below	MXJ-YA2512M
	45.0 kW	MXJ-YA2812M
	50.4 kW ~ 67.2 kW	MXJ-YA2815M
	73.6 kW ~ 95.2 kW	MXJ-YA3419M
	101.6 kW ~ 135.2 kW	MXJ-YA4119M
	140.2 kW and over	MXJ-YA4422M
High pressure Y-joint (C)	22.4 kW	MXJ-YA1500M
	28.0 kW ~ 67.2 kW	MXJ-YA2500M
	73.6 kW ~ 135.2 kW	MXJ-YA3100M
	140.2 kW and over	MXJ-YA3800M


► Branch joint (E)

Select a branch joint according to the sum of indoor unit capacity which will be connected after the branch.

Classification	Model name	Specification (kW)
Y-joint (E)	MXJ-YA1509M	15.0 kW and below
	MXJ-YA2512M	Over 15.0 kW ~ 40.0 kW and below
	MXJ-YA2812M	Over 40.0 kW ~ 45.0 kW and below
	MXJ-YA2815M	Over 45.0 kW ~ 70.3 kW and below
	MXJ-YA3419M	Over 70.3 kW ~ 98.4 kW and below
	MXJ-YA4119M	Over 98.4 kW ~ 135.2 kW and below
	MXJ-YA4422M	Over 135.2 kW
Y-joint (E) (Only H/R)	MXJ-YA1500M	22.4 kW and below
	MXJ-YA2500M	Over 22.4 kW ~ 70.3 kW and below
	MXJ-YA3100M	Over 70.3 kW ~ 135.2 kW and below
	MXJ-YA3800M	Over 135.2 kW

9 Installation

(3) Additional refrigerant



► Basic amount of refrigerant within the outdoor unit (kg)

- Amount of additional refrigerant has to be calculated based on the sum of all liquid pipe length.

Classification	AM080*<i>XVAG</i>*	AM100*<i>XVAG</i>*	AM120*<i>XVAG</i>*	AM140*<i>XVAG</i>*	AM160*<i>XVAG</i>*	AM180*<i>XVAG</i>*
Basic type	5.5	5.5	6.5	7.7	7.7	8.4
Classification	AM200*<i>XVAG</i>*	AM220*<i>XVHG</i>*	AM240*<i>XVAG</i>*	AM260*<i>XVAG</i>*	AM080*<i>XVHG</i>*	AM100*<i>XVHG</i>*
Basic type	8.4	8.4	14.3	14.3	6.5	6.5
Classification	AM120*<i>XVHG</i>*	AM140*<i>XVHG</i>*	AM160*<i>XVHG</i>*	AM180*<i>XVHG</i>*	AM200*<i>XVHG</i>*	AM220*<i>XVHG</i>*
Basic type	6.5	7.7	7.7	8.4	8.4	8.4

► Amount of additional refrigerant depending on the pipe size (@)

- Amount of additional refrigerant has to be calculated based on the sum of all liquid pipe length.

- For the indoor unit already connected to EEV kit, the additional refrigerant charging is 0.01kg per meter regardless of the pipe size.

Size of liquid pipe	Ø 6.35	Ø 9.52	Ø 12.70	Ø 15.88	Ø 19.05	Ø 22.22	Ø 25.40	Ø 28.58
Additional amount (kg/m)	0.02	0.06	0.125	0.18	0.27	0.35	0.53	0.65

9 Installation

► Amount of additional refrigerant for each indoor unit (b)

Capacity (kW)	1.5	1.7	2.2	2.8	3.2	3.6	4.5	5.6	6	7.1	8.2	9	11.2	12.8	14	16	18	22	22.4	28	32	50	500 CMH	1000 CMH
Slim 1way cassette (JSF) (AM***FN1DEH*)			0.25	0.25		0.25																		
Interior 1way cassette (AM***HN1DEH*)		0.15	0.15																					
2way cassette (AM***FN2DEH*)								0.31		0.47														
4Way Casette S (AM***FN4DEH*)							0.45	0.45		0.45		0.45	0.57	0.69	0.69									
Floor Standing Unit (AM***FNFDEH*)						0.22		0.32		0.32														
ERV plus (AM***FNKDEH*)																							0.11	0.36
4way cassette S (600×600) (AM***FNNDEH*)	0.29		0.29	0.29		0.29	0.37	0.37	0.37															
Global duct-1 (AM***HNMPKH*)						0.22	0.22			0.22														
Global duct-2 (AM***HNMPKH*)				0.31	0.31							0.31												
Global duct-3 (AM***HNMPKH*)						0.38	0.38		0.38			0.38	0.38	0.38										
Slim duct (AM***FNLDEH*)	0.17	0.17	0.17			0.26	0.35	0.35		0.45		0.42	0.42	0.62	0.62									
MSP duct (AM***FNMDEH*)			0.24	0.24		0.24	0.28	0.28		0.28		0.32	0.54	0.68	0.68									
Ceiling (AM***FNCDEH* / AM***JNCDKH*)								0.39		0.39			0.56		0.95									
Console (AM***FNJDEH*)				0.27		0.27		0.27																
Neo forte (AM***FNTDEH*)	0.24		0.24	0.24		0.24		0.36		0.36														
Neo forte (with EEV) (AM***FNQDEH*)	0.34		0.34	0.34		0.34	0.51	0.51		0.51														
AR5000 (AM***JNADKH*)	0.16		0.16	0.19		0.25	0.25	0.52		0.52	0.52													
AR5000 (with EEV) (AM***JNVDKH*)	0.22		0.22	0.25		0.34	0.34	0.71		0.71	0.71													
HSP duct (AM***FNHDEH*)													0.68	0.68	0.68			1.18		1.18				
FRESH duct (AM***JNEPEH*)														0.68				1.18		1.18				
Big duct (AM***JNHFKH*)																	1.15		1.15					
Hydro Unit HE (AM***FNBD***)																0.6						0.7	1.2	
Hydro Unit HT (AM***FNBF***)																								
MCU (MCU-S*NEE*N)												0.6	note1)											
												0.50												

► If AHU kit is included among the indoor units, you must add 0.063kg of refrigerant for every 1kW of the AHU capacity increase.

► Method to calculate total amount of additional refrigerant

- Amount of additional refrigerant depending on the pipe length (a)

- Amount of additional refrigerant for each indoor unit (b) = Σ(Amount of additional refrigerant for each connected indoor unit)

Refer to the table

- Total amount of additional refrigerant = a+b

Sum of total amount of additional refrigerant and the basic amount of refrigerant should not exceed 100kg. If the refrigerant exceeds 100kg, separate the module so that weight of the refrigerant doesn't exceed 100kg.

Ex.) For AM200FXVAGT, basic amount of refrigerant is 8.4kg, therefore total amount of additional refrigerant (a+b) should not exceed 91.6 kg.

Additional refrigerant for Duct S is separated by size

: Global duct-1(850mmx250mmx700mm), Global duct-2(1200mmx250mmx700mm), Global duct-3(1300mmx300mmx700mm)

9 Installation

► Example of refrigerant calculation for HP models

Classification	Size of liquid pipe	Length (m)	Unit amount of refrigerant (kg/m)	Amount of additional refrigerant (kg)	Total amount of additional refrigerant (kg)
				×	Σ(×)
Liquid pipe ()	∅ 6.35	35	0.02	0.7	5.575
	∅ 9.52	50	0.06	3.0	
	∅ 12.70	15	0.125	1.875	

Classification	Model name of indoor unit	Number of units	Unit amount of refrigerant (kg/EA)	Amount of additional refrigerant (kg)	Total amount of additional refrigerant (kg)
				×	Σ(×)
Indoor unit ()	4way cassette (AM071FN4DEH*)	4	0.45	1.80	3.10
	Slim duct (AM056FNLDEH*)	2	0.35	0.70	
	Slim duct (AM045FNLDEH*)	1	0.35	0.35	
	1way cassette (AM036FN1DEH*)	1	0.25	0.25	

- Total amount of refrigerant (@+b) = 5.575+3.10 = 8.675 (kg)

► Example of refrigerant calculation for HR models

Classification	Size of liquid pipe	Length (m)	Unit amount of refrigerant (kg/m)	Amount of additional refrigerant (kg)	Total amount of additional refrigerant (kg)
				×	Σ(×)
Liquid pipe ()	∅ 6.35	15	0.02	0.3	11.965
	∅ 9.52	112	0.06	6.72	
	∅ 12.70	25	0.125	3.125	
	∅ 15.88	10	0.18	1.8	
	∅ 6.35 (EEV Kit ~ indoor unit)	2	0.01	0.02	

Classification	Model name of indoor unit	Number of units	Unit amount of refrigerant (kg/EA)	Amount of additional refrigerant (kg)	Total amount of additional refrigerant (kg)
				×	Σ(×)
Indoor unit ()	4way cassette (AM071FN4DEH*)	5	0.45	2.25	4.66
	4way cassette (AM112FN4DEH*)	2	0.57	1.14	
	Neo forte (AM028FNTDEH*)	1	0.27	0.27	
	MCU	2	0.5	1	

- Total amount of refrigerant (@+b) = 11.965+4.66 = 16.625 (kg)

9 Installation

3) Temper grade and minimum thickness of the refrigerant pipe

Outer diameter (mm)	Minimum thickness (mm)	Temper grade
Ø 6.35	0.70	Annealed
Ø 9.52	0.70	
Ø 12.70	0.80	
Ø 15.88	1.00	
Ø 19.05	0.90	Drawn
Ø 22.22	0.90	
Ø 25.40	1.00	
Ø 28.58	1.10	
Ø 31.75	1.10	
Ø 34.92	1.21	
Ø 38.10	1.35	
Ø 41.28	1.43	
Ø 44.45	1.60	
Ø 50.80	2.00	
Ø 53.98	2.10	


※For pipes larger than Ø 19.05, drawn type (C1220T-1/2H or C1220T-H) type copper pipe must be used. If a annealed type (C1220T-O) copper pipe is used, pipe may break due to its low pressure resistance and cause personal injury.

9 Installation


4) Examples of refrigerant pipe installation

(1) Heat Pump

<Using Y-joint>




<Using distribution header>



(2) Heat Recovery

<Using Y-joint>



9 Installation

5) Allowable length of the refrigerant pipe and the installation examples

(1) Heat Pump


Classification	Single Installation	Module installation
Installing only with Y-joint		
Installing with Y-joint and distribution header		
Installing only with distribution header		

Classification				Example	Remarks	
Maximum allowable length of pipe	Outdoor unit ~ Indoor unit	Actual length (Equivalent length)	200m and below (220m and below)	Installing only with Y-joint	$a+b+c+d+e+f+g+p \leq 200\text{m}(220\text{m})$	Equivalent length Y-joint: 0.5 m, Distribution header: 1 m
				Installing with Y-joint and distribution header	$a+b+h \leq 200\text{m} (220\text{m}),$ $a+i+k \leq 200\text{m} (220\text{m})$	
				Installing only with distribution header	$a+i \leq 200\text{m} (220\text{m})$	
	Outdoor unit ~ Outdoor unit (Module installation)	Pipe length	10 m or less	$r \leq 10\text{ m}, s \leq 10\text{ m}, t \leq 10\text{ m}$		
			Equivalent length	13 m or less		$r \leq 13\text{ m}, s \leq 13\text{ m}, t \leq 13\text{ m}$
			Total length of pipe (m)	1,000 m or less		Installing only with Y-joint
			Installing with Y-joint and distribution header	$a+b+c+d+e+f+g+p+h+i \leq 1000\text{m}$	-	
			Installing only with distribution header	$a+b+c+d+e+f+g+p+h+i \leq 1000\text{m}$	-	

9 Installation

Classification			Example	Remarks	
Maximum allowable height difference of pipe	Outdoor unit ~ Indoor unit	110/40m <small>Note 2)</small>	H1 ≤ 110/40m		
	Indoor unit ~ Indoor unit	50m or less	H2 ≤ 50m		
But, when AM***FNQDEH* is installed, H2 is 15 m or less					
Maximum allowable length after branch joint	First branch joint ~ Farthest Indoor unit	Pipe length	45 m or less	b+c+d+e+f+g+p ≤ 45m, i ≤ 45 m	-
			45 m~90 m <small>Note 1)</small>	Required conditions must be satisfied	Exclude H/R

EEV kit		Model name		Remarks	
EEV kit ~ Indoor unit	Actual pipe length	2 m	MEV-E24SA	1 indoor	Apply to products without EEV (Wall mount & ceiling)
			MEV-E32SA		
	20 m or less	2 indoor	MXD-E24K132A		
			MXD-E24K200A		
			MXD-E32K200A		
		3 indoor	MXD-E24K232A		
			MXD-E24K300A		
			MXD-E32K224A		
		MXD-E32K300A			


Classification	Condition	Example
First branch joint ~ Farthest Indoor unit	$45m \leq b+c+d+e+f+g+p \leq 90m$: branch pipes (b, c, d, e, f, g) size must be increased by 1 grade	
Total length of extended pipe	If the size of pipe (main pipe), between the first branch joint and the outdoor unit, is not increased by 1 grade, $a+(b+c+d+e+f+g) \times 2 + h+i+j+k+l+m+n+p \leq 1000$ m	
	If the size of pipe (main pipe), between the first branch joint and the outdoor unit, is increased by 1 grade, $(a+b+c+d+e+f+g) \times 2 + h+i+j+k+l+m+n+p \leq 1000$ m	
Each Y-joint ~ Each indoor unit	$h, i, j, \dots p \leq 45$ m	
Difference between the distance of the outdoor unit to the farthest indoor unit and nearest indoor unit $\leq 45m$, $(a+b+c+d+e+g+p)-(a+h) \leq 45m$		


Note 1) Required condition

Note 2) When indoor unit is located at higher level than outdoor unit, allowable height difference is 40m, but when the indoor unit is located at lower level than outdoor unit, allowable height difference is 110m (If the height difference is over 50m, decide if you need to install PDM kit)
 Model name of the PDM kit: MXD-A38K2A, MXDA12K2A, MXD-A58K2A

9 Installation

(2) Heat Recovery



Items			Examples		Remarks	
Max. piping length	Outdoor ~ Indoor unit	Piping (Equivalent piping)	200 m below (220 m below)	Using MCU only $a+g \leq 200 \text{ m (220 m)}$	Equivalent pipe length Y joint : 0.5 m Header : 1 m MCU : 1 m	
				Using Y-joint and MCU $a+g+m \leq 200 \text{ m (220 m)}$		
		Total piping	1000 m below	Using MCU only $a+b+c+d+e+f+g \leq 1000 \text{ m}$	-	
				Using Y-joint and MCU $a+b+c+d+e+f+g+p+h+i+j+k+m \leq 1000 \text{ m}$	-	
Outdoor unit ~ Outdoor unit (Module installation)	Piping	10 m below	$r \leq 10, s \leq 10, t \leq 10 \text{ m}$			
	Equivalent piping	13 m below	$r \leq 13, s \leq 13, t \leq 13 \text{ m}$			
Level difference	Outdoor ~ Indoor unit	Piping	110 m / 40 m ^{Note1)}	$H1 \leq 110 \text{ m/40 m}$		-
	Indoor ~ Indoor unit	Piping	15 m below	$H2 \leq 15 \text{ m}$		-
	MCU ~ MCU	Piping	15 m below	$H4 \leq 15 \text{ m}$		-
Allowable length after branch	The first branch ~ the farthest indoor unit	Piping	45 m below	Using MCU only	45 m	-
				Using Y-joint and MCU	$g+m \leq 45 \text{ m}$	

Distribution kit			Model		Remarks
Allowable	From distribution kit to indoor unit	2 m	MEV-E24SA, MEV-E32SA (For 1 indoor unit)		For wall-mounted & ceiling indoor unit

Note 1) As an outdoor unit is located in a lower position than indoor unit, level difference is 40 m. If outdoor unit is located in a higher position than indoor unit, level difference is 110 m or under. (If the level difference is higher than 50 m, make a decision simulating by PDM kit installation guide software whether the PDM kit should be installed or not.)




*PDM kit: Pressure Drop Modulation kit

※Total refrigerant amount of the system must be less than 100 kg. If total refrigerant amount of system is over than 100 kg, the system has to be divided into smaller system, each less than 100 kg.




9 Installation


6) Installing the MCU

(1) MCU specification

Model	MCU-S6NEE1N	MCU-S4NEE1N	MCU-S4NEE2N
Exterior of MCU			
Number of connectable indoor units	Up to 6 units	Up to 4 units	Up to 2 units ※ Refer the detail information of installation manual
Maximum capacity of connectable indoor units	56 kW	56 kW	56 kW

(2) Installing the indoor units

Model	MCU-S6NEE1N	MCU-S4NEE1N	MCU-S4NEE2N
Example installing			
Installing indoor units	<p>The indoor unit's capacity which is under 14kW, can be connected in the MCU. Do not connect the indoor unit's capacity exceeds 14kW.</p> <p>Single capacity range under 10.0kW</p> <ul style="list-style-type: none"> - Connect the liquid, gas pipe of indoor unit to each single port in MCU. <p>Single capacity range between 11.2kW to 14.0kW</p> <ul style="list-style-type: none"> - Join two ports in the MCU with offered Y-connector(liquid, gas), then connect to indoor unit as above. <p>* Reference of continuous cooling.</p> <p>In case of continuous cooling at below -5 °C(23 °F) ambient condition, join two ports in the MCU with offered Y-connector, then connect to indoor unit even though unit's capacity is between 5.0kW to 10.0kW.</p> <p>Option switch and key function needs to be set. Detail information refer to pages 87~89.</p>		<p>The indoor unit's capacity which is greater than or equal to 11.2kW, can be connected in the MCU. Do not connect the indoor unit's capacity not exceeding 11.2kW.</p> <p>Single capacity range between 11.2kW to 28.0kW</p> <ul style="list-style-type: none"> - Join two ports in the MCU with offered Y-connector(liquid, gas), then connect to indoor unit as above.



9 Installation

4. Electrical wiring work

1) Specification of the circuit breaker and power cable

Heat Pump - High EER type

Model	MCA	MFA
AM080JXVHGH/EU	22.5	30
AM100JXVHGH/EU	29.9	40
AM120JXVHGH/EU	31.3	40
AM140JXVHGH/EU	31.3	40
AM160JXVHGH/EU	40	40
AM180JXVHGH/EU	48.9	50
AM200JXVHGH/EU	52.5	75
AM220JXVHGH/EU	55.6	75
AM240HXVAGH/EU	60.5	75
AM240JXVHGH/EU*	55	75
AM260HXVAGH/EU	63.8	75
AM260JXVHGH/EU*	55	75
AM280JXVHGH1EU	71.3	75
AM300JXVHGH1EU	80.2	90
AM320JXVHGH1EU	83.8	90
AM340JXVHGH1EU	86.9	90
AM360JXVHGH1EU	86.9	90
AM380JXVHGH1EU	95.6	100
AM400JXVHGH1EU	95.1	100
AM400JXVHGH1EU*	93.5	100
AM420JXVHGH1EU	108.1	125
AM440JXVHGH1EU	111.2	125
AM460JXVHGH1EU	118.2	125
AM480JXVHGH1EU	118.2	125
AM500JXVHGH1EU	126.9	150
AM520JXVHGH1EU	135.8	150
AM540JXVHGH1EU	139.4	150
AM560JXVHGH1EU	142.5	150
AM580JXVHGH1EU	142.5	150
AM600JXVHGH1EU	151.2	200
AM620JXVHGH1EU	161.9	200
AM640JXVHGH1EU	163.7	200
AM660JXVHGH1EU	166.8	200
AM680JXVHGH1EU	173.8	200
AM700JXVHGH1EU	173.8	200
AM720JXVHGH1EU	182.5	200
AM740JXVHGH1EU	191.4	200
AM760JXVHGH1EU	195	200
AM780JXVHGH1EU	198.1	200
AM800JXVHGH1EU	198.1	200

9 Installation

Heat Pump - High EER type (Compact)

Model	MCA	MFA
AM360JXVHGH2EU	88	100
AM380JXVHGH2EU	91.3	100
AM460JXVHGH2EU	110	125
AM480JXVHGH2EU	112.8	125
AM500JXVHGH2EU	124.3	150
AM520JXVHGH2EU	127.6	150
AM580JXVHGH2EU	137.5	150
AM600JXVHGH2EU	140.3	200
AM620JXVHGH2EU	151.8	200
AM640JXVHGH2EU	155.1	200
AM680JXVHGH2EU	158.4	200
AM700JXVHGH2EU	161.7	200
AM720JXVHGH2EU	173.3	200
AM740JXVHGH2EU	176.6	200
AM760JXVHGH2EU	188.1	200
AM780JXVHGH2EU	191.4	200

9 Installation

Heat Pump - Standard type

Model	MCA	MFA
AM080JXVAGH/EU	22.5	30
AM100JXVAGH/EU	29.9	40
AM120JXVAGH/EU	31.3	40
AM140JXVAGH/EU	31.3	40
AM160JXVAGH/EU	40	40
AM180JXVAGH/EU	48.9	50
AM200JXVAGH/EU	52.5	75
AM220JXVAGH/EU	55.6	75
AM240HXVAGH/EU	60.5	75
AM260HXVAGH/EU	63.8	75
AM280JXVAGH1EU	71.3	75
AM300JXVAGH1EU	80.2	90
AM320JXVAGH1EU	83.8	90
AM340JXVAGH1EU	86.9	90
AM360JXVAGH1EU	86.9	90
AM380JXVAGH1EU	95.6	100
AM400JXVAGH1EU	95.1	100
AM420JXVAGH1EU	108.1	125
AM440JXVAGH1EU	111.2	125
AM460JXVAGH1EU	118.2	125
AM480JXVAGH1EU	118.2	125
AM500JXVAGH1EU	126.9	150
AM520JXVAGH1EU	135.8	150
AM540JXVAGH1EU	139.4	150
AM560JXVAGH1EU	142.5	150
AM580JXVAGH1EU	142.5	150
AM600JXVAGH1EU	151.2	150
AM620JXVAGH1EU	160.1	200
AM640JXVAGH1EU	163.7	200
AM660JXVAGH1EU	166.8	200
AM680JXVAGH1EU	173.8	200
AM700JXVAGH1EU	173.8	200
AM720JXVAGH1EU	182.5	200
AM740JXVAGH1EU	191.4	200
AM760JXVAGH1EU	195	200
AM780JXVAGH1EU	198.1	200
AM800JXVAGH1EU	198.1	200

9 Installation

Heat Pump - Standard type (Compact)

Model	MCA	MFA
AM360JXVAGH2EU	109.4	125
AM380JXVAGH2EU	112.7	125
AM460JXVAGH2EU	116.3	125
AM480JXVAGH2EU	119.4	125
AM500JXVAGH2EU	124.3	150
AM520JXVAGH2EU	127.6	150
AM580JXVAGH2EU	165.2	200
AM600JXVAGH2EU	168.3	200
AM620JXVAGH2EU	173.2	200
AM640JXVAGH2EU	176.5	200
AM680JXVAGH2EU	171.7	200
AM700JXVAGH2EU	175	200
AM720JXVAGH2EU	179.9	200
AM740JXVAGH2EU	183.2	200
AM760JXVAGH2EU	188.1	200
AM780JXVAGH2EU	191.4	200

9 Installation


Heat Recovery - High EER type

Model	MCA	MFA
AM080JXVHGR/EU	22.5	30
AM100JXVHGR/EU	29.9	40
AM120JXVHGR/EU	31.3	40
AM140JXVHGR/EU	31.3	40
AM160JXVHGR/EU	40	40
AM180JXVHGR/EU	48.9	50
AM200JXVHGR/EU	52.5	75
AM220JXVHGR/EU	55.6	75
AM240JXVHGR1EU	60.5	75
AM260JXVHGR1EU	63.8	75
AM280JXVHGR1EU	71.3	75
AM300JXVHGR1EU	80.2	90
AM320JXVHGR1EU	83.8	90
AM340JXVHGR1EU	86.9	90
AM360JXVHGR1EU	86.9	90
AM380JXVHGR1EU	95.6	100
AM400JXVHGR1EU	95.1	100
AM420JXVHGR1EU	108.1	125
AM440JXVHGR1EU	111.2	125
AM460JXVHGR1EU	118.2	125
AM480JXVHGR1EU	118.2	125
AM500JXVHGR1EU	126.9	150
AM520JXVHGR1EU	135.8	150
AM540JXVHGR1EU	139.4	150
AM560JXVHGR1EU	142.5	150
AM580JXVHGR1EU	142.5	150
AM600JXVHGR1EU	151.2	200
AM620JXVHGR1EU	160.6	200
AM640JXVHGR1EU	163.7	200
AM660JXVHGR1EU	166.8	200
AM680JXVHGR1EU	173.8	200
AM700JXVHGR1EU	173.8	200
AM720JXVHGR1EU	182.5	200
AM740JXVHGR1EU	191.4	200
AM760JXVHGR1EU	195	200
AM780JXVHGR1EU	198.1	200
AM800JXVHGR1EU	198.1	200

9 Installation

- ※ When installing outdoor units in module, select the power supply cable according to the sum of outdoor unit capacity. (Refer to the table for each model)
- ※ Power Supply cords of parts of appliances for outdoor use shall not be lighter than polychloroprene sheathed flexible cord. (Code designation IEC:60245 IEC 66 / CENELEC: H07RN-F)

Ex) AM500*XVA



- This device is intended for the connection to a power supply system with a maximum permissible system impedance shown in the table (on the left page) at the interface point (power service box) of the user's supply.
- The user must ensure that this device is connected only to a power supply system which fulfills the requirement above. If necessary, the user can ask the public power supply company for the system impedance at the interface point.
- This equipment complies with IEC 61000-3-12 provided that the short-circuit power S_{sc} is greater than or equal to $S_{sc}(*2)$ at the interface point between the user's supply and the public system. It is the responsibility of the installer or user of the equipment to ensure, by consultation with the distribution network operator if necessary, that the equipment is connected only to a supply with a short-circuit power S_{sc} greater than or equal to $S_{sc}(*2)$.

[$S_{sc}(*2)$]


Model	S_{sc} [MVA]	Model	S_{sc} [MVA]
AM080JXVHG*	3.3	AM180JXVHG*	7.6
AM100JXVHG*	4.5	AM200JXVHG*	8.1
AM120JXVHG*	5.3	AM220JXVHG*	8.6
AM140JXVHG*	5.3	AM240HXVAG*	11.7
AM160JXVHG*	6.8	AM260HXVAG*	8.6

Model	S_{sc} [MVA]	Model	S_{sc} [MVA]
AM080JXVAG*	3.3	AM160JXVAG*	6.8
AM100JXVAG*	4.5	AM180JXVAG*	7.6
AM120JXVAG*	5.3	AM200JXVAG*	8.1
AM140JXVAG*	5.3	AM220JXVAG*	8.6



Caution for electrical work

- You must install ELCB or MCCB + ELB
 - ELCB: Earth leakage breaker
 - MCCB: Molded case circuit breaker
 - ELB: Earth leakage breaker
- Do not operate the outdoor unit before completing the refrigerant pipe work.
- Do not disconnect or change the cable inside the product. It may cause damage to the product.
- Specification of the power cable is selected based on following installation condition; culvert installation/ ambient temperature 30 °C/ single multi conductor cables. If the condition is different from the ones stated, please consult an electrical installation expert and re-select the power cable.
 - If the length of power cable exceed 50m, re-select the power cable considering the voltage drop.
- Use a power cable made out of incombustible material for the insulator (inner cover) and the sheath (outer cover).
- Do not use the power cable with the core wire exposed due to insulator damage occurred during removal of the sheath. When the core wire is exposed, it may cause fire.




<The example of exposed core wire>

9 Installation

2) Power wiring diagram


(1) Supplying 3 phase 4 wires (380-415 V~)

- ▶ Connect a power cable of the outdoor unit after checking that R-S-T-N (3 phase 4 wire) is properly connected. (If the 380-415 V power is supplied to the N phase, PCB and other electrical part will be damaged.)
- ▶ Communication cable between indoor and outdoor units and communication cable between outdoor units has no polarity.
- ▶ Arrange the cables with a cable tie.
- ※ ELCB and ELB must be installed since there is risk of electric shock or fire when they are not installed.



3) Installing the Solution device


- ▶ When the number of indoor units installed with the outdoor unit is 16 or less




9 Installation

4) Connecting the MCU


(1) Example 1



(2) Example 2



- ▶ **A** Power must be supplied to the MCU separately from the outdoor unit.
- ▶ **B** Connect the communication cable of the outdoor unit (F1, F2) to the communication cable of the MCU (F1, F2)



9 Installation

5) Grounding work

(1) Grounding the power cable

- ▶ The standard of grounding may vary according to the rated voltage and installation place of the air conditioner.
- ▶ Ground the power cable according to the following table.

Installation place	Power condition	
	Voltage to ground is lower than 150V	Voltage to ground is over 150V
High humidity	Must perform the grounding work 3. ^{Note 1)} (Including the case where earth leakage breaker is installed)	
Average humidity	Perform grounding work 3. ^{Note 1)}	Must perform the grounding work 3. ^{Note 1)} (Including the case where earth leakage breaker is installed)
Low humidity	Perform grounding work 3, if possible, for your safety. ^{Note 2)}	

Note 1) About grounding work 3.

- Grounding work must be done by an expert (with qualification).
- Check if the grounding resistance is lower than 100Ω. When installing a earth leakage breaker (that can cut the electric circuit within 0.5 second in case of a short circuit), allowable grounding resistance should be 30~500Ω.


Note 2) Grounding at dry place

- The grounding resistance should be lower than 100Ω. Even in worst case, grounding resistance should be lower than 250Ω.


(2) Performing the grounding work

- ▶ Use a rated grounding cable by referring to the specification of the electric cable for the outdoor unit.

※When using the exclusive grounding terminal
(When the grounding terminal is already built on the house)



※When using grounding of the switch board



SAMSUNG

2015.09
Ver.1.3

Samsung Electronics Co., LTD.
B2B PM / SE

Head Office (Suwon Korea) 129, Samsung-Ro, Yeongtong-Gu, Suwon City, Gyeonggi-Do, Korea 443-742
Website : www.samsung.com Email : airconditioner@samsung.com
Images and data in this book may subject to change without prior notice.

SAMSUNG