

Access Point

WEA302i



Radio Specifications	802.11a/b/g/n, Dual concurrent radio 2 X 2 MIMO, 2 spatial streams PHY data rates up to 300 Mbps 802.11n high throughput (HT20/40) Dynamic frequency selection (DFS)				
Operation Mode	Controller-based, Standalone mode				
Supported Wireless LAN Controller	WEC8500 series WEC8050 series				
RF Monitoring	Dedicated RF and security monitoring module in AP				
Data Rates	802.11a: 6, 9, 12, 18, 24, 36, 48, and 54 Mbps 802.11g: 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48 and 54 Mbps 802.11n: MCS 0 to MCS 15 (6.5 Mbps to 300 Mbps)				
Frequency	802.11b/g/n: 2.412 GHz to 2.472 GHz 13 CH 802.11a/n: 5.180 GHz to 5.825 GHz 24 CH * Available Channels are Compliant with local regulations				
Maximum Transmit Power	20 dBm with 2 streams (17 dBm/Path) * The maximum transmission power will vary by channel and according to individual regulations				
Receive Sensitivity	802.11n	2.4 GHz		5 GHz	
	MCS Index	HT20	HT20	HT40	
	MCS 0	-96	-96	-93	
	MCS 1	-96	-96	-91	
	MCS 2	-94	-93	-89	
	MCS 3	-90	-89	-85	
	MCS 4	-87	-86	-82	
	MCS 5	-83	-82	-78	
	MCS 6	-81	-80	-77	
	MCS 7	-80	-78	-75	
	MCS 8	-95	-95	-91	
	MCS 9	-92	-91	-88	
	MCS 10	-90	-89	-86	
	MCS 11	-87	-86	-82	
	MCS 12	-83	-83	-79	
	MCS 13	-78	-78	-74	
	MCS 14	-77	-76	-73	
	MCS 15	-75	-75	-72	
		802.11 b			
	1 Mbps	-104			
11 Mbps	-94				
	802.11 a/g				
6 Mbps	-96	-95			
54 Mbps	-82	-81			

* Maximum capability of the hardware provided

Access Point

Integrated Antenna	2.4 GHz: 4 dBi Intelligent Beam Selectable Antenna (IBSA) 5 GHz: 5.5 dBi Intelligent Beam Selectable Antenna (IBSA)
Interfaces	10/100/1000 BASE-T ethernet autosensing (RJ-45) Management console port (RJ-45)
Dimensions	Diameter X Height: 174 mm X 34.1 mm
Weight	650 g
Environmental	Storage temperature: -20 °C to 70 °C Operating temperature: 0 °C to 45 °C Operating humidity: 5 to 95 % (noncondensing)
Input Power Requirements	IEEE 802.3af PoE: 44 to 57 VDC
Powering Options	Local power supply: 100 to 250 VAC, 50/60 Hz
Power Draw	10.55 W
Compliance Standards	<ul style="list-style-type: none">• Safety: UL 60950-1 UL 2043 IEC 60950-1 EN 60950-1EMI and susceptibility (Class B) FCC Part 15.107 and 15.109 EN 301 489-1 and -17 (Europe) KN 301 489-1 / KN 301 489-17 (Korea)• Radio approvals: FCC Part 15.247, 15.407 EN 300 328, EN 301 893 (Europe) Radio Equipment Specifications• EAP type (s): Extensible Authentication Protocol-Transport Layer Security (EAP-TLS) EAP-Tunneled TLS (TTLS) or Microsoft Challenge Handshake Authentication Protocol Version 2 (MSCHAPv2) Protected EAP (PEAP) v0 or EAP-MSCHAPv2 Extensible Authentication Protocol-Flexible Authentication via Secure Tunneling (EAP-FAST) PEAPv1 or EAP-Generic Token Card (GTC) EAP-Subscriber Identity Module (SIM) Multimedia: Wi-Fi Multimedia (WMM) WMM-PS
Part Number	<ul style="list-style-type: none">• AP type WDS-A302CI / KOR (Korea) WDS-A302CI / XAR (US & Canada) WDS-A302CI / EUS (EU)• Mounting kit WDS-A300WK / KOR, / XAR, / EUS: Wall mounting WDS-A300CK / KOR, / XAR, / EUS: Ceiling mounting

SAMSUNG